

Floor

Grey antiskid GRP reinforced for trolleys
No wheel recess under the floor
2 Drain holes with siphon Ø 40 front L&R

Inside equipments

250 mm Aluminium kick strip

1 universal steel Combi-rail 3009 (surface mounted) on side walls

General aspect

Bodywork : standard white RAL 9016
Outside capping in anodized aluminium
With reflective stickers

Fridge equipments

Front bulkhead reinforced + aperture for THERMO KING TX-800 R50
With ATP blue stickers

Other equipments

2 Rubber buffers 490*110 on the rear frame
2 Rubber buffers 310*80 on the chassis
2 Spring door retainers

2 Internal LED roof lights **with 20 mn timer**

2 multifunction LED lights on top rear frame

FRIDGE UNIT

THERMO KING TX-800 R50 Diesel & stand-by 400 v

Cooling capacity at -20°C = 4200 W (8000 W at 0°C)

Air flow = 2700 m³/h

Three-phase power 380 v

Refrigerant R452a

Standard control box in cab

Automatic defrosting

Extra battery + battery box included

Cooling unit powered by vehicle's tank

1 temperature recorder **TouchLog Premium** in cab with printer

1 door switch for ventilation cut-off on right rear door (fan stop switches)

Fitting & commissioning included

15 meter electrical extension lead

With ATP certificate FRC