
Body fitted on chassis + fridge

CHASSIS SPECIFICATIONS

Trade mark : IVECO
Model : Daily 70 C Euro 3
G.V.W : 7 tons
Wheelbasis : 3450 mm
Voltage 12 or 24 v

BODY CFR IR 65 (14,1 m³ - single-temp >>> from -20°C to + 18°C)

outer length : **3500** mm inner length : **3300** mm
outer width : **2300** mm inner width : **2154** mm
outer height : 2240 mm inner height : **2000** mm

Thickness of Panels

Floor : **130** mm Roof : **102** mm
Front : **117** mm Rear : **85** mm
Sides : **65** mm

Side wall laminate

Exterior : G.R.P. Interior : G.R.P.

Apertures

Stainless steel rear frame 2 doors - Total opening
2 stainless steel locking gears
Opening priority to the right rear door

110° door retainers

Floor

Grey antiskid GRP reinforced for trolleys
With wheel recess >>> cuttings under the floor
2 Drain holes with siphon Ø 40 front L&R

Inside equipments

250 mm Aluminium kick strip

1 universal steel Combi-rail 3009 (surface mounted) on side walls
Location : mm

Chassis equipments

Galvanized steel subframe, welded model
1 rear pull out ladder 3 steps
Aluminium sideguards
Plastic mudguards & mudflaps

General aspect

Bodywork : standard white RAL 9016
Outside capping in anodized aluminium

Fridge equipments

Front bulkhead reinforced + aperture for THERMO KING TX-600 R50

Other equipments

2 Rubber buffers 490*110 on the rear frame
2 Rubber buffers 310*80 on the chassis
2 Spring door retainers

1 Internal roof light (4 leds – 1100 lumens) **with motion sensor**
2 multifunction LED lights on top rear frame

FRIDGE UNIT

THERMO KING TX-600 R50 Diesel & stand-by 400 v

Cooling capacity at -20°C = 4000 W (6800 W at 0°C)
Air flow = 2700 m³/h
Three-phase power 380 v
Refrigerant R452a
Standard control box in cab
Automatic defrosting

Extra battery + battery box included
Powered by the vehicle's tank (no additional tank)

1 temperature recorder **TouchLog Premium** in cab with 2 probes & printer

Fitting & commissioning included
10 meter electrical extension lead