

No	Equipment	Piece
1	Mobile Service	1



Dimensions / mm.	Length	4.500	Width	2.150	Height	2.300
------------------	--------	--------------	-------	--------------	--------	--------------

Bodywork

MWS bent C type channel steel.
 Column sheets 3 mm. Panels 2 mm.
 Base cross members 80mm height 3mm.
 Base 18 mm Plywood.
 Sliding windows to usable areas.
 Stainless hinges and locks.



Sliding glass rear door.
 Monolithic crane connection channel to the body frame.
 Acrylic industrial chassis paint.
 Quick access rear bumper drawers.
 Metal parts are fixed to the chassis.

Outer Covering


Acrylic Industrial Coating.
 Paint over primer coating.
 Hygienic, mold-proof, stainless and corrosion resistant.
 Shiny and smooth appearance.



Solvent-free, high water resistance.
 CE certified

Insulation

Elastomeric Rubber Edges, Ceiling 18/40 mm.
 Provides high performance thermal insulation with its low thermal conductivity structure.
 Has a high water vapor diffusion resistance of.









Used in system solutions with high condensation risk.
 Increases energy amount.
 Protects against pressure fluctuations.
 Unaffected by mold and microorganisms, antimicrobial.







Control Panel







Center control panel.
 Generator and compressor areas are quickly accessible cover.
 Electrical cables are hidden inside the insulated chassis.
 Cables in protective plastic sheath.















Polyurethane hose in air line duct.
 Mains Electricity Connection Input.
 Perimeter and interior lighting 220v.







No	Equipment	Pcs	Picture	Specifications	
2	Open Jaw Wrench Short Pattern Set	1		6 – 7 – 8 – 9 – 10 – 11 – 12 – 13 – 14 – 15 – 16 – 17 – 18 – 19 – 20 – 21 – 22	
3	1/2" Twelve Corner Socket Wrench Set 24 pcs	1		1/2" Twelve Corner Socket Wrench:10.11.12.13.14.15.16 .17.18.19.21.22.23.24.26.27. 28.30.32 1/2" Ratchet Handle: 250 1/2" Joint: 70 mm 1/2" T Handle Adapter	
4	Screwdriver Set	4100	1		Screwdriver Set 7 Piece Flat Tip: 3x80 - 4x80 - 4x100 - 5x125 - 6x150 Phillip Tip: 4.5x80 - 6x100
5	Hammer	5800	1		Baked, Varnished Handle Electrostatic Powder Paint Alloy Steel Weight : 2 Kg.
6	Air Impact Wrench Set	OPT 600K	1		Bolt Diameter: 22 mm Socket Square: 3/4" Max. Torque: 670 Nm Working Pressure: 6.2 atu Length: 243 mm 26 - 27 - 29 - 30 - 32 - 35 - 36 - 38 mm socket 3/4
7	Hammer 3 psc	5800	1		Baked, Varnished Handle Electrostatic Powder Paint Alloy Steel Weight : 0,500 / 1 / 2 Kg.







No	Equipment	Pcs	Picture	Specifications
8	Chrome Tape Measure	1		Model: Chrome Dimensions: 8 Mt Weight: 410 Gr
9	Led Flashlight 5345	1		Light power High: 1000 Lumens Medium: 500 Lumens Low: 200 Lumens High / Medium: 2 / 2.5 Hours Low: 12 Hours Weight: 219 Gr
10	Cordless Drill Driver	1		Chuck diameter: 1.5/13 mm Aluminum/Wood:13/35 mm Steel / Screw : 13 / 10 mm Battery voltage: 18 Volt Torque (max): 50 Nm Battery type: Lithium-ion Torque steps: 20+1
11	Angle Grinder Machine	1		Disc Diameter: 125 mm Nominal Power: 1,400 Watt Idle Speed: 11,500 rpm Grinding Spindle : M14 Hole Diameter: 22.23 mm Switch: Lockable Key Weight: 2.2 kg
12	Air Compressor 12 bar	1		Engine Power: 3 hp. Air Intake: 400 lt/min. Speed: 950 rpm. Pressure: 8 bar
13	Air Tank 300 lt	1		Capacity : 300 lt. Working Pressure: 15 bar. Test Pressure: 15 Bar. Sheet Thickness: 4 mm. Compressor Connection : 1" Air Outlet : 1/2"







No	Equipment	Pcs	Picture	Specifications
14	Air Regulator OPT3042FRL	1		<p>Air Inlet : 1/2"</p> <p>Filter : 20u</p> <p>Working Pressure: 05-9.9 atu</p> <p>Operating Temp.: 5-60°C</p> <p>Water Capacity: 80 ml</p> <p>Air Per.: 2200 lt/min</p>
15	Air Reel 15 mt.	1		<p>Hose Length:20mt.10x15mm</p> <p>Working Pressure: 15 Bar</p> <p>Inlet and Outlet Dim.: 3/8"</p> <p>Automatic Rewind</p> <p>Steel swivel wall bracket</p> <p>Size: 50x43.5x23.5 cm</p> <p>Weight: 8.3 Kg</p>
16	MMA Welding Machine	1		<p>Mains Voltage : 400 V</p> <p>Power Drawn from the Network: 19.6 kVA</p> <p>Rated Welding Current: 350</p> <p>Open Circuit Voltage: 86 V</p> <p>Electrode Dia.:1.60-5.00 mm</p> <p>Weight : 32 Kg</p>
17	Digital Multimeter	1		<p>Ultra LCD: maximum measurement data display up to 3999</p> <p>Universal digital multimeter, extremely useful and versatile</p> <p>Large LCD disp, easy to read</p>
18	Auto Control Pen	1		<p>Chrome vanadium, chrome plated</p> <p>Transparent cellulose acetate handle</p> <p>Cable length: 1 Mt</p> <p>L : 135 mm. / L1 : 60 mm</p> <p>Weight: 30 Gr</p>
19	Compression Test Kit Petrol / Diesel	1		<p>Compressor pressure testing up to 50 bar (725 PSI).</p> <p>Includes injector adapters M20, M22, M24 and Stanadyne injector adapter for Ford, spark plug adapters M10, M12, M14 and M18.</p>


No	Equipment	Reference	Pcs	Picture	Specifications
20	Hydraulic & Pneumatic Jack	GMS 110	1		Folding Arm Mobile Jack Lifting Capacity: 40/25 tons Min. Height: 180 mm Mak. Height: 273 mm Lifting Distance: 40 / 85-25 / 80 mm Weight: 58 kg
21	Oil Pump 18 lt.		3		Pneumatic pumps for oil Flow rate: 18 l / min Air working pres.: 6/8 bar Av. air con.: 370 l / min Noise level: 81 dB Oil viscosity: 80 SAE
22	Oil Reel 15 mt.		3		Pressure: 150 bar Length: 15 mt Compatible fluids: Oils Material: Painted Steel Inlet-Outlet : G 1/2 - G 1/2 Pressure - Size: 1/2 " 160 bar
23	Oil Gun		3		Flu: Technopolymer Digital meter: Yes Inlet swivel joint: G 1/2 f Filter: Yes Level locking button: Yes
24	Grease Lubrication Kit		1		Grease disp. kit Ratio: 50:1 Flow rate: 1500 g/min Av. air conmsp.: 330 l/min Noise level: 81 dB Weight: 4.6kg Grease guns
25	Grease Reel 15 mt.		1		Pressure: 400 bar. Hose Length: 15 mt. Compatible fluids: Water Swivel joint: Stainless Metal Characteristic: Fixed Material: Painted steel

No	Equipment	Reference	Pcs	Picture	Specifications
26	Repairman's Sled	TK6	1		Product Dimensions: 101x47x13 Cm / 40" 6 pcs for easy maneuvering Weight: 5 Kg. With practical carrying handle. Oil-resistant, wide wheels
27	Rubber Brake Pad		1		Made of PE material and portable. The triangle structure and rubber pads at the bottom keep the vehicle in place
28	Tire Repair Kit 78 Pieces		1		1x T-handle 100mm, 175mm 1x hexagonal angle wrench for loosening the ends of the T-handles, 15 x 50mm 70x vulcanizing strips 1x box sealing lubricant 4x glue tube
29	Ratchet Torque Wrench 1/2"		1		Socket square 1/2" Tightening range: 40-200 Nm Weight: 1,590 Gr
30	Mechanical Tool Kit - 62 Pcs		1		Metal Tool Box 5 Eyes Chrome Tape Measure 5 Mt Magnetic Bit Holder Short Flat / Stars / Torx Bit Tip Opaque Star Screwdriver 135 mm Control Pen
31	Magnetic Tool Holder		1		Magnetic Tool Holder Stainless Tray Set 290x270 mm and 95x65mm and 105mm Set Used as Tool Holder in Automotive Services

No	Equipment	Reference	Pcs	Picture	Specifications
32	Bungee Cords or Straps	H44002	1		Holds, ties and fixes your materials tightly Both ends have sturdy hooks 80 cm fixed length, reaches 185 cm max length when stretched.
33	Protective Gloves		1		Spandex Nylon fabric NBR Micro Finish Foam Nitrile Coating 4131X CE, EN 388 12 Pcs.
34	Battery Booster 12V 2500A		1		Voltage: 12 V Boost rate: 2500 P.LE Charge regeneration: 230 V Battery life (cycle): 400-500 Cable diameter: 25 mm ² Dimensions: 31 x 10 x 28 Weight: 9.5 kg.
35	Battery Charger 12V-24V 15 A		1		Input Voltage: 110-240 VAC 50/60Hz, Power (Input): Max. 72 W Output Voltage: DC 12V Output Current: 5 A
36	Extension Cable 25 Mt 5x1.5 Mm		1		Cable length: 25 Mt Cable type: 5x1.5 mm H07RN-F Cable Thermal fuse Black rubber cable 1 Three-ph. socket 5x16 Ah 2 Single-ph. socket 1x16 Ah
37	Outdoor Lighting		10		Operating : DC 24/15V 1.4A Light Source: 3W 12pcs LED LENS Feature: 25° LENS White:5000-7000K Physical Properties : Polycarbonate plastic black aluminum profile

No	Equipment	Reference	Pcs	Picture	Specifications
38	Lighting	WT066C	6		<p>Watt: 19 W Light Flux: 1800 Lm Dim Feature: Fixed Driver Product Life: 25000 H Color Temperature: 4000K IP Protection Class: IP65</p>
39	RUBBER FLOORING 5 mm	236	1		<p>It is used on all kinds of surfaces, in the production lines of factories, on the floors of the bodies of vehicles such as trucks, lorries, vans and buses, counters.</p>
40	Shelving System	17073	1		<p>Galvanized shelves and uprights. Width: 750 mm Depth: 600 mm Height: 2.000 mm Drawer: 5 pcs.</p>
41	Wall Mounted Axial Fan	EF800T	1		<p>Max. air flow 14000 m³ / h Metal cable glands for electrical connection. The product is Exproof Motor certified (I I 2 G Ex db I I C T 4 Gb I I 2 D Ex tb I I C t120 ° Db)</p>
42	Oxygen Propane Welding and Cutting Set	8210	1		<p>Pressure Reducer Oxygen - With Cover :1 pcs. Pressure Reducer Propane - With Manometer :1 pcs. Cutting Torch :1 pcs. Cutting Nozzle Set:1 pcs. Welding Arm No:4:1 pcs.</p>
43	Oxygen Propane Reel / 20 mt.	8530.704	1		<p>Pressure : 20 bar. Hose Length : 20 mt. Hose Size : ø 2 x 5/16" Compatible fluids : Welding Material : Painted Steel Couplings : Brass Inlet / Outlet :G 3/8" (f)</p>

No	Equipment	Reference	Pcs	Picture	Specifications	
44	Oxygen Propane Wheelbarro w	450801	1		Oxygen / Argon / Nitrogen Electro powder painted. Car chassis 32 x 2 mm. Chain is secure. Rings: 30 x 10 sheet Table: 2/3 diamond plate Wheels: 300 mm	
45	Work Bench	ALR11180	Alura	1		Width: 1.800 mm Depth: 700 mm Height: 2.000 mm Number of Drawers: 10 Drawer Carrying Capa: 60 kg.
46	Metal Cabinet with Drawers	6225		1		Material Cabinet Width: 1.000 mm Depth: 450 mm Height: 2.000 mm Number of Shelves: 7 Pieces
47	Generator	FDL 13500SE3		1		Working Power: 13.75 kVa Prime Power : 10 kVa Starting System: Starter Fuel Tank: 15 lt Voltage AC: 220 / 380 Cooling: Air Cooled
48	Hoist 1 Ton 3 Mt	G1CE103		1		Capacity: 1 Ton Tested value: 22.5 KN Chain thickness: 6 mm Chain length: 3 Mt Net weight: 11 Kg Extra chain weight per meter: 1.6 Kg
49	Aluminum Shutters	CLK1		3		Manuel Working Locking Systems Size : 1000 x 2200 mm.

No	Equipment	Reference	Pcs	Picture	Specifications
50	Fire Extinguisher	STR1806	2		<p>ABC Grade Fire Ext. Powder 6 Kg Capacity MAP Rate 40% Body made of A1 7114 Quality Plastered Sheet 18 Bar Working Pressure 0.70 Mic.Elec. Static Paint</p>

No	Equipment	Piece
1	Mobile Service	1
2	Open Jaw Wrench Short Pattern Set 2112	1
3	1/2" Twelve Corner Socket Wrench Set 1113	1
4	Screwdriver Set	1
5	Hammer	1
6	Air Impact Wrench Set	1
7	Hammer 3 psc	1
8	Chrome Tape Measure	1
9	Led Flashlight	1
10	Cordless Drill Driver	1
11	Angle Grinder Machine	1
12	Air Compresor 12 bar	1
13	Air Tank 300 lt	1
14	Air Regulator	1
15	Air Reel 15 mt.	1
16	MMA Welding Machine	1
17	Digital Multimeter	1
18	Auto Control Pen	1
19	Compression Test Kit Petrol / Diesel 1500-8401	1
20	Hydraulic & Pneumatic Jack	1
21	Oil Pump18 lt.	3
22	Oil Reel 15 mt.	3
23	Oil Gun	3
24	Grease Lubrication Kit	1
25	Grease Reel15 mt.	1
26	Repairman's Sled	1
27	Rubber Brake Pad	1
28	Tire Repair Kit 78 Pieces	1
29	Ratchet Torque Wrench 1/2	1
30	Mechanical Tool Kit - 62 Pcs	1
31	Magnetic Tool Holder	1
32	Bungee Cords or Straps	1
33	Protective Gloves	1
34	Battery Booster 12V 2500A	1
35	Battery Charger 12V-24V 15 A	1

No	Equipment	Piece
36	Extension Cable 25 Mt 5x1.5 Mm	1
37	Outdoor Lighting	10
38	Lighting	6
39	RUBBER FLOORING 5 mm	1
40	Shelving System	1
41	Wall Mounted Axial Fan	1
42	Oxygen Propane Welding and Cutting S 8210	1
43	Oxygen Propane Reel / 20 mt.	1
44	Oxygen Propane Wheelbarrow	1
45	Work Bench	1
46	Metal Cabinet with Drawers	1
47	Generator	1
48	Hoist 1 Ton 3 Mt	1
49	Aluminum Shutters	3
50	Fire Extinguisher	2