

Heavy Duty Tipper Trailers 32T

General Dimension:

Gross weight: 59.000 kilo

Axle weight: 3 x 13.000 kilo

Kingpin weight: 20.000 kilo

Payload: 59.000 kilo

Volume: 32 m³

Trailer length: 10.040 mm

Fifth wheel height: 1.350 mm approximately empty

Frame:

An heavy duty frame consisting of two assembled I main beams with necessary crossmembers. In the frame a fifth wheel section with 3,5" Jost kingpin, which if necessary can be changed for a 2" pin. At the rear a swivelling bumper.

Axles:

Three axles with mechanical suspension. The axles with drum brakes 420 x 180 mm. Capacity per axle 13.000 kilo.

Tires:

13 pieces of tire with steel rim, dimension 315/80R22.5 a spare wheel carrier of the bow type. The tires, tubeless make Tyrex.

Brake system:

A two line Wabco brake system without ABS. SAE air couplings.

Light system:

A 24 V light system. A seven pole connectors towards the truck. No side markers. Rear Lights.

Hydraulics:

A Penta front tip cylinder. Tipping angle will be approximately 45°. Quick connector coupling on the cylinder.

Body:

A rear tipping square body with volume 32 m³. Scissors between body and chassis. The free swivelling door at the rear closes against the body by locked hooks at the bottom of the door.

Various:

Mudguards with rubber mud flaps. Steel toolbox. Basket for spare wheel.

Paint treatment:

All steel after assembly shot blasted primed and painted. Chassis Colour is RAL 7021(dark grey), body colour is RAL 7005(grey). Yellow reflective stripes on the outside of the body walls.