

Lindner & Fischer Tank body for the transport and distribution of fuel

Type: TA 85 SD
Volume: approx. 8 500 ltr. +3% expansion

Superstructure

The “*Special L&F Low-Torsion body mounting system*” for tank bodies is recommendable due to their strongness, torsion-resistant design, in particular for “Off-Road” operation under rough cross-country conditions. The elastic connection between the truck chassis and the sub-frame provides a torsion-absorbing function.

This arrangement absorbs any stresses passing from chassis to tank.

The sub-frame is mounted to the truck frame in a way to ensure equal load distribution.

Otherwise mounted according to truck supplier’s “Assembling Instruction”.

Tank support

The tank itself is supported in tank saddles which are bolted on the reinforced longitudinal frame members with heavy duty rubber mountings in front.

Tank

Tank shape: Elliptical 8 500 ltr. + 3% expansion
Tank compartments: One (1)

Manufactured of thick high-grade steel –S235JRG2-, thickness 4 mm electrically welded throughout with accurately finished welding seams. Dished bulkheads on both sides and appropriate nos. of splash walls. The splash walls are mounted not less than 900 mm and not more than 1750 mm between each other according ADR.

Dome-pan

Overflow protection welded along the tank with drain pipe and shutoff cock.

The dome pan is designed as an over-roll protection in order to protect the dome armatures.

Walkway

Open mesh walkway on the right-hand side of the manhole cover, with rear mounted access ladder.

One (1) collapsible handrail made of aluminum, operated manually, fixed as safety barrier, according UVV regulation along the dome-pan.

Operation of handrail manual, next to access ladder.

Top fittings per compartment

One (1) 500 mm dia. manhole cover with 250 mm dia. hinged lid, complete with one (1) dipstick, increments; 1000 / 1000 ltr.

Flame proofed safety vent valve and pneumatic operated tipping valve DN 65.

Discharge fittings per compartment

At the lowest point of each compartment one (1) pneumatic bottom valve DN 80.

For each compartment, a separate filling/discharge pipe DN80, mechanical valve and 2 ½" Cam-lock coupling coupler and dust-cap leads in to armature box.

One (1) filling/discharge for all compartments together, connected to fuel-pump

Pump

One (1) self-sucking pump, installed at the vehicle's chassis, hydraulically driven by PTO of truck engine and can be operated pneumatically from the drivers cabin. The suction pipe is equipped with a suction filter. Suction and delivery connections are provided with hose coupling and cab. Oil-cooler mounted with electric fan.

Hydraulic manifold with pressure inside armature box for operation of pump

Pump capacity: approx. 500 ltr./min

Metering system

On the right side of the vehicle in a cabinet the metering system 2" is mounted, consisting of:

Gas separator, meter rated for a flow of 35 -375 ltr. / min

4-digit resettable register

8-digit non-resettable totalizer.

Hose-reel

One (1) hose reel spring loaded with 20m hose DN 32 and manual discharge nozzle, mounted next to armature box behind cabin

Armature box

One (1) on right hand side mounted, with discharge outlets and pneumatic operations, pump and metering system

One (1) LED light is mounted inside armature box and operated by master switch.

Two (2) discharge valves mounted on lowest position of armature box to drain-off fuel-spillage.

A pneumatic air regulator and lubricator is mounted inside with all necessary valves, adjustments and filling port.

Delivery options

- discharge by gravity, via 2 ½" Cam-lock coupling
- discharge with pump, measured via 2 ½" Cam-lock coupling
- discharge with pump, measured via hose-reel
- self-filling with own pump
- filling with external pump
- filling from top

Hose and hose-carrier

Two lockable, galvanised and painted hose tubes, both mounted on one side with two hoses

Hose type: NW 65 with 2 ½" Cam-lock coupling

Hose length: approx. 3,00m each

Bonding reel

Manual rewind reel with 15m of 2mm steel-cable and grounding clip

Standard accessories

PVC mudguards with rubber mud-flaps

One (1) spare-wheel carrier with winch and handling arm mounted behind cabin

One (1) fire extinguisher, 6 kg each

One (1) lockable tool box mounted on chassis

Three (3) warning labels for hazard goods

One (1) earthing point welded next to armature box

Special accessories

Yellow reflective strips on rear tank shape and along both sides of tank and cabin

Red/white signal marking at rear of chassis

LED brake, tail and indicator lights mounted on rear upper part of the tank

Paintwork and finishing

All steel parts are sand-blasted and prime-coated.

Tank body painted in one RAL colour.

Substructure, etc. painted in chassis colour

Acceptance test

Leakage testing of tank 0,35 bar

Functional test

Documentation

One (1) spare part list

One (1) operating manual

All instruction plaques, lists, manuals and signs in English