

SCHMITZ CARGOBULL insulated Truck - body FERROPLAST

MKO - FP COOL V7 - FP 60 COOL with THERMO KING T 600R

The truck has to be configured for all optional hardware and electrical wiring & consumption before Schmitz Cargobull undertakes any further work on the "final product". If the truck is not prepared accordingly, Schmitz Cargobull reserves the right to pass on to the customer any additional costs that may arise as a result of Schmitz Cargobull's additional work.

Dimensions and weights

Internal length	ap.	6.050 mm	Total tare weight	+/- 3%	3.489 kg
Internal width	ap.	2.460 mm	Overall length	ap.	6.200 mm
Internal height	ap.	2.250 mm	Overall trailer width	ap.	2.600 mm
Usable internal length	ap.	6.050 mm	Door aperture height	ap.	2.240 mm
Usable internal height	ap.	2.250 mm	Door aperture width	ap.	2.460 mm
Side aperture width	ap.	900 mm			
Total height at front (unladen)	ap.	2.469 mm			
Side aperture height	ap.	2.051 mm			
Side door from inside bulkhead	ap.	1.500 mm			
Total height at rear (unladen)	ap.	2.469 mm			
Brand of truck		IVECO			
Type of truck		EUROCARGO			
Axle formula		4x2			
Trailer operation		NEIN			

Chassis

CARGOBULL * HIGHLIGHTS *****

C00275 Production PANEVEZYS

P02192 2 warning plates to rear 565x132 ECE-R70 yellow/red stripes; on tail lift platform
X91048 Country of registration: "Algeria"
 X91501 without HACCP certificate
X90121 International custom seal (TIR) for body with rear door, side door, without TIR certificate
 M00902 Without tachograph test acc. §57b
SON005* F75329 ATP FRC test report

Chassis

M00133 Body assembly on diesel truck chassis
 M00307 M.KO order as solo vehicle (without trailer delivery by SCB)
 C20000 rear underrun bar in conjunction with tail lift
 M00300 no provision for trailer traffic
X00233 Side guard for HGV
M00131 Adapt HGV chassis frame protrusion

Sub frame

C00201 Galvanized subframe screwed

Brake system

B99988 Without air couplings fitted on the truck

Light system

C24026 M.KO lamp holder galvanised
 E00096 Without side tracking lights
E00308 without "Plug & Play" options in truck specification
 K75086 Switch for interior light at the rear, under the floor
K91507 internal lights controlled by proximity switch on tail lift
E00222 Side marker lights with reflectors for rigid
 K75101 2 white front top position marker lights, 2 red rear top position marker lights

Spray suppression

P00830 Vertical plastic mudguards
P00706 Anti-spray mud flaps with Schmitz Cargobull logo, side spray guard

Further chassis equipment

M00142 Truck without demounting of roof spoilers
 V00008 Without lashing rings
X90037 One-line license plate holder with LED lighting
X10404 Plastic toolbox with cover holder, sleeves and drawer
 P02020 2 rear corner rubber block buffers
C90305 Access step at the rear (tail lift)
P02131 1 fire extinguisher 6kg, with storage box

Tail-Lift

L00051 Without trolley stop
L00071 Edge strip PML for nesting the drive on sheet at tail lift
L00076 S/Steel strad. nose for tail lift at rear wall frame, hex-screwable version, sloped
L00105 Earth cable for tail lift (MKO)
L00206 Fitting of cantilever tail lift 1500 kg with CARGOBULL interface
L10014 Supply tail lift
L13424 DHOLLANDIA-tail-lift type DH-LM20 1500 24V m. EG-UF Alu-platform 2200 mm
L00153 Warning flags at the tail lift platform
L00141 Remote control unit w. plug at operating box
 L00147 Without 2nd external controls for tail lift
L00161 Standing pos. markings on tail lift platform

Bodywork

Body

K00001 PU foam panel, free of thermal bridges, sealed against vapour diffusion

- K00886 M.KO FP V7, internal length 6050 mm**
 K09001 Inner skin is 0.6mm PVC coated steel scuffproof and load safe
SON001* Fxxxx internal length 5000mm
SON001* without K00886

Front bulkhead/Roof/Side walls

- K21020 Insulated front bulkhead, NX17 foam, with reinforcement for fridge installation
 K41022 without kick strip for distribution transport Loading/unloading
 K41028 Without alu. inner angle roof / side wall
 K43010 EFP insulated sidewall, COOL 60, NX17 foam
K72315 2 x Row(s) recessed galvanized load restraint track to both walls,with side door (6050)
 Floor to middle of 1st load securing rail 600 mm
 Floor to middle of 2nd load securing rail 1.200 mm
 K63005 FP insulated roof, NX 17 foam

Rear closure

- K31050 FP 2-wing rear door, insulated, NX17 foam, with simple stainl. steel locking mechanism
K56005 Rear wall door -Emergency opener from inside, rotatable design
 K39013 Rear frame is stainless steel, sand blasted finish
 K73311 300mm depth, anodized aluminium kick strip fitted at base of each rear door
P02041 Hinge protection rubber buffers fitted vertically full height of the rear frame
 P02071 Without add. buffer protection to rear frame across bottom

Side door

- K53009 Single leaf side door FP60 900mm wide,RHS in direction of travel.**
K56004 Side door - Emergency opener from inside, rotatable design

floor

- K11104 2 drains with taps at the rear of the floor with extended hoses**
 K11151 Aluminium barley seed floor, low noise Test load 5500 kg V7
 K12001 300mm aluminium kick strip at front and both sides welded to floor
SON001* Fxxxxx 4 pairs of lashing rings in the body floor, spaced 1m apart (Longitudinal)

Further body equipment

- C90105 Foldable ladder on the bulkhead in driving direction left**
C90201 1 galvanized steel access step in the area of the side door
E10077 Install. rev. cam. u. floor (prov. by custom, incl. cable & monitor) as per GSR
 K72466 without multifunction clamping bars
 K75113 Particularly bright LED lighting inside the box
K72427 2 x Rounded steel telescopic locking bar (galv. steel) horizontal, with pins on both sides
K72441 4 x Tension belt appr. 3500mm with tension lock
 K72448 Without tension belt for double stack system
K92003 Plastic curtain, longwise adjustable, 3x crosswise movable
K92050 Plastic strip curtain for the side door
SON001* F89825 Fridge Standby Cable
 20m

Cooling unit

- K80111 Power cable for fridge with plug, behind the axles, in the tool box, app. 5m length**
 K80259 without add. fuel tank, the customer accepts the hole in truck's fuel tank f. cooling unit
K91538 Door contact switch for cooling unit ON/OFF coupled with roller shutter / rear wall door
K91555 Side door contact switch for cooling unit ON/OFF
 K80572 provision for THERMO KING T-600R
 K80001 Fridge unit aperture cut out and bolt holes drilled in front bulkhead
K81330 THERMO KING T-600R 50 with Battery and Battery box
K80177 Asmby package f.MonoTemp.cooling unit, M.KO (plug-in device) B
 K91440 Without provision for temperature recorder (only for ATP application)
K80117 Assembly of control unit for remote control refrig. unit in driver's cab in radio bay

- K91376*** **Temperature recorder Touch Log Premium with printer, according to EU dir. 12830**
- K80092*** **2 temperature sensors for temp. recorder**
- K80254*** **Add.steel fuel tank, black, 90 litres on truck for ref.unit**

Painting/Finishing

- K99061 side door frame stainl. steel in body colour
- K99204 Roof painted in SCB 9010 white
- L00020** **Painting of tail lift platform, external (top surface not painted)**
- X90340 Partial contour marking, side, white, rear red all around
- X90621 without loading line without frigoroute-sticker
- K99050 Body finished in white SCB 9010
- X90199 Without lettering
- X90622*** **Loading line 40mm width on side wall 270mm lower edge roof, with Frigoroute foil**

* Special request or custom size / weight

Finishing / Colour specification

Part	Color	Number	Classification
Subframe	HOT DIP GALVANISED	10	–
Side guard	WHITE ALUMINIUM (SILVER)	9006	RAL
Body	SCHMITZ WHITE	9010	SCB
Roof	SCHMITZ WHITE	9010	SCB
Tail lift	SCHMITZ GRANITE AKZO 499H3	7350	–