

**MERCEDES-BENZ
ACTROS 2035 4X4
FIRE FIGHTING
TRUCK**

It.	Article	Description	Qty.	Mea.
700,0	102445	ADAPTOR MORRIS Adaptor instantaneous female - instantaneous male. 1 1/2" female - 2 1/2" male customs tariff no.: 7609 00 00	4,00	Pce
701,0	042582	Branchpipe B multi-purpose British Standard With tight coupling Morris 2 1/2" male of light metal. customs tariff no.: 8424 89 00	2,00	Pce
702,0	042726	Branchpipe holder LM British Standard Inlet Morris 2 1/2" male, outlet 2 1/2" female. customs tariff no.: 8481 80 99	2,00	Pce
703,0	800302	MED. EXPAN. FOAM BRANCHPIPE M4 ZIEGLER medium expansion foam branch pipe with ball valve and pressure gauge, with, instantaneous male coupling. Branch barrel from stainless steel. Type M 4, 625 mm long. Capacity: 400 l/min. Weight approx. 7 kgs. customs tariff no.: 8424 89 00	2,00	Pce
704,0	6390000	ZIEGLER Hose customs tariff no.: 5909 00 10	10,00	Pce
	704,0-10	Delivery hose Pionier 500		
	704,0-20	65 mm		
	704,0-30	20 Meter		
	704,0-40	bandaged with coupling: British Standard "BSS 336" 65 mm		
	704,0-50	Norm 65 mm		
	704,0-60	Norm Beschriftung		
705,0	031239	Suction/delivery hose 2,5 m with Morris couplings Advantages: Small bending radius of only 600 mm, weight saving of up to 30%. The suction hoses with a smooth inside surface and a	6,00	Pce

It.	Article Description	Qty. Mea.
	<p>ripped outside surface feature a hidden inside spiral. The rubber material is resistant to corrosion and rotting. The pressure load is at least 6 bar for a period of 5 minutes and the vacuum load at least 0.8 bar for a period of 1 minute. The binding parts are without a spiral. With couplings size 100 mm (BRST 4")</p> <p>Length: 2.5 m</p> <p>Wall thickness: 7 mm</p> <p>Weight: 15,9 kg</p> <p>customs tariff no.: 4009 22 00</p>	
706,0	<p>042323 Suction strainer A, LM</p> <p>British Standard</p> <p>Suction strainer 4", light metal, with 4" BSRT.</p> <p>customs tariff no.: 7326 90 98</p>	1,00 Pce
707,0	<p>800305 Suction wrench</p> <p>Suction hose wrench for BS couplings.</p> <p>customs tariff no.: 8204 11 00</p>	2,00 Pce
708,0	<p>059422 Fire extinguisher PEP 6 GA</p> <p>With wall bracket</p> <p>with the dry chemical powder GLUTEX for fire classes ABC. With internal propellant cartridge, automatic pressure charging after releasing and operation of the triggering device. Pistol with shut-off. Type charging extinguisher, with extinguishing nozzle. Contents: 6 kg.</p> <p>customs tariff no.: 8424 10 00</p>	1,00 Pce
709,0	<p>055898 Spreader SP 35-L, Weber</p> <p>Acc. to EN 13204, EN Class S 35/600-17.</p> <p>Low weight spreader. Bars from light metal which can be charged over the complete length for spreading.</p> <p>Bars partially with inside riffle for squeezing (up to max. 77 kN).</p> <p>With two handles, thereof one foldable handle as carrier handle. Space-saving slim shape, tips with integrated peeling set.</p> <p>With connection hose pair 0,3 m, black colour.</p> <p>Spreading force in working range: 38 - 172 kN.</p> <p>Closing force: up to 77 kN,</p> <p>Pushing distance: 630 mm,</p> <p>Weight: approx. 16,6 kg</p> <p>customs tariff no.: 8467 89 00</p>	1,00 Pce
710,0	<p>056143 Replacement tips (pair) for SP 30, SP 30 LS and SP 35, Weber</p>	1,00 pa

It.	Article Description	Qty.	Mea.
	without bolts. Weight: approx. 0,8 kg customs tariff no.: 8467 99 00		
711,0	055899 Kettensatz 1,8 m lang, für Spreizer SP 35-L, SP 53BS, Weber Gewicht: ca. 13,8 kg customs tariff no.: 8467 89 00	1,00	Pce
712,0	054918 Cutter RSX 105-29, Weber Extremely light-weight, but nevertheless powerful cutter. Excellent cutting performance thanks to new cutting technology. Compact and lean shape. Technical data: Opening width: 105 mm, max. cutting power: 29 t, max. cutting performance at round bar: Ø 22 mm, EN cutting class: AC 105-E-9, NFPA cutting class: A5/B4/C5/D6/E6. Weight: approx. 9,3 kg customs tariff no.: 8467 11 90	1,00	Pce
713,0	054919 Spare shear blade (pair) for cutter RSX 105-29, Weber customs tariff no.: 8467 11 90	1,00	pa
714,0	057013 Hydraulic power unit V 50-T+ SAH 20, w. single-coupl., Weber EN 13204 EN class ATO/MTO. With 4-stroke petrol engine 2.6 kW. Working pressure 630/700 bar, oil volume 4 l. With built-in quick-intervention reel and 2 ultra high-pressure hose pairs 20 m, yellow and red, with SINGLE couplings, either for "turbo" operation with one tool or for simultaneous operation of two tools. The hoses can be drawn off from the reels separately even when under pressure. With integrated rewinder and reel brake. With 10 m connection cable and pressure-water protected plug. Dim. (LxWxH): approx. 845x440x472 mm, weight: approx. 71 kg. (The picture shows the unit with holding device for cutter and spreader, art.no. 057008.) customs tariff no.: 8413 50 20	1,00	Pce
715,0	059656 Compr. air breathing apparatus PSS 3000 with manometer, Dräger Easy handling, high wearing comfort, small weight	6,00	Pce

It. Article Description	Qty. Mea.
--------------------------------	------------------

and rugged design. Approval EN 137:2006 Type 2.
Ergonomic and antistatic carrying frame,
high pressure and medium pressure line integrated in
in the carrying frame, flame resistant harness reducing the
carrying load. Thanks to the rigid connection of the lap
belt solid fitting and good wearing comfort. Technical data:

- inlet pressure: 0 - 300 bar
- nominal outlet pressure of the first stage: 7,5 bar
- outlet flow of the first stage: > 1.000 l/min
- LDV outlet flow: > 400 l/min
- noise level of the whistle: > 90 dBA
- dim.: (HxWxD): approx. 590x290x160 mm,
- weight: approx. 2,7 kg (back plate and carrying harness)
- customs tariff no.: 9020 00 00

716,0 058578 Lung demand valve PSS-N Dräger	6,00 Pce
--	-----------------

Normal pressure round thread connection acc. to
EN 148-1, with short hose.
Small, light-weight and low noise in operation.
Housing of impact-proof plastics, bonded with
non-slip silicone protective cover.
Reliable, easy to maintain body.
Approved with all Dräger compressed-air breathing
apparatus of the product lines PSS, PA 94 UP, PA 80 UP.
Weight: approx. 0,4 kg
customs tariff no.: 9020 00 00

717,0 058683 Full face mask Panorama Nova RA PC, Dräger	6,00 Pce
--	-----------------

With normal pressure round thread connection
RD 40 mm x 1/7", acc. to EN 148-1.
Inner face mask with control valves, each with skin
compatible, especially rugged and refined rubber
compound EPDM (ethylene propylene dimonomer).
Easily adjustable 5-point bands and practical
neckstrap. Excellent visual field thanks to wide concave
pane, one piece, of extremely flexible, impact and heat-
resistant polycarbonate, clamped in stainless
steel frame. Plastic connection piece one part with
patented plug-type connection. With stainless
steel talking membrane for excellent
communication. Tested acc. to EN 136.
Weight: approx. 0,6 kg
customs tariff no.: 9020 00 00
authorization required on export outside EU 1A004A

It.	Article Description	Qty.	Mea.
718,0	058770 Compr. air cylinder 6l/300 bar of steel, light Acc. to DIN 3171, with impact-secured cylinder valve acc. to EN 144, G 5/8" straight, with locking screw and TÜV approval. TÜV-checking every 5 years. Service life unlimited. Dia.: approx. 140 mm, length with valve: approx. 605 mm, weight: approx. 9,8 kg (filled) customs tariff no.: 2853 00 30	6,00	Pce
719,0	058770 Compr. air cylinder 6l/300 bar of steel, light Acc. to DIN 3171, with impact-secured cylinder valve acc. to EN 144, G 5/8" straight, with locking screw and TÜV approval. TÜV-checking every 5 years. Service life unlimited. Dia.: approx. 140 mm, length with valve: approx. 605 mm, weight: approx. 9,8 kg (filled) customs tariff no.: 2853 00 30	2,00	Pce
720,0	061529 Bolt cutter with hook, 650 mm with exchangeable blades of chrome vanadium steel, painted steel pipe handles with grips of synthetic material. Cutting capacity 9 mm at 75 kp/mm². Total length: approx. 650 mm, weight: approx. 2,4 kg customs tariff no.: 8203 30 00	2,00	Pce
721,0	061527 Wire cutter 1000V Protective covers insulated to 1000 V. With exchangeable jaws made from chrome-vanadium steel (DBP), adjustable by eccentric screws. Steel pipe handles PVC insulated, with pivoting catching hooks. Cuts up to 125 kg/mm² (structural steels up to 8 mm dia.) Length (without catching hooks) approx. 470 mm weight approx. 1,7 kg. customs tariff no.: 8203 30 00	2,00	Pce
722,0	056323 Pike pole 5 m DIN 14851, 2-part, pole of Oregon Pine, varnished, with galvanized screw coupling. Total length: approx. 5 m, weight of hook: approx. 1,5 kg, total weight: approx. 8 kg	2,00	Pce

It.	Article Description	Qty. Mea.
	customs tariff no.: 8205 59 80	
723,0	056543 Vehicle first-aid kit B f. cars, DIN 13164 Of PP-plastics, black. Dim. (LxWxH): approx. 255x166x80 mm, weight incl. contents: approx. 0,55 kg customs tariff no.: 3006 50 00	1,00 Pce
724,0	8911511 Rescue gloves "Boxer" Acc. to EN 659:CAT III (EN 388, EN 407). Hydrophobized neats leather with ankle and pulse protection of shagreen leather, lined leather cuff, knitted inside glove of 100 % Kevlar, heat and cold insulating, breathable, good protection against mechanic risks, excellent wearing comfort, good grip, reflective trim on gauntlet circumferential with imprint FEUERWEHR, with ring and snap hook. Performance stages: Abrasion resistance 2, cut resistance 2, tear growth resistance 2, stab resistance 2, burning behaviour 4. Sizes: 7 - 12, Length: approx. 36 cm customs tariff no.: 4203 29 10	10,00 pa
725,0	064313 Box for assembly tools, 5-part of steel plate, painted, empty. Dim. (LxWxH): approx. 430x200x200 mm, weight: approx. 4,6 kg customs tariff no.: 7310 29 90	1,00 Pce
726,0	064315 Set of tools consisting of: - chipping chisel A 300 DIN 6553 - sledge hammer 2 S DIN 6475 - pliers 180 with grip jackets DIN 5244 - hammer 500 S DIN 604 - screw driver A 0.8x5.5x125 DIN 5265 - screw driver A 1.6x8x200 DIN 5265 Weight: 4 kg. customs tariff no.: 8205 90 00	1,00 Pce

It.	Article Description	Qty.	Mea.
727,0	061376 Cut-off saw PC-7414, 35 cm, Dolmar mit 20 mm Welle, 2-Takt Motor, 73 cm ³ , Leistung 3,8 kW, für Trennscheiben mit Ø 350 mm, inkl. Trennscheibe für Stein/Beton. Gewicht: ca. 10 kg customs tariff no.: 8467 29 59	1,00	Pce
728,0	061518 Composite cutting disc for steel, 350 mm Borehole 20 mm. customs tariff no.: 8467 99 00	2,00	Pce
729,0	061519 Composite cutting disc for stone and concrete, 350 mm Borehole 20 mm. customs tariff no.: 8467 99 00	2,00	Pce
730,0	063217 Hydraulic lifting device Büffel B 10 Lifting equipment to be used in vertical or horizontal position, adjustable lifting claw (5 positions). Permissible load: 10,000 kg, closed height: 800 mm, piston stroke: 350 mm. Weight: approx. 37 kg customs tariff no.: 8425 42 00	1,00	Pce
731,0	056279 Hand-Vario SPS 260-H, Weber Acc. to EN 13204, EN cutting class BK 33/250-E-11, NFPA cutting class A6/B6/C6/D7/E7. Manual compact combi tool with integrated hydraulic drive versatile for cutting and spreading. Low weight, little space required. Head piece can be rotated to any position within 360°. Opening: 260 mm, max. cutting force: 29 t, spreading force in working range: 33 - 383 kN, cutting capacity (round steel bar): 25 mm. Weight: approx. 11,2 kg customs tariff no.: 8467 89 00	1,00	Pce
732,0	061595 Motor chain saw 115, 38 cm, Dolmar Universal and perfected. Features: vibration damping, ecological oil pump, maintenance-free electronic ignition, 2-stage prefilter, strong engine. With saw chain, pitch 3/8". Displacement 52 cm ³ , power output 2,7 kW/3,7 HP. Weight: approx. 5,1 kg	1,00	Pce

It.	Article Description	Qty.	Mea.
733,0	061575 Combi can Double-can of polyethylene, red, with discharge pipe, with UN-certification no. 3H1W/Y1.OZ1.0/150/02/D/BAM6080-huen, consisting of 2 separate chambers und never-lost white screw lids, for 5.5 l and 3 l. Dim. (LxWxH): approx. 316x145x312 mm, weight: approx. 0,8 kg customs tariff no.: 3923 30 90	1,00	Pce
734,0	098821 Grease gun Fettpresse customs tariff no.: 3403 99 00	1,00	Pce
735,0	031166 Delivery hose S25 EN 1947 50 m, on both sides C coupling EN 1947 (former DIN 14817). Quick-intervention hose with multiple cord fibre layer (offset) for heavy-duty demands. Hose lining 8 mm, working pressure 20 bar, test pressure 30 bar, bursting pressure 45 bar. Inside dia. 25 mm, electrically conductive, on both sides size C coupling, length 50 m. customs tariff no.: 4009 32 00	1,00	Pce
736,0	042541 Multi-purpose branchpipe CM DIN 14365, PN 16, Storz C Normal type with housing, control device, tube, nozzle and mouth piece of light metal. Tube with insulation for cold. Dim.(WxHxD): approx. 450x98x165 mm. Weight: approx. 1,38 kg customs tariff no.: 8424 89 00	1,00	Pce
737,0	055828 Scaling ladder upper section, light alloy, Günzbg.Steigtech. EN 1147, 2,7 m, 7 rungs. Of light metal, rungs with heat-insulating and simultanesously handy protection. The foot caps with profiles are anti-slip and exchangeable. The shoes are of light metal, the pin bolts of steel. Weight: approx. 9,8 kg customs tariff no.: 7610 90 90	3,00	Pce
738,0	055829 Scaling ladder, lower section of light alloy	1,00	Pce