

1 MERCEDES-BENZ 3345 K 6x4 Z 13 "ZETROS"  
Chassis for tipper

## Special equipment

A1E Front axle 9.0 t  
A1X Straight front axle, increased ground clearance  
A2H Rear axle, crown wheel 300, planetary, 16.0 t  
A2Z Differential lock, rear axle  
A6J Axle ratio  $i = 5.333$   
B0A Pipe fracture protection, for braking system  
B1A Electronic braking system with ABS  
B1F Heating, electronic air-processing unit  
B1H Electr. compressed air supply and control, centre  
B1Z ABS, disengageable  
B2B Drum brakes on front and rear axle  
B2Z Parking brake, additional on front axle  
B4M Air reservoir, steel  
B5B Trailer brake, 2-line  
C00 Frame overhang 850 mm  
C3A Wheelbase 5100 mm  
C5J Mounting parts, for tipper  
C5T Reinforced frame  
C5V Frame front end, reinforced, for spec. attachments  
C6C Steering, single-circuit  
C6J Power steering pump, uncontrolled  
C6Q Stabiliser, front axle  
C6Y Stabiliser, under frame, rear axle  
C7C R.underride gd.fold., steel tipper, test force 80%  
C7I Battery carrier cover, lockable  
C7J Battery carrier, batteries side by side  
C8F Wing, for chassis transit  
D1B Driver's suspension seat, standard  
D1S Co-driver's suspension seat, standard  
D1Z Centre seat, with 3-point seat belt  
D2Y Seat belt monitor  
D4W Power windows, all-round  
D6F Air conditioning system  
D6Z Construction-site filter  
D7A Heat insulation, additional  
E1B Batteries 2 x 12 V/170 Ah, low-maintenance  
E1M Alternator, 28 V/150 A  
E2J Automatic cutouts  
E3C Additional socket, 24 V/15 A, in centre console  
E3J Socket, 24 V/10 A, on battery carrier

E5E Battery master switch, single-pin  
E6A Trailer socket, 24 V, 15-pin  
E6E Adapter, 15-pin to 2x7-pin socket  
E6Z Reversing buzzer  
F1Q M-cab  
F2G Cab width 2.30 m  
F2O Cab, 250 mm attachment height  
F2Z M-cab, Zetros, 2.30 m, level floor  
F4H Cab rear wall, without window  
F6C Windscreen, tinted  
F6M Main mirror heatable and electrically adjustable  
F6N Wide-angle mirror, heated  
F6O Kerb mirror  
F6Q Air horn  
F7B Bumper, with steel corners  
F7Y Cab entrance, left/right, movable  
F9Y Vehicle key, without transponder  
G0B Powertrain, 44 t to 80 t  
G0R Transmission support arms, optimised for removal  
G1J Transmission G 260-16/11.7-0.69  
G5B Double-disc clutch  
G5H Gearshift, manual  
I4I Wheel arrangement 6x4  
I5H 33.0-tonner  
I6B Tipper chassis  
I6W Leaf suspension, rear axle  
I8Y Model series Zetros Off-road  
I8Z Model series Zetros  
J1C Instrument cluster, 12.7 cm, with video function  
J1K Tachograph, 1 day + 2 drivers, modular  
J2E Radio with USB connector  
J4A Maintenance system  
K0S AdBlue tank, 75 l, right  
K5C Tank, 390 l, right, 650 x 565 x 1250 mm, steel  
K5M Tanks, lockable  
K5Q Fuel screen, tank filler neck  
K5R Protective plate for tank  
K7A Exhaust system, tailpipe vertical  
L1B Daytime driving lamps  
L1H Foglamps, halogen  
L1Q Tail lights, construc. in metal holder with grille  
L2B Auxiliary main-beam headlamp, additional, on roof  
L2K Rotating beacon, yellow, left and right, front  
L4Z Protective grille, metal, for headlamps  
L9E Pre-install. electr. interface, 10 A, non-MB body  
L9F Provision for fitting marker lights, side  
M0K Engine package, for heavy-duty operation  
M0S Noise encapsulation in accordance with ECE  
M3K Eng. OM460, inline 6, 12.8 l, 330kW (449hp), 2200 Nm  
M5S Engine version Euro V, export  
M5U Exhaust brake, standard system  
M6L Air compressor, 2-cylinder  
M7J Guard plate, bumper  
M8L Cyclone filter for coarse dust  
M8Y Fuel pre-filter, chassis-mounted, additional  
N2E PTO MB 131-2c, pump  
N6Z Transmission oil cooling

Q1M Front spring, 7.5 t, 3-leaf  
Q3B Rear springs, 2 x 13.0 t, for axle spacing 1450 mm  
Q8M End crossmember lower, reinforced  
Q8W End crossmember, 100 mm indented  
R0Z Wheel-nut cap  
R3P Tapered rims, 8.50-24, multi-piece  
R8A Spare wheel jack, side  
R8P Spare wheel/spare wheel rim  
S5A Speed limiter, 90 km/h (56 mph), ECE  
S5Z Cruise control  
S8A First aid kit  
S8B Fire extinguisher, 2 kg  
S8C Hazard warning triangle  
S8D Warning lamp  
U00 Control code, oil pan, aluminium, constr. site  
U2I Control code EBS, 4th generation  
V0T Vehicle class N3G, off-road vehicle  
V1K Zetros New  
V1W Standard  
V3F Zetros model generation 1  
V8A Chassis number FIN  
W5W Weight variant 33.0 t (7.5/13.0/13.0)  
X2A Model identification, acc. to weight variant  
X2E Model plate, EU  
X3Z Powertrain warranty as per T and Cs 3yrs/250,000km  
X4H Instrument/labels/documentation, German  
Y3I Grille, painted in vehicle colour  
Y4D Telescopic jack, 16 t/25 t  
Y4J 2 wheel chocks  
Y4V Air pressure gauge, analogue  
Y4Y Tyre inflating hose  
Z3Z Export code  
Z5M PTO, single  
Z5X Left-hand drive  
Z5Y Vehicle, for right-side traffic  
Z8S Main contractor, Wörth Plant