

1 MERCEDES-BENZ 2045 S 4x2 Z 13 "ZETROS"

Chassis for truck tractor

Special equipment

A1E Front axle 9.0 t
A1X Straight front axle, increased ground clearance
A2G Rear axle, crown wheel 300, planetary, 13.4 t
A2Z Differential lock, rear axle
A6C Axle ratio $i = 4.833$
B0A Pipe fracture protection, for braking system
B1A Electronic braking system with ABS
B1F Heating, electronic air-processing unit
B1H Electr. compressed air supply and control, centre
B1Z ABS, disengageable
B2B Drum brakes on front and rear axle
B2Z Parking brake, additional on front axle
B4M Air reservoir, steel
B5B Trailer brake, 2-line
B5I Brake and electrical connections, high
B5N Compressed air supply connection, front
B5Z Brake system for tandem combination
C0F Frame overhang 1000 mm
C30 Wheelbase 4700 mm
C5B Step plate above frame, partial cover
C5T Reinforced frame
C5V Frame front end, reinforced, for spec. attachments
C6C Steering, single-circuit
C6J Power steering pump, uncontrolled
C6Q Stabiliser, front axle
C6Y Stabiliser, under frame, rear axle
C7I Battery carrier cover, lockable
C7J Battery carrier, batteries side by side
C8G Wing, three-piece, without EC splash guard
D1B Driver's suspension seat, standard
D1U Co-driver's fixed seat, standard
D1Z Centre seat, with 3-point seat belt
D2Y Seat belt monitor
D4W Power windows, all-round
D6F Air conditioning system
D6Z Construction-site filter
D7A Heat insulation, additional
E1B Batteries 2 x 12 V/170 Ah, low-maintenance
E1M Alternator, 28 V/150 A
E2J Automatic cutouts
E6A Trailer socket, 24 V, 15-pin
E6Z Reversing buzzer

F1Q M-cab
F2G Cab width 2.30 m
F2O Cab, 250 mm attachment height
F2Z M-cab, Zetros, 2.30 m, level floor
F4H Cab rear wall, without window
F6C Windscreen, tinted
F6M Main mirror heatable and electrically adjustable
F6N Wide-angle mirror, heated
F6O Kerb mirror
F6Q Air horn
F7B Bumper, with steel corners
F7R Reinforced A-pillar
F7Y Cab entrance, left/right, movable
F9Y Vehicle key, without transponder
G0R Transmission support arms, optimised for removal
G1J Transmission G 260-16/11.7-0.69
G5A Single-disc clutch
G5H Gearshift, manual
H2I Fifth-wheel lead +900 mm
I4A Wheel arrangement 4x2
I5C 20.0-tonner
I6D Semitrailer tractor
I6W Leaf suspension, rear axle
I8Y Model series Zetros Off-road
I8Z Model series Zetros
J1C Instrument cluster, 12.7 cm, with video function
J1O Dig. tachograph, 2nd gen., working speed control
J1S Tachograph manufacturer VDO
J2E Radio with USB connector
J4A Maintenance system
J4X Belt warning w/ seat occup. detection, co-driver
K0S AdBlue tank, 75 l, right
K5C Tank, 390 l, right, 650 x 565 x 1250 mm, steel
K5G Second tank 390 l, left, 650x565x1250 mm, steel
K5M Tanks, lockable
K5R Protective plate for tank
K7A Exhaust system, tailpipe vertical
L1B Daytime driving lamps
L1Q Tail lights, construc. in metal holder with grille
L2B Auxiliary main-beam headlamp, additional, on roof
L2I Side marker lights
L4Z Protective grille, metal, for headlamps
M0K Engine package, for heavy-duty operation
M0S Noise encapsulation in accordance with ECE
M3K Eng. OM460, inline 6, 12.8 l, 330kW (449hp), 2200 Nm
M5S Engine version Euro V, export
M5U Exhaust brake, standard system
M6L Air compressor, 2-cylinder
M7J Guard plate, bumper
M8L Cyclone filter for coarse dust
M8Y Fuel pre-filter, chassis-mounted, additional
N6Z Transmission oil cooling
Q0X Configuration incompatible with Euro semitrailers
Q1Y Front spring, 9.0 t, 4-leaf
Q2V Rear spring, 13.0 t, hard
Q4K Fifth wheel coupling height = 185 mm
Q4X Fifth wheel coupling, manually lubricated

Q5Q Fifth wheel coupling, standard, Jost JSK 37C
Q6D Mounting plate, 40 mm, 20 t
Q6Y 5th-wheel bracket, w/ hole pattern, extend.,reinf.
R0Z Wheel-nut cap
R1Q 15-degree tapered rims, 9.00 x 22.5
R1T 15-degree tapered rims, 11.75 x 22.5, front axle
R8F Spare wheel carrier, provisional
R8P Spare wheel/spare wheel rim
S5A Speed limiter, 90 km/h (56 mph), ECE
S5Z Cruise control
S8A First aid kit
S8C Hazard warning triangle
S8D Warning lamp
U0O Control code, oil pan, aluminium, constr. site
U2I Control code EBS, 4th generation
V0T Vehicle class N3G, off-road vehicle
V1K Zetros New
V1W Standard
V3F Zetros model generation 1
V5Y Vehicle with sovereign rights
V8A Chassis number FIN
W1L Weight variant 22.0 t (9.0/13.0)
X1A Instrument/labels/documentation, English
X2A Model identification, acc. to weight variant
X2E Model plate, EU
X2S Test booklet
X2Y Registration certificate, Part II, prepared
X3Z Powertrain warranty as per T and Cs 3yrs/250,000km
Y3I Grille, painted in vehicle colour
Y4A Telescopic jack, 12 t/19 t
Y4H Holder for wheel chock
Y4J 2 wheel chocks
Y4V Air pressure gauge, analogue
Y4Y Tyre inflating hose
Z4B Domestic (Germany)
Z5X Left-hand drive
Z5Y Vehicle, for right-side traffic
Z8S Main contractor, Wörth Plant