

Mercedes Benz ZETROS 3342 A 6X6

General

Model:	Mercedes-Benz Zetros
Vehicle type:	3342 A
Drivetrain:	6X6
Baumuster:	95901812
Vehicle type:	Cowl vehicle
Engine power:	310 kW (421 PS)
Wheelbase:	5100 mm
Gross vehicle weight:	30000kg
Steering type:	left

Paint

Cab:	MB 9147 arctic white
------	----------------------

Chassis version

V1K	Zetros New
V1W	Standard
C3A	Wheelbase 5100 mm

Axle load distribution

W7V	Weight variant 30.0 t (9.0/10.5/10.5)
-----	---------------------------------------

Engine

M3J	Eng. OM460, inline 6, 12.8 l, 310kW (421hp),2100 Nm
M0K	Engine package, for heavy-duty operation
M5W	Engine version, Euro III
M8L	Cyclone filter for coarse dust
M8Y	Fuel pre-filter, chassis-mounted, additional
M5U	Exhaust brake, standard system
M6L	Air compressor, 2-cylinder

Clutch & transmission

G5A	Single-disc clutch
G1J	Transmission G 260-16/11.7-0.69
N6Z	Transmission oil cooling
G0R	Transmission support arms, optimised for removal
G4D	Transfer case VG 2800-3W/1.45-1.04, permanent
G4Z	Oil cooler, for transfer case
G5H	Gearshift, manual
N2E	PTO MB 131-2c, pump
Z5M	PTO, single
N6K	Gear shift interlock for PTO

Axles & suspension

A1E	Front axle 9.0 t
A1W	Differential lock, front axle
A2G	Rear axle, crown wheel 300, planetary, 13.4 t
A2Z	Differential lock, rear axle
A6J	Axle ratio $i = 5.333$
Q1Y	Front spring, 9.0 t, 4-leaf
Q3Q	Rear springs, 2 x 10.5 t, for axle spacing 1450 mm
C6Q	Stabiliser, front axle

Wheels & tyres

R4Y	Wide-base rims, 10.00W-20, tubeless, single tyres
R8A	Spare wheel jack, side
R8P	Spare wheel/spare wheel rim
1.A.	402KVA 10 2x 14.00 R 20 Cross country all pos.
2.A.	402KVA 10 2x 14.00 R 20 Cross country all pos.
3.A.	402KVA 10 2x 14.00 R 20 Cross country all pos.
	402KVA 10 1x 14.00 R 20 Cross country all pos.

Frame and components attached to frame

C5T	Reinforced frame
C5V	Frame front end, reinforced, for spec. attachments
C0L	Frame overhang 1300 mm
C6C	Steering, single-circuit
C6J	Power steering pump, uncontrolled
C7I	Battery carrier cover, lockable
C7J	Battery carrier, batteries side by side
K4Z	Tank, 290 l, right, 650 x 565 x 950 mm, steel
K5M	Tanks, lockable
K5Q	Fuel screen, tank filler neck
K5R	Protective plate for tank
K7D	Exhaust system, tailpipe to right and outwards
C8F	Wing, for chassis transit
F7B	Bumper, with steel corners
M7H	Protective plate, radiator to engine
M7J	Guard plate, bumper
Q8E	Tow-away coupling, rear, Rockinger
Q8M	End crossmember lower, reinforced

Brake system

B2B	Drum brakes on front and rear axle
B1A	Electronic braking system with ABS
B1Z	ABS, disengageable
B1F	Heating, electronic air-processing unit
B1H	Electr. compressed air supply and control, centre
B4M	Air reservoir, steel
B2Z	Parking brake, additional on front axle

Cab exterior

F1Q	M-cab
F2G	Cab width 2.30 m
F2O	Cab, 250 mm attachment height
F2Z	M-cab, Zetros, 2.30 m, level floor
F7R	Reinforced A-pillar
F4H	Cab rear wall, without window
F6C	Windscreen, tinted
F7Y	Cab entrance, left/right, movable
F6M	Main mirror heatable and electrically adjustable
F6N	Wide-angle mirror, heated
F6O	Kerb mirror
F6Q	Air horn
F9Y	Vehicle key, without transponder

Cab interior

D1B	Driver's suspension seat, standard
D1S	Co-driver's suspension seat, standard
D3Z	Seat cover, man-made leather
J1H	Instrument cluster, 12.7 cm
J1Z	Speedometer, deletion, tachograph
E6Z	Reversing buzzer
J4A	Maintenance system
E2J	Automatic cutouts
D6Z	Construction-site filter
D7A	Heat insulation, additional
D6F	Air conditioning system

Electrics / electronics

E1B	Batteries 2 x 12 V/170 Ah, low-maintenance
E1M	Alternator, 28 V/150 A
L9E	Pre-install. electr. interface, 10 A, non-MB body
E3W	PSM, 2nd generation
E4F	Pre-installation of electrical interface for BB
L1B	Daytime driving lamps
L4Z	Protective grille, metal, for headlamps
L2B	Auxiliary main-beam headlamp, additional, on roof
L1Q	Tail lights, construc. in metal holder with grille
L9F	Provision for fitting marker lights, side
E5V	ADR type class FL, incl. EX/II, EX/III and AT
S5A	Speed limiter, 90 km/h (56 mph), ECE
S5Z	Cruise control

Additional scopes

M0Z	Noise regulation acc. to UN-R 51.03, phase 1
S8A	First aid kit
S8C	Hazard warning triangle
S8D	Warning lamp
Y4A	Telescopic jack, 12 t/19 t
Y4V	Air pressure gauge, analogue
Y4Y	Tyre inflating hose
Y4F	Steel wheel chocks
Y4J	2 wheel-chocks
V0T	Vehicle class N3G, off-road vehicle
V8A	Chassis number FIN
X3Z	Powertrain warranty as per T and Cs 3yrs/250,000km
Y3I	Grille, painted in vehicle colour
V3F	Zetros model generation 1
X2A	Model identification, acc. to weight variant
X2E	Model plate, EU
X1A	Instrument/labels/documentation, English
Z5X	Left-hand drive
Z5Y	Vehicle, for right-side traffic

Spare-parts included

Air-filter kit	2x
Brake tensioners	2x
Drum-brake set front	2x
Drum-brake set rear	2x
Oil-filter cartridge steering	2x
Cartridge for fuel-supply filter	2x
V-belt	2x
Oil-filter cartridge	4x
Fuel-filter cartridge	4x
Dryer filter	4x
Dust-filter	4x
Windshield wipers	6x