



Vehicle description for: TGM 18.320 4x2 BB CH



Illustration can deviate

Vehicle standards		
	Product family	The new MAN Truck Generation
	Model & Variant	TGM 18.320 4x2 BB CH
	Emission class	EURO5
	Engine family	D08R6
	Engine output	235 kW
	Battery gross capacity	0 kWh
	Batteries number	0
	Vehicle type	Vehicle type, platform truck and chassis (LK)
	Body type	300 Beverage transporter
	Cab	DN cab: the crew cab (narrow, extra long, normal height)
	Main wheel distance	4425 mm
	Overhang	2325 mm
	Steering configuration	Left

Vertical Load		
	National Registration	Technical Load
Gross weight	18,000 kg	18,300 kg
Front axle	7,500 kg	7,500 kg
Rear axle	11,500 kg	11,500 kg

Horizontal Load		
	National Registration	Technical Load
Gross train weight	0 kg	0 kg



The printed images in this offer are for explanatory purposes and may differ from the actual configuration.
For further product information on the tire selection "selectively", please contact our sales staff.

Vehicle characteristics

Basic characteristics

<input type="checkbox"/>	Vehicle version for public service deployment	0P0H7
<input type="checkbox"/>	Chassis	0P2U9
<input type="checkbox"/>	Chassis class, light/medium	0P2UB
<input type="checkbox"/>	Merchant tonnage 18 t	0P8LF
<input type="checkbox"/>	Basic layout of vehicle, all-round	0PGCU
<input type="checkbox"/>	Frame type, normal height	0P2TS
<input type="checkbox"/>	Vehicle type, platform truck and chassis (LK)	0P2UQ
<input type="checkbox"/>	Left-hand-drive	0P3AS
<input type="checkbox"/>	Right-hand traffic	0P3F5
<input type="checkbox"/>	Vehicle documents in Arabic	0P2L0
<input type="checkbox"/>	Labelling in English	0P8NM
<input type="checkbox"/>	Signage in Arabic, additional	0P2JF
<input type="checkbox"/>	Cab position 530 mm (distance from frame lower edge to cab floor)	0PHBD

Registration

<input type="checkbox"/>	Vehicle approval, N3 class	0P3JR
<input type="checkbox"/>	Maximum speed limiter, 89 km/h, tolerance +1 km/h, electronic, engine speed regulation	0P2UJ
<input type="checkbox"/>	Maximum vehicle noise level not defined	0P2YN
<input type="checkbox"/>	Height over cab, unloaded up to 4,000 mm	0PHA1
<input type="checkbox"/>	Vehicle classification in accordance with regulation (EU) 2018/858	0PKAW

Documents

<input type="checkbox"/>	Without registration documentation, national	0P3B0
<input type="checkbox"/>	Special confirmation, heavy load / municipal operation	0P3CK

Application scope / transport tasks

<input type="checkbox"/>	Distribution transport, general cargo	0P6WA
<input type="checkbox"/>	Increase of the tyre load capacity by 10% (for communal supplement)	0P0UU
<input type="checkbox"/>	300 Beverage transporter	0P2RX
<input type="checkbox"/>	Temperature range, vehicle deployment, warm country	0PHIB
<input type="checkbox"/>	Case hardness of final drive Distribution	0P4F0

Lines, editions and packages

<input type="checkbox"/>	Special request paintwork	0PJTD
<input type="checkbox"/>	Without Individual Lion package	0PJT1

Horizontal and vertical loads

<input type="checkbox"/>	18,000 kg permitted gross load, vertical, nat. appr.	0P5PB
<input type="checkbox"/>	18,300 kg permitted gross load, vertical, tech.	0P5S6
<input type="checkbox"/>	18,300 kg permitted gross load, vertical, tech. Plus	0P8GS
<input type="checkbox"/>	7,500 kg permitted load on front axle, nat. appr.	0P5KR
<input type="checkbox"/>	7,500 kg permitted load on front axle, tech.	0P5LL
<input type="checkbox"/>	7,500 kg permitted load on front axle, tech. Plus	0P8D1
<input type="checkbox"/>	11,500 kg permitted load on rear axle NatZu	0P5G7



<input type="checkbox"/>	11,500 kg permitted load on rear axle, tech.	0P5IJ
<input type="checkbox"/>	11,500 kg permitted load on rear axle, tech. Plus	0P8BN
<input type="checkbox"/>	0kN D value	0P8XD

Notification texts

<input type="checkbox"/>	Note: With increased permissible gross weight, increase in wear of driveline and reduced service life	0PFZP
<input type="checkbox"/>	Note: Difference of more than 2% in FA/RA rolling circumference may lead to perceptible tension in the driveline.	0PHCX
<input type="checkbox"/>	Without note (propshaft wear)	0PJRV

Chassis

Vehicle frame (wheelbase, overhang, ...)

<input type="checkbox"/>	Main wheelbase, 4,425 mm	0P2ZV
<input type="checkbox"/>	Frame overhang, rear, 2,325 mm	0P3DT
<input type="checkbox"/>	Main frame side member thickness, 7 mm	0P0Y5
<input type="checkbox"/>	Vehicle rear, straight end of frame	0P0XT

Exhaust system, air intake

<input type="checkbox"/>	Exhaust silencer, side, right	0P1BH
<input type="checkbox"/>	Exhaust tailpipe, towards middle of frame	0P1BT
<input type="checkbox"/>	Air intake, behind cab, raised	0P0AY

Battery cases, batteries, alternator

<input type="checkbox"/>	2 batteries, 12 V, 150 Ah, standard (SLI), maintenance free	0PHLB
<input type="checkbox"/>	Three-phase alternator 28 V, 120 A, 3,360 W, Longlife Eco	0P1BW
<input type="checkbox"/>	Small battery box, 2 batteries	0P0WS
<input type="checkbox"/>	Battery box, left	0P0WO
<input type="checkbox"/>	Main battery switch, mechanical	0P0WF
<input type="checkbox"/>	Fuses	0P1V1
<input type="checkbox"/>	Lockable battery box, without padlock	0P0WK

Tanks and fuel line

<input type="checkbox"/>	300 l objem palivovej nádrže, vpravo	0P4E8
<input type="checkbox"/>	Fuel tank, right, steel	0P4GN
<input type="checkbox"/>	Tank cross-section, right, medium	0P4HE
<input type="checkbox"/>	AdBlue tank capacity 27 l, right	0P4CY
<input type="checkbox"/>	AdBlue tank, right, plastic	0P4HU
<input type="checkbox"/>	Fuel tank cap, lockable for master key system	0P4H5
<input type="checkbox"/>	Cap for AdBlue tank, lockable	0P4GE
<input type="checkbox"/>	Filter screen for fuel tank filler neck	0P1EM
<input type="checkbox"/>	Fuel pre-filter on the frame	0PKN2

Frame attachments

<input type="checkbox"/>	Underride protection, front	0P1FN
<input type="checkbox"/>	Without working platform	0P0VH
<input type="checkbox"/>	Without underride protection, side	0P1FG
<input type="checkbox"/>	Spare wheel, provisionally mounted	0P1GR



<input type="checkbox"/>	Final cross member, with hole pattern 160 x 100 mm	0P1SB
<input type="checkbox"/>	Underride protection, rear, round	0P1FD
<input type="checkbox"/>	Wheel chock, 2 unit, with retaining device	0P1FQ
<input type="checkbox"/>	Without body attachment brackets/thrust plates	0P0X6

Pneumatic brakes, compressed-air generation, brake system

<input type="checkbox"/>	Air compressor, 1-cylinder, 238 ccm	0P0AD
<input type="checkbox"/>	Air dryer, heated	0P0B2
<input type="checkbox"/>	Compressed-air treatment, electronically controlled	0P0AA
<input type="checkbox"/>	Steel compressed-air tank	0P0XH
<input type="checkbox"/>	Electronic brake system (EBS)	0P0BL
<input type="checkbox"/>	Anti-lock braking system (ABS)	0P0BE
<input type="checkbox"/>	Full brake assistant	0P0CM
<input type="checkbox"/>	Without preparation for EBS Full control unit	0PHPM
<input type="checkbox"/>	Engine brake, exhaust flap	0P0BU
<input type="checkbox"/>	Disc brakes on front axle	0P1I9
<input type="checkbox"/>	Disc brakes on rear axle	0P1I4
<input type="checkbox"/>	Parking brake control, next to driver's seat	0P3KH
<input type="checkbox"/>	Parking brake with spring-type actuator on rear axles (incl. leading axle/ trailing axle)	0PGBL
<input type="checkbox"/>	MAN EasyStart immobiliser	0P1TF
<input type="checkbox"/>	Brake lining thickness display, with brake lining wear warning	0P0BG

Lights and acoustic signals on the chassis (rear lights, ...)

<input type="checkbox"/>	Rear lights	0P2AQ
<input type="checkbox"/>	Acoust. Reversing warning system when reverse gear selected	0P3CD
<input type="checkbox"/>	Light function test	0P2AD
<input type="checkbox"/>	No side marker lights	0P2BK

Driveline/running gear

Engine, radiator

<input type="checkbox"/>	Diesel engine MAN D0836 LFL91, 235 kW (320 hp) output, 1,250 Nm torque, Euro 5	0P5YJ
<input type="checkbox"/>	Fuel filter, heated, for fuels up to Cleanliness Class 25	0PHIG
<input type="checkbox"/>	Fuel pre-filter, with oil separator/water trap, with water sensor, heated	0P4XP
<input type="checkbox"/>	Without torque reduction	0P0G5
<input type="checkbox"/>	Engine dry-air filter, with safety insert	0P0B8
<input type="checkbox"/>	Ventilation, crankcase, closed	0P8PM
<input type="checkbox"/>	Engine skirt, in wheel arch, to prevent engine soiling	0P2E9
<input type="checkbox"/>	Engine cooler, normal length	0P4XX
<input type="checkbox"/>	Engine oil dipstick	0P0B5
<input type="checkbox"/>	Antifreeze, down to -32 °C	0P0AK
<input type="checkbox"/>	Service product level indicator and intake system vacuum	0P3KT

Gearbox, clutch

<input type="checkbox"/>	MAN PowerMatic 08.13 OD	0PHMK
<input type="checkbox"/>	Gearbox for normal percentage of overrun during driving operation	0PGDA
<input type="checkbox"/>	Gearbox, 8-speed	0PHML
<input type="checkbox"/>	MAN TipMatic actuation, with drop arm, manual (DNR option, switching strategy option)	0P3KI



<input type="checkbox"/>	MAN Idle Speed Driving gearbox function	0P0ER
<input type="checkbox"/>	MAN TipMatic Efficiency driving program, up to 70,000 kg	0P0FA
<input type="checkbox"/>	Without drive clutch	0PIXX
<input type="checkbox"/>	Main propshaft, 14,000 Nm functional limit torque	0PKZG
<input type="checkbox"/>	Propshafts with standard grease, cannot be lubricated	0PKZL
<input type="checkbox"/>	Gearbox heat exchanger	0P0FW

Wheels, tyres

<input type="checkbox"/>	Required tyre speed index G	0PFWA
<input type="checkbox"/>	Front axle tyres optionally 295/80R22.5 Steering-Short-haul TL (154/148 K)	0PEV9
<input type="checkbox"/>	Rim type, front axle, steel, single-part	0P0P0
<input type="checkbox"/>	Rim size, front axle, 10-hole, 9.00x22.5	0P0NI
<input type="checkbox"/>	Rear axle tyres optionally 295/80R22.5 Steering-Short-haul TL (154/148 K)	0PDPH
<input type="checkbox"/>	Rim type, rear axle, steel, single-part	0P0OO
<input type="checkbox"/>	Rim size, rear axle, 10-hole, 8.25x22.5	0P0MQ
<input type="checkbox"/>	Spare wheel, in accordance with configuration for front axle tyres	0P0MH
<input type="checkbox"/>	Tyre inflation hose, 20 m, with pressure gauge	0P1UA

Axles

<input type="checkbox"/>	4x2	0P3B1
<input type="checkbox"/>	Steering ratio, standard	0P1JX
<input type="checkbox"/>	Steering oil tank with dipstick	0P1JW
<input type="checkbox"/>	Front axle, 7,500 kg, not driven, cranked, steered, not liftable	0P5EQ
<input type="checkbox"/>	Mudguard, front axle	0P1AT
<input type="checkbox"/>	Splash guard mat on mudguard, front axle, longer at bottom	0P1XS
<input type="checkbox"/>	Rear axle, 11,500 kg, HY axle without drive shaft, straight, not steered, not liftable	0P4ZL
<input type="checkbox"/>	Twin tyre on rear axle	0P1HN
<input type="checkbox"/>	Transfer mudguard, rear axle	0P1AQ
<input type="checkbox"/>	Axle ratio, $i = 4.63$	0P0D9
<input type="checkbox"/>	Differential locks on driven rear axles	0P0DI
<input type="checkbox"/>	Without differential locks, front axles	0P0DL

Axle control system and suspension

<input type="checkbox"/>	Suspension type for front axles and driven rear axles, leaf/leaf (BB)	0P2YB
<input type="checkbox"/>	Leaf-spring suspension on front axle, parabolic, 1-leaf, steel	0P1JC
<input type="checkbox"/>	Leaf-spring suspension on rear axle, parabolic, 4-leaf, steel	0PGBF
<input type="checkbox"/>	Spring load-bearing capacity front axle 7,500 kg	0P5CZ
<input type="checkbox"/>	Spring load-bearing capacity of rear axle, 11,500 kg	0P5BT
<input type="checkbox"/>	Shock absorbers on front axle	0P1M4
<input type="checkbox"/>	Shock absorbers on rear axle	0P1LQ
<input type="checkbox"/>	Stabiliser, front axle	0P1LD
<input type="checkbox"/>	Stabiliser, rear axle	0P1LA
<input type="checkbox"/>	Axle location system not as wishbone	0P6ZY
<input type="checkbox"/>	Without air suspension control, trailer/semitrailer	0PHN2

Cab

Cab and cab exterior



<input type="checkbox"/>	DN cab: the crew cab (narrow, extra long, normal height)	0P2DE
<input type="checkbox"/>	Cab mount, Comfort	0P1V9
<input type="checkbox"/>	Cab tilt mechanism, manual	0P1V6
<input type="checkbox"/>	Tilting roof, mechanical	0P1VW
<input type="checkbox"/>	Bumper, steel, 3 pieces	0P1SG
<input type="checkbox"/>	Front step, integrated, with grab option	0P1VE
<input type="checkbox"/>	Windscreen, composite safety glass, tinted	0P1X0
<input type="checkbox"/>	Sunblind, in front of windscreen	0P1WK
<input type="checkbox"/>	Wiper system for windscreen	0P1WG
<input type="checkbox"/>	Wiper activation, manual	0P1UL
<input type="checkbox"/>	Step unit, rigid	0P1UZ
<input type="checkbox"/>	Central locking, no remote control	0P1WS
<input type="checkbox"/>	Vehicle key, 4 units	0P3JU
<input type="checkbox"/>	No door extension	0P1WV
<input type="checkbox"/>	Door labelling, according to maximum technically permitted overall vehicle weight	0P2DO
<input type="checkbox"/>	Door windows, tinted	0P1WO
<input type="checkbox"/>	Door window, safety glass	0P1WM
<input type="checkbox"/>	Cab rear wall, no window	0P1VD

Lights and acoustic signals on cab exterior (headlights, horn, ...)

<input type="checkbox"/>	H7 package, front headlights, fog lights	0PKWS
<input type="checkbox"/>	Front headlights, H7	0P1ZN
<input type="checkbox"/>	Stone protection for front headlights, guard, wide mesh	0P1ZT
<input type="checkbox"/>	Daytime driving lights, LED	0P2BP
<input type="checkbox"/>	Fog lights, H7	0P2AH
<input type="checkbox"/>	Turn signal lights, sides, bulb	0P1Z6
<input type="checkbox"/>	Headlight beam regulator, manual	0P2AC
<input type="checkbox"/>	Driving-light control, manual	0P1ZF
<input type="checkbox"/>	Contour lights, LED, 2 units	0P2BS
<input type="checkbox"/>	Comfort indicator function, can be activated	0P1ZW
<input type="checkbox"/>	Horn, single-tone, electrical	0P1W0
<input type="checkbox"/>	Preparation for additional lighting, on cab roof	0P2C5
<input type="checkbox"/>	Preparation for additional lighting, vehicle rear	0P2C3
<input type="checkbox"/>	Without revolving beacons at the rear of the vehicle	0PJRO

Mirrors and mirror replacements

<input type="checkbox"/>	Exterior rear-view mirror, manually adjustable, front mirror, kerb mirror, right	0PKWY
<input type="checkbox"/>	Exterior rear-view mirror, mechanically adjustable	0P2CC
<input type="checkbox"/>	Kerb mirror, right, mechanically adjustable	0P2CH
<input type="checkbox"/>	Front mirror, mechanical adjustment	0P2CJ
<input type="checkbox"/>	Mirror label, Arabic language	0P2CY
<input type="checkbox"/>	Mirror housing, not painted	0P2CP
<input type="checkbox"/>	Vehicle components, suitable for body width larger than 2,400 mm to 2,600 mm	0P2CT

Seats

<input type="checkbox"/>	Seat covers, fabric, standard	0P2PQ
<input type="checkbox"/>	Plus driver's seat package, air-sprung	0PKXF
<input type="checkbox"/>	Comfort driver's seat, air-sprung	0P2P2
<input type="checkbox"/>	Basic co-driver's seat package, unsprung, fore-and-aft, height and backrest adjustment	0PKTX



- | | | |
|--------------------------|--|-------|
| <input type="checkbox"/> | Co-driver's seat, not sprung, length, height and backrest adjustment | 0P2OP |
| <input type="checkbox"/> | Rear bench seat for 4 persons | 0P2Q2 |

Driver's workplace

- | | | |
|--------------------------|---|-------|
| <input type="checkbox"/> | Multi-function steering wheel, adjustable height and angle | 0P2GD |
| <input type="checkbox"/> | Steering wheel, with parking position | 0P2GE |
| <input type="checkbox"/> | Steering lock | 0P3JZ |
| <input type="checkbox"/> | Professional instrumentation, 12.3" | 0P3L2 |
| <input type="checkbox"/> | Tachograph Simulation Unit (TSU), instead of tachograph | 0P2KY |
| <input type="checkbox"/> | Tachograph, calibrated | 0P2KG |
| <input type="checkbox"/> | Socket, cab centre, 2 units, 12 V and 24 V | 0P2HX |
| <input type="checkbox"/> | Plug-in ashtray, instrument panel in middle section, 1 unit | 0P2FO |
| <input type="checkbox"/> | Cigarette lighter | 0P2IH |
| <input type="checkbox"/> | Single DIN slots, 4 units, roof space, front | 0P2FJ |
| <input type="checkbox"/> | Without storage tray next to seat | 0PJRS |

Cab air-conditioning system

- | | | |
|--------------------------|---------------------------------|-------|
| <input type="checkbox"/> | Air-conditioning system, manual | 0P2NU |
|--------------------------|---------------------------------|-------|

Bunk area

- | | | |
|--------------------------|-------------------|-------|
| <input type="checkbox"/> | Without bunk area | 0PKFY |
|--------------------------|-------------------|-------|

Cab interior

- | | | |
|--------------------------|---|-------|
| <input type="checkbox"/> | Colour scheme for interior styling, dark | 0P2I6 |
| <input type="checkbox"/> | Interior styling analogous to colour scheme | 0PGBT |
| <input type="checkbox"/> | Basic driver's workplace package | 0PKPN |
| <input type="checkbox"/> | Windscreen roller blind, internal | 0P2FE |
| <input type="checkbox"/> | Interior light, reading light (driver's side) | 0PKMY |
| <input type="checkbox"/> | Interior light, central | 0PHA6 |
| <input type="checkbox"/> | Reading light, 1 unit, driver's side | 0P2IQ |
| <input type="checkbox"/> | Entry lighting | 0P2IO |
| <input type="checkbox"/> | Entry handles, standard | 0PHPK |
| <input type="checkbox"/> | Door interior cladding, washable | 0P2IA |
| <input type="checkbox"/> | Drawer in middle section | 0PKWC |
| <input type="checkbox"/> | Drawer, 1 unit, instrument panel in middle section | 0P2HJ |
| <input type="checkbox"/> | Multi-purpose storage box, centre of crew cab, in front of 2nd row of seats | 0P2ES |
| <input type="checkbox"/> | Grab handle, above door, internal, 2 units, 1 right and 1 left | 0P2G2 |
| <input type="checkbox"/> | Grab handles on cab roof interior, rear | 0P8QG |

Accessories and tools

- | | | |
|--------------------------|--|-------|
| <input type="checkbox"/> | Vehicle tool kit without accessories | 0PKXB |
| <input type="checkbox"/> | Vehicle toolkit | 0P2TX |
| <input type="checkbox"/> | No warning triangle | 0P3FH |
| <input type="checkbox"/> | Jack, 10,000 kg | 0P3F7 |
| <input type="checkbox"/> | Operator's manual in Arabic, printed, additional | 0PHZY |

Intelligent Truck

Assistance systems



<input type="checkbox"/>	Electronic Stability Program (ESP)	0P1TN
<input type="checkbox"/>	Anti-slip control (ASR)	0P1T2
<input type="checkbox"/>	Tempomat (cruise control, CC)	0P1TR
<input type="checkbox"/>	Without advanced emergency braking system	0P1U5
<input type="checkbox"/>	Without driving fitness detection system	0PHN5
<input type="checkbox"/>	Without Front Detection	0PHNA
<input type="checkbox"/>	Without traffic sign recognition	0PHNE
<input type="checkbox"/>	Without Reversing Motion System	0PHNV
<input type="checkbox"/>	Without distance warning system	0PKA0
<input type="checkbox"/>	Without MAN SafeStop Assist	0PLB5

Infotainment (radio,...)

<input type="checkbox"/>	Radio preparation, 12 V	0P2M4
<input type="checkbox"/>	Loudspeaker, door, 2 units, 1 left and 1 right	0P2ME
<input type="checkbox"/>	No navigation map	0P2N2
<input type="checkbox"/>	English additionally for display	0P2JQ

Bodies/interfaces

Interfaces to semitrailer (e.g. fifth-wheel coupling, brake connection,...)

<input type="checkbox"/>	Without trailer brake connection behind cab	0P1O3
<input type="checkbox"/>	No fifth-wheel coupling	0P1RJ
<input type="checkbox"/>	Without sensing of the fifth-wheel coupling	0PHN7

Interfaces to trailer (e.g. trailer coupling, brake connections,...)

<input type="checkbox"/>	Towing coupling at final cross member, ROCKINGER SK5	0P1MZ
<input type="checkbox"/>	Towing coupling on final cross member	0P1SH
<input type="checkbox"/>	Without trailer brake connection at end of frame, centre	0P1O0
<input type="checkbox"/>	Without trailer socket at frame end	0P1OW
<input type="checkbox"/>	Without trailer socket for anti-lock brake system (ABS)	0P1O9

Ex works bodies and interfaces to bodies (e.g. tipper indicator...)

<input type="checkbox"/>	Interface for digital data exchange (Application Fit)	0PIXU
<input type="checkbox"/>	Interface for extended signal output (EIO)	0PJBE

PTOs

<input type="checkbox"/>	Without fan wheel for PTO, gearbox-dependent	0P4VR
<input type="checkbox"/>	Preparation, electr., for subsequent installation of a shiftable PTO, gearbox-dependent	0P4OI

Towing, recovery and lashing

<input type="checkbox"/>	Central coupling jaw, integrated in bumper/front cross member, with lock pin	0P1MK
<input type="checkbox"/>	Shackles, 2 units, front of vehicle	0P1S3

Paintworks

Paintwork, cab, top

<input type="checkbox"/>	Top coating, cab	0P6YB
--------------------------	------------------	-------



Paintwork, cab, bottom			
<input type="checkbox"/>	Textured coating, step units	0P6X9	
<input type="checkbox"/>	Textured coating, mudguard, behind cab	0P6YG	
<input type="checkbox"/>	Textured coating, bumper, steel	0P6YQ	
Paintwork, chassis			
<input type="checkbox"/>	Without additional top coating on chassis	0PJTK	
<input type="checkbox"/>	Top coating, rims, steel, white-aluminium	0P6YL	
Additional operating equipment			
<input type="checkbox"/>	Eintrag in KFZ-Brief: Anhängelast 40.000kg bei Zgg. 59.000kg	ZW001	
Colour			
<input type="checkbox"/>	Top coating, cab	FLAME RED RAL 3000	N



Technical data: TGM 18.320 4x2 BB CH / L08DAA04

Vehicle type: Vehicle type, platform truck and chassis (LK)

Cab: DN cab: the crew cab (narrow, extra long, normal height)

Drive Type: 4x2

Lengths		mm
TD071	Total length	8445.0
TD063	Front vehicle overhang	1530.0
TD057	Wheelbase between front axles	0
TD058	Wheelbase between leading axle and rear axle	0
TD059	Wheelbase between rear axles	0
TD060	Wheelbase between rear axle and trailing axle	0
TD064	Rear frame overhang	2325.0
TD072	Distance from first front axle to body	1604.0
TD067	Distance to kingpin from front axle, nominal position	-
TD074	Slew radius, front	-
TD075	Slew radius, rear	-
TD068	Coupling length	8130.0

Widths		mm
TD008	Width included rearview mirror	2981.0
TD001	Width over cab	2240.0

Frame		mm
TD009	Frame width at front	964.0
TD010	Frame width at the rear	864.0
TD078	Frame profile	270 x 70 x 7

Heights		mm
TD033	Maximum external height, unladen	3031.0
TD082	Total transport height, unladen	3031.0
TD034	Maximum external height, laden	2953.0
TD035	Frame height at theoretical rear wheelbase, unladen	1107.0
TD036	Frame height at theoretical rear wheelbase, laden	976.0
TD045	Raising from driving position, front	0.0
TD046	Lowering from driving position, front	0.0
TD047	Raising from driving position, rear	0.0
TD048	Lowering from driving position, rear	0.0
TD051	Height of fifth-wheel coupling above ground, unladen	-
TD052	Height of fifth-wheel coupling above ground, laden	-

Circle dimensions		m
TD055	Track circle diameter	15.5
TD056	Wall-to-wall turning circle diameter	17.0

Weights/loads		kg
TD026	Chassis weight with cab	5909.0
TD027	Chassis weight, front	---
TD028	Chassis weight, rear	---
TD029	Payload	---

TD018	Statutorily permissible gross vehicle weight	18000
TD025	Technically permissible gross vehicle weight	18300
TD031	Statutorily permissible gross train weight	0
TD032	Statutorily permissible trailer load	0

The technical data must be considered as an approximation. Some of the values are given in a simplified form. More detailed notes and descriptions can be found in the respective information in the overview. Contents and specifications have been compiled with the greatest possible care. Nevertheless, we do not assume responsibility for the data and values supplied being correct and up to date. Subject to errors and changes. MAN Truck & Bus AG is liable only in cases of intent, gross negligence or culpable breach of significant contractual obligations.