



Vehicle description for: TGM 18.250 4x2 BB CH



Illustration can deviate

Vehicle standards

Product family	The new MAN Truck Generation
Model & Variant	TGM 18.250 4x2 BB CH
Emission class	EURO5
Engine family	D08R6
Engine output	184 kW
Vehicle type	Vehicle type, platform truck and chassis (LK)
Body type	060 Box body, universal
Cab	Compact CC cab
Main wheel distance	5425 mm
Overhang	2875 mm
Steering configuration	Left

Vertical Load

	National Registration	Technical Load	Technical Load Plus
Gross weight	17,000 kg	18,600 kg	18,600 kg
Front axle	6,300 kg	7,100 kg	7,100 kg
Rear axle	11,000 kg	11,500 kg	11,500 kg

Horizontal Load

	National Registration	Technical Load	Technical Load Plus
Gross train weight	0 kg	0 kg	0 kg



The printed images in this offer are for explanatory purposes and may differ from the actual configuration.
For further product information on the tire selection "selectively", please contact our sales staff.

Vehicle characteristics

Basic characteristics

<input type="checkbox"/>	Application area, beside road easy (T1)	0PLSE
<input type="checkbox"/>	Vehicle version for public service deployment	0P0H7
<input type="checkbox"/>	Chassis	0P2U9
<input type="checkbox"/>	Chassis class, light/medium	0P2UB
<input type="checkbox"/>	Destination: Ghana (GH)	0P3GJ
<input type="checkbox"/>	Merchant tonnage 18 t	0P8LF
<input type="checkbox"/>	Basic layout, weight-optimised vehicle	0PLSK
<input type="checkbox"/>	Frame type, normal height	0P2TS
<input type="checkbox"/>	Vehicle type, platform truck and chassis (LK)	0P2UQ
<input type="checkbox"/>	Left-hand-drive	0P3AS
<input type="checkbox"/>	Right-hand traffic	0P3F5
<input type="checkbox"/>	Vehicle documents in English	0P2L7
<input type="checkbox"/>	Labelling in English	0P8NM
<input type="checkbox"/>	Cab position 530 mm (distance from frame lower edge to cab floor)	0PHBD

Registration

<input type="checkbox"/>	Vehicle approval, N3 class	0P3JR
<input type="checkbox"/>	Maximum speed limiter, 80 km/h, electronic, engine speed regulation	0P2UG
<input type="checkbox"/>	Maximum vehicle noise level, 80 dB in acc. with UN/ECE-R 51.02	0PINC
<input type="checkbox"/>	Height over cab, unloaded up to 4,000 mm	0PHA1
<input type="checkbox"/>	Vehicle classification in accordance with regulation (EU) 2018/858	0PKAW

Documents

<input type="checkbox"/>	Without registration documentation, national	0P3B0
--------------------------	--	-------

Application scope / transport tasks

<input type="checkbox"/>	Fire service/emergency services	0P6WN
<input type="checkbox"/>	060 Box body, universal	0P2QS
<input type="checkbox"/>	Temperature range, vehicle deployment, warm country	0PHIB
<input type="checkbox"/>	Case hardness of final drive Distribution	0P4F0

Lines, editions and packages

<input type="checkbox"/>	Without Efficient Drive	0PVBQ
<input type="checkbox"/>	Special request paintwork	0PJTD
<input type="checkbox"/>	Without Individual Lion package	0PJT1

Horizontal and vertical loads

<input type="checkbox"/>	17,000 kg permitted gross load, vertical, nat. appr.	0P5O6
<input type="checkbox"/>	18,600 kg permitted gross load, vertical, tech.	0P5S7
<input type="checkbox"/>	18,600 kg permitted gross load, vertical, tech. Plus	0P8GT
<input type="checkbox"/>	6,300 kg permitted load on front axle, nat. appr.	0P5KM
<input type="checkbox"/>	7,100 kg permitted load on front axle, tech.	0P5LK
<input type="checkbox"/>	7,100 kg permitted load on front axle, tech. Plus	0P8DY
<input type="checkbox"/>	11,000 kg permitted load on rear axle NatZu	0P5G4
<input type="checkbox"/>	11,500 kg permitted load on rear axle, tech.	0P5IJ



- | | | |
|--------------------------|---|-------|
| <input type="checkbox"/> | 11,500 kg permitted load on rear axle, tech. Plus | 0P8BN |
| <input type="checkbox"/> | 0kN D value | 0P8XD |

Notification texts

- | | | |
|--------------------------|---|-------|
| <input type="checkbox"/> | Note: With increased permissible gross weight, increase in wear of driveline and reduced service life | 0PFZP |
| <input type="checkbox"/> | Note: Difference of more than 2% in FA/RA rolling circumference may lead to perceptible tension in the driveline. | 0PHCX |
| <input type="checkbox"/> | Without note (propshaft wear) | 0PJRV |

Chassis

Vehicle frame (wheelbase, overhang, ...)

- | | | |
|--------------------------|--|-------|
| <input type="checkbox"/> | Main wheelbase, 5,425 mm | 0P3A9 |
| <input type="checkbox"/> | Frame overhang, rear, 2,875 mm | 0P3EB |
| <input type="checkbox"/> | Main frame side member thickness, 7 mm | 0P0Y5 |
| <input type="checkbox"/> | Vehicle rear, straight end of frame | 0P0XT |

Exhaust system, air intake

- | | | |
|--------------------------|---|-------|
| <input type="checkbox"/> | Exhaust silencer, side, right | 0P1BH |
| <input type="checkbox"/> | Exhaust tailpipe, towards middle of frame | 0P1BT |
| <input type="checkbox"/> | Air intake, behind cab, raised | 0P0AY |
| <input type="checkbox"/> | Pre-separator for engine air intake | 0P0BA |

Battery cases, batteries, alternator

- | | | |
|--------------------------|--|-------|
| <input type="checkbox"/> | 2 batteries, 12 V, 180 Ah, long-life (EFB), maintenance free | 0PGB1 |
| <input type="checkbox"/> | Three-phase alternator 28 V, 120 A, 3,360 W, Longlife Eco | 0P1BW |
| <input type="checkbox"/> | Medium battery box, 2 batteries | 0P0WU |
| <input type="checkbox"/> | Battery box, left | 0P0WO |
| <input type="checkbox"/> | Main battery switch, mechanical | 0P0WF |
| <input type="checkbox"/> | Fuses | 0P1V1 |

Tanks and fuel line

- | | | |
|--------------------------|---|-------|
| <input type="checkbox"/> | Fuel tank capacity 300 l, right | 0P4E8 |
| <input type="checkbox"/> | Fuel tank, right, steel | 0P4GN |
| <input type="checkbox"/> | Tank cross-section, right, low | 0P4HF |
| <input type="checkbox"/> | AdBlue tank capacity 35 l, right | 0P4CZ |
| <input type="checkbox"/> | AdBlue tank, right, plastic | 0P4HU |
| <input type="checkbox"/> | Fuel tank cap, lockable for master key system | 0P4H5 |
| <input type="checkbox"/> | Cap for AdBlue tank, lockable | 0P4GE |
| <input type="checkbox"/> | Fuel pre-filter on the frame | 0PKN2 |

Frame attachments

- | | | |
|--------------------------|---|-------|
| <input type="checkbox"/> | Underride protection, front | 0P1FN |
| <input type="checkbox"/> | Without working platform | 0P0VH |
| <input type="checkbox"/> | Without underride protection, side | 0P1FG |
| <input type="checkbox"/> | Spare wheel hoist on left side, in front of rear axle | 0P0XO |
| <input type="checkbox"/> | Hoist for spare wheel | 0P0VN |
| <input type="checkbox"/> | Final cross member, with hole pattern 160 x 100 mm | 0P1SB |
-



<input type="checkbox"/>	Underride protection, rear, round	0P1FD
<input type="checkbox"/>	Wheel chock, 1 unit, with retaining device	0P1FO
<input type="checkbox"/>	Without body attachment brackets/thrust plates	0P0X6

Pneumatic brakes, compressed-air generation, brake system

<input type="checkbox"/>	Air compressor, 1-cylinder, 238 ccm	0P0AD
<input type="checkbox"/>	Air dryer, heated	0P0B2
<input type="checkbox"/>	Compressed-air treatment, electronically controlled	0P0AA
<input type="checkbox"/>	Steel compressed-air tank	0P0XH
<input type="checkbox"/>	Electronic brake system (EBS)	0P0BL
<input type="checkbox"/>	Anti-lock braking system (ABS)	0P0BE
<input type="checkbox"/>	Full brake assistant	0P0CM
<input type="checkbox"/>	Without preparation for EBS Full control unit	0PHPM
<input type="checkbox"/>	MAN EVB high-performance engine brake	0P0BV
<input type="checkbox"/>	Disc brakes on front axle	0P1I9
<input type="checkbox"/>	Disc brakes on rear axle	0P1I4
<input type="checkbox"/>	Parking brake control, next to driver's seat	0P3KH
<input type="checkbox"/>	Parking brake with spring-type actuator on rear axles (incl. leading axle/ trailing axle)	0PGBL
<input type="checkbox"/>	MAN EasyStart immobiliser	0P1TF
<input type="checkbox"/>	Brake lining thickness display, with brake lining wear warning	0P0BG

Lights and acoustic signals on the chassis (rear lights, ...)

<input type="checkbox"/>	Rear lights	0P2AQ
<input type="checkbox"/>	Acoust. Reversing warning system when reverse gear selected	0P3CD
<input type="checkbox"/>	Light function test	0P2AD
<input type="checkbox"/>	No side marker lights	0P2BK

Driveline/running gear

Engine, radiator

<input type="checkbox"/>	Diesel engine MAN D0836 LFL89, 184 kW (250 hp) output, 1,050 Nm torque, Euro 5	0P5ZX
<input type="checkbox"/>	Fuel filter, heated, for fuels up to Cleanliness Class 25	0PHIG
<input type="checkbox"/>	Fuel pre-filter, with oil separator/water trap, with water sensor, heated	0P4XP
<input type="checkbox"/>	Without torque reduction	0P0G5
<input type="checkbox"/>	Ventilation, crankcase, closed	0P8PM
<input type="checkbox"/>	Anti-noise skirt, engine	0P2E7
<input type="checkbox"/>	Engine cooler, normal length	0P4XX
<input type="checkbox"/>	Engine oil dipstick	0P0B5
<input type="checkbox"/>	Antifreeze, down to -32 °C	0P0AK

Gearbox, clutch

<input type="checkbox"/>	MAN PowerMatic 08.13 OD	0PHMK
<input type="checkbox"/>	Gearbox for normal percentage of overrun during driving operation	0PGDA
<input type="checkbox"/>	Gearbox, 8-speed	0PHML
<input type="checkbox"/>	MAN TipMatic actuation, with drop arm, manual (DNR option, switching strategy option)	0P3KI
<input type="checkbox"/>	MAN Idle Speed Driving gearbox function	0P0ER
<input type="checkbox"/>	MAN TipMatic Efficiency driving program, up to 70,000 kg	0P0FA
<input type="checkbox"/>	Without drive clutch	0PIXX



- Main propshaft, 14,000 Nm functional limit torque 0PKZG
- Propshafts with standard grease, cannot be lubricated 0PKZL
- Gearbox heat exchanger 0P0FW

Wheels, tyres

- Required tyre speed index F 0PFW9
- Tyres for front axle, Goodyear 295/80R22.5 OMNITRAC S Steering-Road+Offroad TL 0PGJZ



The image shows a Goodyear OMNITRAC S tyre on a wheel. To the right is the EU Energy Label for the tyre. The label includes the following information:

- Brand: Goodyear, Tyre type identifier: 569544
- Size: 295/80R22,5 152/148 K, Speed category: C3
- Fuel efficiency class: D (indicated by a black arrow pointing to 'D' on the scale)
- Wet grip class: B (indicated by a black arrow pointing to 'B' on the scale)
- External rolling noise: 71 dB (indicated by a black arrow pointing to '71 dB' on the scale)
- Severe snow tyre: YES (indicated by a snowflake icon)

Product Information Sheet

Delegated Regulation (EU) 2020/740

Supplier name or trademark	GOODYEAR
Commercial name or trade designation	OMNITRAC S
Tyre type identifier	569544
Tyre size designation	295/80R22.5
Load-capacity index	152
Load-capacity index (Load index for Dual mounting)	148
Speed category symbol	K
Fuel efficiency class	D
Wet grip class	B
External rolling noise class	A
External rolling noise value	71 dB
Severe snow tyre	YES
Date of start of production	40/18
Date of end of production	-
Additional information	
Load-capacity index (Single load index for Additional Service Description)	
Load-capacity index (Dual load index for Additional Service Description)	
Speed category symbol (for Additional Service Description)	

- Rim type, front axle, steel, single-part 0P0P0
- Rim size, front axle, 10-hole, 9.00x22.5 0P0N1



- Wheel nut cover ring, front axle 0P0PR
- Tyres for rear axle, Goodyear 295/80R22.5 OMNITRAC D Drive-Road+Offroad TL 0PGEB



Product Information Sheet

Delegated Regulation (EU) 2020/740

Supplier name or trademark	GOODYEAR
Commercial name or trade designation	OMNITRAC D
Tyre type identifier	569562
Tyre size designation	295/80R22.5
Load-capacity index	152
Load-capacity index (Load index for Dual mounting)	148
Speed category symbol	K
Fuel efficiency class	D
Wet grip class	B
External rolling noise class	B
External rolling noise value	75 dB
Severe snow tyre	YES
Date of start of production	40/18
Date of end of production	-
Additional information	
Load-capacity index (Single load index for Additional Service Description)	
Load-capacity index (Dual load index for Additional Service Description)	
Speed category symbol (for Additional Service Description)	

- Rim type, rear axle, steel, single-part 0P000
- Rim size, rear axle, 10-hole, 8.25x22.5 0P0MQ
- Spare wheel, in accordance with configuration for front axle tyres 0P0MH
- Centring sleeves for rim mounting 0PHZW

Axles

- 4x2 0P3B1
- Steering ratio, standard 0P1JX
- Steering oil tank with dipstick 0P1JW
- Front axle, 7,500 kg, not driven, cranked, steered, not liftable 0P5EQ
- Mudguard, front axle 0P1AT
- Splash guard mat on mudguard, front axle, longer at bottom 0P1XS
- Rear axle, 11,500 kg, HY axle without drive shaft, straight, not steered, not liftable 0P4ZL
- Twin tyre on rear axle 0P1HN



<input type="checkbox"/>	Transfer mudguard, rear axle	0P1AQ
<input type="checkbox"/>	Axle ratio, $i = 4.63$	0P0D9
<input type="checkbox"/>	Differential locks on driven rear axles	0P0DI
<input type="checkbox"/>	Without differential locks, front axles	0P0DL

Axle control system and suspension

<input type="checkbox"/>	Suspension type for front axles and driven rear axles, leaf/leaf (BB)	0P2YB
<input type="checkbox"/>	Leaf-spring suspension on front axle, parabolic, 1-leaf, steel	0P1JC
<input type="checkbox"/>	Leaf-spring suspension on rear axle, parabolic, 4-leaf, steel	0PGBF
<input type="checkbox"/>	Spring load-bearing capacity front axle 7,100 kg	0P5CY
<input type="checkbox"/>	Spring load-bearing capacity of rear axle, 11,500 kg	0P5BT
<input type="checkbox"/>	Shock absorbers on front axle	0P1M4
<input type="checkbox"/>	Shock absorbers on rear axle	0P1LQ
<input type="checkbox"/>	Stabiliser, front axle	0P1LD
<input type="checkbox"/>	Stabiliser, rear axle	0P1LA
<input type="checkbox"/>	Axle location system not as wishbone	0P6ZY
<input type="checkbox"/>	Without air suspension control, trailer/semitrailer	0PHN2

Cab

Cab and cab exterior

<input type="checkbox"/>	Compact CC cab	0P2DK
<input type="checkbox"/>	Cab mount, Basic	0P1V8
<input type="checkbox"/>	Cab tilt mechanism, manual	0P1V6
<input type="checkbox"/>	No tilting roof/sliding roof	0P1VY
<input type="checkbox"/>	Bumper, steel, 3 pieces	0P1SG
<input type="checkbox"/>	Front step, integrated, with grab option	0P1VE
<input type="checkbox"/>	Windscreen, composite safety glass, tinted	0P1X0
<input type="checkbox"/>	Sunblind, in front of windscreen	0P1WK
<input type="checkbox"/>	Wiper system for windscreen	0P1WG
<input type="checkbox"/>	Wiper activation, manual	0P1UL
<input type="checkbox"/>	Step unit, rigid	0P1UZ
<input type="checkbox"/>	Central locking, no remote control	0P1WS
<input type="checkbox"/>	Vehicle key, 4 units	0P3JU
<input type="checkbox"/>	No door extension	0P1WW
<input type="checkbox"/>	Door labelling, according to trade tonnage of vehicle	0P2DQ
<input type="checkbox"/>	Door windows, tinted	0P1WO
<input type="checkbox"/>	Door window, safety glass	0P1WM
<input type="checkbox"/>	Cab rear wall, no window	0P1VD

Lights and acoustic signals on cab exterior (headlights, horn, ...)

<input type="checkbox"/>	H7 package, front headlights, fog lights	0PKWS
<input type="checkbox"/>	Front headlights, H7	0P1ZN
<input type="checkbox"/>	Stone protection guard for front headlights, wide and fine mesh	0PICD
<input type="checkbox"/>	Daytime driving lights, H7	0P2BN
<input type="checkbox"/>	Fog lights, H7	0P2AH
<input type="checkbox"/>	Turn signal lights, sides, bulb	0P1Z6
<input type="checkbox"/>	Headlight beam regulator, manual	0P2AC



<input type="checkbox"/>	Driving-light control, manual	0P1ZF
<input type="checkbox"/>	Contour lights, bulb, 2 units	0P2BT
<input type="checkbox"/>	Horn, two-tone, electrical	0P1W1
<input type="checkbox"/>	Preparation for revolving beacons (wiring)	0P2BF
<input type="checkbox"/>	2 revolving beacons on cab roof, 1 right and 1 left	0P2B3
<input type="checkbox"/>	Preparation for loading area lighting	0P2A5
<input type="checkbox"/>	Without revolving beacons at the rear of the vehicle	0PJRO

Mirrors and mirror replacements

<input type="checkbox"/>	Mirror package, exterior rear-view mirror, manually adjustable, front mirror, kerb mirror, right	0PKWY
<input type="checkbox"/>	Exterior rear-view mirror, mechanically adjustable	0P2CC
<input type="checkbox"/>	Kerb mirror, right, mechanically adjustable	0P2CH
<input type="checkbox"/>	Front mirror, mechanical adjustment	0P2CJ
<input type="checkbox"/>	Mirror housing, not painted	0P2CP
<input type="checkbox"/>	Vehicle components, suitable for body width larger than 2,400 mm to 2,600 mm	0P2CT

Seats

<input type="checkbox"/>	Seat covers, fabric, standard	0P2PQ
<input type="checkbox"/>	Plus driver's seat package, air-sprung	0PKXF
<input type="checkbox"/>	Comfort driver's seat, air-sprung	0P2P2
<input type="checkbox"/>	Basic co-driver's seat package, unsprung, with storage box	0PKTZ
<input type="checkbox"/>	Co-driver's seat, not sprung, with storage box	0P2OO
<input type="checkbox"/>	Storage space, in seat bracket of co-driver's seat	0P2Q6
<input type="checkbox"/>	Middle seat, folding backrest, 2-point seatbelt	0P2PG

Driver's workplace

<input type="checkbox"/>	Multi-function steering wheel, adjustable height and angle	0P2GD
<input type="checkbox"/>	Steering wheel, with parking position	0P2GE
<input type="checkbox"/>	Steering lock	0P3JZ
<input type="checkbox"/>	Professional instrumentation, 12.3"	0P3L2
<input type="checkbox"/>	Tachograph Simulation Unit (TSU), instead of tachograph	0P2KY
<input type="checkbox"/>	Tachograph, calibrated	0P2KG
<input type="checkbox"/>	Plug-in ashtray, instrument panel in middle section, 1 unit	0P2FO
<input type="checkbox"/>	Cigarette lighter	0P2IH
<input type="checkbox"/>	Single DIN slots, 4 units, roof space, front	0P2FJ
<input type="checkbox"/>	Without storage tray next to seat	0PJRS

Cab air-conditioning system

<input type="checkbox"/>	Air-conditioning system, manual	0P2NU
<input type="checkbox"/>	Pre-separator (cyclone filter) for interior air intake	0P2O7

Bunk area

<input type="checkbox"/>	Without bunk area	0PKFY
--------------------------	-------------------	-------

Cab interior

<input type="checkbox"/>	Dark Moon Grey with silver colour scheme for cab interior	0PKFZ
<input type="checkbox"/>	Interior styling analogous to colour scheme	0PGBT
<input type="checkbox"/>	Basic driver's workplace package	0PKPN
<input type="checkbox"/>	Windscreen roller blind, internal	0P2FE



<input type="checkbox"/>	Interior light, reading light (driver's side)	0PKMY
<input type="checkbox"/>	Interior light, central	0PHA6
<input type="checkbox"/>	Reading light, 1 unit, driver's side	0P2IQ
<input type="checkbox"/>	Entry lighting	0P2IO
<input type="checkbox"/>	Entry handles, standard	0PHPK
<input type="checkbox"/>	Door interior cladding, washable	0P2IA
<input type="checkbox"/>	Without additional storage and stowage space	0PKWA
<input type="checkbox"/>	Grab handle, above door, internal, 2 units, 1 right and 1 left	0P2G2
<input type="checkbox"/>	Grab handle, cab roof, internal	0P2G0

Accessories and tools

<input type="checkbox"/>	Vehicle tool kit without accessories	0PKXB
<input type="checkbox"/>	Vehicle toolkit	0P2TX
<input type="checkbox"/>	No warning triangle	0P3FH
<input type="checkbox"/>	Jack, 10,000 kg	0P3F7
<input type="checkbox"/>	Operator's manual in English, printed, additional	0P2JB

Intelligent Truck

Assistance systems

<input type="checkbox"/>	Anti-slip control (ASR)	0P1T2
<input type="checkbox"/>	Tempomat (cruise control, CC)	0P1TR
<input type="checkbox"/>	Road speed limiter, adjustable, limiter (engine speed regulation)	0P0C3
<input type="checkbox"/>	Without advanced emergency braking system	0P1U5
<input type="checkbox"/>	Without driving fitness detection system	0PHN5
<input type="checkbox"/>	Without Front Detection	0PHNA
<input type="checkbox"/>	Without traffic sign recognition	0PHNE
<input type="checkbox"/>	Without Reversing Motion System	0PHNV
<input type="checkbox"/>	Without distance warning system	0PKA0
<input type="checkbox"/>	Without MAN SafeStop Assist	0PLB5

Infotainment (radio,...)

<input type="checkbox"/>	MMT infotainment system, Starter Basic	0P2M1
<input type="checkbox"/>	MAN loudspeaker system	0P2MF
<input type="checkbox"/>	No navigation map	0P2N2
<input type="checkbox"/>	French additionally for display	0P2JT

Bodies/interfaces

Interfaces to semitrailer (e.g. fifth-wheel coupling, brake connection,...)

<input type="checkbox"/>	Without trailer brake connection behind cab	0P1O3
<input type="checkbox"/>	No fifth-wheel coupling	0P1RJ
<input type="checkbox"/>	Without sensing of the fifth-wheel coupling	0PHN7

Interfaces to trailer (e.g. trailer coupling, brake connections,...)

<input type="checkbox"/>	Towing coupling at final cross member, RINGFEDER type 6451	0P1MY
<input type="checkbox"/>	Towing coupling on final cross member	0P1SH



<input type="checkbox"/>	Without trailer brake connection at end of frame, centre	0P100
<input type="checkbox"/>	Without trailer socket at frame end	0P10W
<input type="checkbox"/>	Without trailer socket for anti-lock brake system (ABS)	0P109

Ex works bodies and interfaces to bodies (e.g. tipper indicator...)

<input type="checkbox"/>	Interface for data exchange with tipper (customer-specific control module) and intermediate engine speed (ZDR), front area of cab and behind cab	0PKNU
<input type="checkbox"/>	Interface for vehicle data (FMS)	0P2J3

PTOs

<input type="checkbox"/>	PTO, engine-dependent, non-shiftable	0P4N8
<input type="checkbox"/>	PTO, engine-dependent, flywheel, flange (6-hole, 100 mm), f=1.219, 600/720 Nm continuous/short	0P4W4
<input type="checkbox"/>	Flange connection on PTO, engine-dependent, 100 mm diameter (6-hole)	0P4OR
<input type="checkbox"/>	Engine-dependent power take-off, continuous operation	0P4XF
<input type="checkbox"/>	PTO, gearbox-dependent, Heavy Duty type, with flange, f=1.3, position approx. 3 o'clock	0PHOC
<input type="checkbox"/>	PTO, gearbox-dependent, continuous operation	0P4VJ
<input type="checkbox"/>	PTO, gearbox-dependent, powershift	0PHMM
<input type="checkbox"/>	Without fan wheel for PTO, gearbox-dependent	0P4VR
<input type="checkbox"/>	Function parameters for PTO; gearbox-dependent, driving operation	0P4WP
<input type="checkbox"/>	Sector-specific parameterisation, general	0P4X0

Towing, recovery and lashing

<input type="checkbox"/>	Central coupling jaw, integrated in bumper/front cross member, with lock pin	0P1MK
<input type="checkbox"/>	Shackles, 2 units, front of vehicle	0P1S3

Paintworks

Paintwork, cab, top

<input type="checkbox"/>	Top coating, cab	0P6YB
--------------------------	------------------	-------

Paintwork, cab, bottom

<input type="checkbox"/>	Textured coating, step units	0P6X9
<input type="checkbox"/>	Textured coating, mudguard, behind cab	0P6YG
<input type="checkbox"/>	Textured coating, bumper, steel	0P6YQ

Paintwork, chassis

<input type="checkbox"/>	Without additional top coating on chassis	0PJTK
<input type="checkbox"/>	Top coating, rims, steel, white-aluminium	0P6YL

Colour

<input type="checkbox"/>	Top coating, cab	FLAME RED RAL 3000	N
--------------------------	------------------	--------------------	---



Technical data: TGM 18.250 4x2 BB CH / L08DAA07

Vehicle type: Vehicle type, platform truck and chassis (LK)

Cab: Compact CC cab

Drive Type: 4x2

Lengths		mm
TD071	Total length	9995.0
TD063	Front vehicle overhang	1530.0
TD057	Wheelbase between front axles	0
TD058	Wheelbase between leading axle and rear axle	0
TD059	Wheelbase between rear axles	0
TD060	Wheelbase between rear axle and trailing axle	0
TD064	Rear frame overhang	2875.0
TD072	Distance from first front axle to body	441.0
TD067	Distance to kingpin from front axle, nominal position	-
TD074	Slew radius, front	-
TD075	Slew radius, rear	-
TD068	Coupling length	9677.0

Lengths		mm
TD071	Total length	9995.0
TD063	Front vehicle overhang	1530.0
TD057	Wheelbase between front axles	0
TD058	Wheelbase between leading axle and rear axle	0
TD059	Wheelbase between rear axles	0
TD060	Wheelbase between rear axle and trailing axle	0
TD064	Rear frame overhang	2875.0
TD072	Distance from first front axle to body	441.0
TD067	Distance to kingpin from front axle, nominal position	-
TD074	Slew radius, front	-
TD075	Slew radius, rear	-
TD068	Coupling length	9677.0

Widths		mm
TD008	Width included rearview mirror	2981.0
TD001	Width over cab	2240.0

Widths		mm
TD008	Width included rearview mirror	2981.0
TD001	Width over cab	2240.0

Frame		mm
TD009	Frame width at front	964.0
TD010	Frame width at the rear	864.0
TD078	Frame profile	270 x 70 x 7

Frame		mm
TD009	Frame width at front	964.0
TD010	Frame width at the rear	864.0
TD078	Frame profile	270 x 70 x 7

Heights		mm
TD033	Maximum external height, unladen	2949.0
TD082	Total transport height, unladen	2949.0
TD034	Maximum external height, laden	2873.0
TD035	Frame height at theoretical rear wheelbase, unladen	1077.0
TD036	Frame height at theoretical rear wheelbase, laden	944.0
TD045	Raising from driving position, front	0.0
TD046	Lowering from driving position, front	0.0
TD047	Raising from driving position, rear	0.0
TD048	Lowering from driving position, rear	0.0
TD051	Height of fifth-wheel coupling above ground, unladen	-
TD052	Height of fifth-wheel coupling above ground, laden	-

Heights		mm
TD033	Maximum external height, unladen	2949.0
TD082	Total transport height, unladen	2949.0
TD034	Maximum external height, laden	2873.0
TD035	Frame height at theoretical rear wheelbase, unladen	1077.0
TD036	Frame height at theoretical rear wheelbase, laden	944.0
TD045	Raising from driving position, front	0.0
TD046	Lowering from driving position, front	0.0
TD047	Raising from driving position, rear	0.0
TD048	Lowering from driving position, rear	0.0
TD051	Height of fifth-wheel coupling above ground, unladen	-
TD052	Height of fifth-wheel coupling above ground, laden	-

Circle dimensions		m
TD055	Track circle diameter	18.5
TD056	Wall-to-wall turning circle diameter	20.0

Circle dimensions		m
TD055	Track circle diameter	18.5
TD056	Wall-to-wall turning circle diameter	20.0

Weights/loads		kg
TD026	Chassis weight with cab	5841
TD027	Chassis weight, front	3866
TD028	Chassis weight, rear	1975
TD029	Payload	11159
TD018	Statutorily permissible gross vehicle weight	17000
TD025	Technically permissible gross vehicle weight	18600
TD031	Statutorily permissible gross train weight	0
TD032	Statutorily permissible trailer load	0

Weights/loads		kg
TD026	Chassis weight with cab	5841
TD027	Chassis weight, front	3866
TD028	Chassis weight, rear	1975

The technical data must be considered as an approximation. Some of the values are given in a simplified form. More detailed notes and descriptions can be found in the respective information in the overview. Contents and specifications have been compiled with the greatest possible care. Nevertheless, we do not assume responsibility for the data and values supplied being correct and up to date. Subject to errors and changes. MAN Truck & Bus AG is liable only in cases of intent, gross negligence or culpable breach of significant contractual obligations.



TD029	Payload	11159
TD018	Statorily permissible gross vehicle weight	17000
TD025	Technically permissible gross vehicle weight	18600
TD031	Statorily permissible gross train weight	0
TD032	Statorily permissible trailer load	0

The technical data must be considered as an approximation. Some of the values are given in a simplified form. More detailed notes and descriptions can be found in the respective information in the overview. Contents and specifications have been compiled with the greatest possible care. Nevertheless, we do not assume responsibility for the data and values supplied being correct and up to date. Subject to errors and changes. MAN Truck & Bus AG is liable only in cases of intent, gross negligence or culpable breach of significant contractual obligations.
