

Vehicle description for: TGS 33.440 6x6 BB CH



Illustration can deviate

Vehicle standards

Product family	The new MAN Truck Generation
Model & Variant	TGS 33.440 6x6 BB CH
Emission class	EURO5
Engine family	D20
Engine output	324 kW
Vehicle type	Vehicle type, platform truck and chassis (LK)
Body type	090 Crane body
Cab	Local transport cab NN
Main wheel distance	4500 mm
Overhang	2500 mm
Steering configuration	Left

Vertical Load

	National Registration	Technical Load	Technical Load Plus
Gross weight	33,000 kg	33,000 kg	33,000 kg
Front axle	8,000 kg	8,000 kg	8,000 kg
Rear axle	13,000 kg	13,000 kg	13,000 kg
Rear axle 2	13,000 kg	13,000 kg	13,000 kg

Horizontal Load

	National Registration	Technical Load	Technical Load Plus
Gross train weight	44,000 kg	45,000 kg	62,000 kg

The printed images in this offer are for explanatory purposes and may differ from the actual configuration.
For further product information on the tire selection "selectively", please contact our sales staff.

Vehicle characteristics

Basic characteristics

<input type="checkbox"/> Vehicle version for public service deployment	0P0H7
<input type="checkbox"/> Chassis	0P2U9
<input type="checkbox"/> Chassis class, heavy	0P2UC
<input type="checkbox"/> Destination Togo (TG)	0PGB2
<input type="checkbox"/> Merchant tonnage 33 t	0P8LK
<input type="checkbox"/> Basic layout, standard vehicle	0PLSI
<input type="checkbox"/> Application area, beside road hard (T2)	0PLSF
<input type="checkbox"/> Frame type, high	0P2TP
<input type="checkbox"/> Vehicle type, platform truck and chassis (LK)	0P2UQ
<input type="checkbox"/> Left-hand-drive	0P3AS
<input type="checkbox"/> Right-hand traffic	0P3F5
<input type="checkbox"/> Vehicle documents in English	0P2L7
<input type="checkbox"/> Labelling in English	0P8NM
<input type="checkbox"/> Cab position 720 mm (distance from frame lower edge to cab floor)	0PHBF

Registration

<input type="checkbox"/> VO (EU) (towing equipment) not required	0PJW7
<input type="checkbox"/> Vehicle approval, N3G class	0P3JS
<input type="checkbox"/> Maximum speed limiter, 85 km/h, electronic, engine speed regulation	0P2UI
<input type="checkbox"/> VO (E.U.) 1003/2010 (mounting and fixing of number plate) not required	0PFWT
<input type="checkbox"/> Maximum vehicle noise level not defined	0P2YN
<input type="checkbox"/> Height over cab, unloaded up to 4,000 mm	0PHA1
<input type="checkbox"/> Vehicle classification in accordance with regulation (EU) 2018/858	0PKAW

Documents

<input type="checkbox"/> Without registration documentation, national	0P3B0
<input type="checkbox"/> Special confirmation, heavy load / municipal operation	0P3CK

Application scope / transport tasks

<input type="checkbox"/> Construction	0P6WH
<input type="checkbox"/> 090 Crane body	0P2R2
<input type="checkbox"/> Temperature range, vehicle deployment, warm country	0PHIB
<input type="checkbox"/> Case hardness of final drive Distribution	0P4F0

Lines, editions and packages

<input type="checkbox"/> Without Efficient Drive	0PVBQ
<input type="checkbox"/> Special request paintwork	0PJTD
<input type="checkbox"/> Without Individual Lion package	0PJT1

Horizontal and vertical loads

<input type="checkbox"/> 33,000 kg permitted gross load, vertical, nat. appr.	0P5QP
<input type="checkbox"/> 33,000 kg permitted gross load, vertical, tech.	0P5UA
<input type="checkbox"/> 33,000 kg permitted gross load, vertical, tech. Plus	0P8HZ
<input type="checkbox"/> 8,000 kg permitted load on front axle, nat. appr.	0P5KT
<input type="checkbox"/> 8,000 kg permitted load on front axle, tech.	0P5LN

<input type="checkbox"/> 8,000 kg permitted load on front axle, tech. Plus	0P8D4
<input type="checkbox"/> 13,000 kg permitted load on rear axle NatZu	0P5HC
<input type="checkbox"/> 13,000 kg permitted load on rear axle, tech.	0P5IO
<input type="checkbox"/> 13,000 kg permitted load on rear axle, tech. Plus	0P8BY
<input type="checkbox"/> 13,000 kg permitted load on 2nd rear axle NatZu	0P5FM
<input type="checkbox"/> 13,000 kg permitted load on 2nd rear axle, tech.	0P5M9
<input type="checkbox"/> 13,000 kg permitted load on 2nd rear axle, tech. Plus	0P7TJ
<input type="checkbox"/> 44,000 kg permitted gross train weight, national registration	0PB1Y
<input type="checkbox"/> 45,000 kg permissible gross train weight TechH.	0PBWF
<input type="checkbox"/> 62,000 kg permitted gross train weight, Tech. Plus	0PBQG
<input type="checkbox"/> 0kN D value	0P8XD

Notification texts

<input type="checkbox"/> Note: Restricted steerability with engaged differential lock on front axle	0PFZN
<input type="checkbox"/> Note: With increased permissible gross weight, increase in wear of driveline and reduced service life	0PFZP
<input type="checkbox"/> Note: Max. 55,000 kg tech. permitted gross weight with engaged off-road reduction ratio in transfer case	0PFZT
<input type="checkbox"/> Note: Difference of more than 2% in FA/RA rolling circumference may lead to perceptible tension in the driveline.	0PHCX
<input type="checkbox"/> Without note (propshaft wear)	0PJRV

Chassis

Vehicle frame (wheelbase, overhang, ...)

<input type="checkbox"/> Main wheelbase, 4,500 mm	0P2ZW
<input type="checkbox"/> Wheelbase between rear axles, 1,400 mm	0P3BX
<input type="checkbox"/> Frame overhang, rear, 2,500 mm	0P3E1
<input type="checkbox"/> Main frame side member thickness, 9.5 mm	0P0Y7
<input type="checkbox"/> Vehicle rear, straight end of frame	0P0XT

Exhaust system, air intake

<input type="checkbox"/> Exhaust silencer, side, left	0P1BG
<input type="checkbox"/> Exhaust tailpipe, towards rear	0P1BQ
<input type="checkbox"/> Air intake, behind cab, raised	0P0AY
<input type="checkbox"/> Pre-separator for engine air intake	0P0BA

Battery cases, batteries, alternator

<input type="checkbox"/> 2 batteries, 12 V, 180 Ah, long-life (EFB), maintenance free	0PGB1
<input type="checkbox"/> Three-phase alternator 28 V, 120 A, 3,360 W, Longlife Eco	0P1BW
<input type="checkbox"/> Medium battery box, 2 batteries	0P0WU
<input type="checkbox"/> Battery box, left	0P0WO
<input type="checkbox"/> Main battery switch, mechanical	0P0WF
<input type="checkbox"/> Fuses	0P1V1

Tanks and fuel line

<input type="checkbox"/> Fuel tank capacity 400 l, right	0P4ED
<input type="checkbox"/> Fuel tank, right, steel	0P4GN
<input type="checkbox"/> Tank cross-section, right, medium	0P4HE

<input type="checkbox"/> AdBlue tank capacity 35 l, left	0P8N3
<input type="checkbox"/> AdBlue tank, left, plastic	0P4H1
<input type="checkbox"/> Fuel tank cap, lockable for master key system	0P4H5
<input type="checkbox"/> Cap for AdBlue tank	0P4GD
<input type="checkbox"/> Fuel pre-filter position on the battery box	0PIW9

Frame attachments

<input type="checkbox"/> Without underride protection, front	0P1FM
<input type="checkbox"/> Without working platform	0P0VH
<input type="checkbox"/> Without underride protection, side	0P1FG
<input type="checkbox"/> Spare wheel, provisionally mounted	0P1GR
<input type="checkbox"/> Final cross member, with hole pattern 160 x 100 mm	0P1SB
<input type="checkbox"/> Underride protection, rear, round	0P1FD
<input type="checkbox"/> Wheel chock, 1 unit, with retaining device	0P1FO
<input type="checkbox"/> Without body attachment brackets/thrust plates	0P0X6

Pneumatic brakes, compressed-air generation, brake system

<input type="checkbox"/> Air compressor, 1-cylinder, 360 ccm	0P0AF
<input type="checkbox"/> Compressed-air treatment, electronically controlled	0P0AA
<input type="checkbox"/> Steel compressed-air tank	0P0XH
<input type="checkbox"/> Electronic brake system (EBS)	0P0BL
<input type="checkbox"/> Anti-lock braking system (ABS)	0P0BE
<input type="checkbox"/> Full brake assistant	0P0CM
<input type="checkbox"/> Without preparation for EBS Full control unit	0PHPM
<input type="checkbox"/> MAN EVB high-performance engine brake	0P0BV
<input type="checkbox"/> Drum brakes on front axle	0P1IA
<input type="checkbox"/> Drum brakes on rear axle	0P1I5
<input type="checkbox"/> Drum brakes on 2nd rear axle	0P1IF
<input type="checkbox"/> Parking brake control, next to driver's seat	0P3KH
<input type="checkbox"/> Brake cylinder with parking brake for increased gross weight	0P8QF
<input type="checkbox"/> Parking brake with spring-type actuator on rear axles (incl. leading axle/ trailing axle)	0PGBL
<input type="checkbox"/> MAN EasyStart immobiliser	0P1TF

Lights and acoustic signals on the chassis (rear lights, ...)

<input type="checkbox"/> Rear lights	0P2AQ
<input type="checkbox"/> Acoust. Reversing warning system when reverse gear selected	0P3CD
<input type="checkbox"/> Light function test	0P2AD
<input type="checkbox"/> No side marker lights	0P2BK

Driveline/running gear

Engine, radiator

<input type="checkbox"/> Diesel engine MAN D2066 LF44, 324 kW (440 hp) output, 2,100 Nm torque, Euro 5	0P6BG
<input type="checkbox"/> Fuel filter, for fuels up to Cleanliness Class 25	0PHII
<input type="checkbox"/> Fuel pre-filter, with oil separator/water trap, with water sensor	0P4XO
<input type="checkbox"/> Without torque reduction	0P0G5
<input type="checkbox"/> Engine dry-air filter, with safety insert	0P0B8
<input type="checkbox"/> Ventilation, crankcase, open	0P8PN

<input type="checkbox"/> Engine skirt, in wheel arch, to prevent engine soiling	0P2E9
<input type="checkbox"/> Reduction of dust swirl through radiator fan	0P1YE
<input type="checkbox"/> Engine cooler, extended	0P4XY
<input type="checkbox"/> Radiator protection, lower	0P1XE
<input type="checkbox"/> Front radiator protection, grille	0P1VP
<input type="checkbox"/> Engine oil dipstick	0P0B5
<input type="checkbox"/> Warning message for engine coolant level, with advance warning	0P0KA
<input type="checkbox"/> Antifreeze, down to -32 °C	0P0AK

Gearbox, clutch

<input type="checkbox"/> MAN TipMatic 12.28 OD	0P5VW
<input type="checkbox"/> Gearbox for increased percentage of overrun during driving operation	0PGCL
<input type="checkbox"/> MAN TipMatic actuation, with drop arm, manual (DNR option, switching strategy option)	0P3KI
<input type="checkbox"/> MAN Idle Speed Driving gearbox function	0P0ER
<input type="checkbox"/> Rock-free gearbox function	0P0EV
<input type="checkbox"/> MAN TipMatic Efficiency driving program, up to 70,000 kg	0P0FA
<input type="checkbox"/> MAN TipMatic Offroad gearbox shift strategy, up to 70,000 kg	0P0F4
<input type="checkbox"/> MAN TipMatic Manoeuvre driving program, manoeuvring feature	0P0FI
<input type="checkbox"/> Transfer case MAN G252 with on-road and off-road gear	0P4XL
<input type="checkbox"/> Transfer case lock management, electronic (VSM)	0P0FU
<input type="checkbox"/> Single-disc clutch, 430 mm, dry, reinforced (LongLife)	0P0DW
<input type="checkbox"/> Main propshaft, 30,000 Nm functional limit torque	0PKZJ
<input type="checkbox"/> Propshafts with standard grease, cannot be lubricated	0PKZL
<input type="checkbox"/> Driveline propshaft, reinforced	0P0E2
<input type="checkbox"/> Propshaft, 2nd rear axle, reinforced	0PGCF

Wheels, tyres

<input type="checkbox"/> Required tyre speed index G	0PFWA
<input type="checkbox"/> Tyres, front axle, Goodyear 325/95R24 OMNITRAC S HD Steer-Road+Offroad TL	0PJH5
<input type="checkbox"/> Rim type, front axle, steel, single-part	0P0P0
<input type="checkbox"/> Rim size, front axle, 10-hole, 8.5x24	0P0NH
<input type="checkbox"/> Wheel nut cover ring, front axle	0P0PR
<input type="checkbox"/> Tyres, rear axle, Goodyear 325/95R24 OMNITRAC D HD Drive-Road+Offroad TL	0PJER
<input type="checkbox"/> Rim type, rear axle, steel, single-part	0P0OO
<input type="checkbox"/> Rim size, rear axle, 10-hole, 8.5x24	0P0MT
<input type="checkbox"/> Tyres, 2nd rear axle, Goodyear 325/95R24 OMNITRAC D HD Drive-Road+Offroad TL	0PJFM
<input type="checkbox"/> Tyre tread OMNITRAC D HD, 2nd rear axle	0PIP1
<input type="checkbox"/> Rim type, 2nd rear axle, steel, single-part	0P0PA
<input type="checkbox"/> Rim size, 2nd rear axle, 10-hole, 8.5x24	0P0O6
<input type="checkbox"/> Spare wheel, in accordance with configuration for front axle tyres	0P0MH

Axles

<input type="checkbox"/> 6x6	0P3BD
<input type="checkbox"/> Steering ratio, indirect	0P1JY
<input type="checkbox"/> Steering oil tank with electrical measuring sensor	0P1JV
<input type="checkbox"/> Front axle, 9,000 kg, planetary axle without drive shaft, straight, steered, not liftable	0P5ES
<input type="checkbox"/> Front axle as planetary axle, driven, engageable	0P1GY
<input type="checkbox"/> Mudguard, front axle	0P1AT

<input type="checkbox"/> Rear axle HPD-1382, 13,000 kg, planetary axle with drive-through, straight, not steered, not liftable	0PIY1
<input type="checkbox"/> Twin tyre on rear axle	0P1HN
<input type="checkbox"/> Mudguard, rear axle, plastic half shells in front of rear axle	0P1AO
<input type="checkbox"/> 2nd rear axle HP-1352, 13,000 kg, planetary axle without drive-through, straight, not steered, not liftable	0PIVD
<input type="checkbox"/> Twin tyre on 2nd rear axle	0P1HW
<input type="checkbox"/> Mudguard, plastic half shells, behind 2nd rear axle, with transfer tarpaulin over both rear axles	0P1AY
<input type="checkbox"/> Splash guard mat on mudguard, 2nd rear axle	0P1XY
<input type="checkbox"/> Axle ratio, i = 4.33	0P0D6
<input type="checkbox"/> Differential locks on driven rear axles	0P0DI
<input type="checkbox"/> Differential locks on driven front axles	0P0DK
<input type="checkbox"/> Warning buzzer when front axle locks are engaged	0P0DQ

Axle control system and suspension

<input type="checkbox"/> Suspension type for front axles and driven rear axles, leaf/leaf (BB)	0P2YB
<input type="checkbox"/> Leaf-spring suspension on front axle, parabolic, 3-leaf, steel	0P1JE
<input type="checkbox"/> Leaf-spring suspension on rear axle, parabolic, 5-leaf, steel	0P1J2
<input type="checkbox"/> Leaf-spring suspension on 2nd rear axle, parabolic, 5-leaf, steel	0P1JL
<input type="checkbox"/> Spring load-bearing capacity front axle 9,500 kg	0P5C4
<input type="checkbox"/> Spring load-bearing capacity of rear axle, 16,000 kg	0P5BW
<input type="checkbox"/> Spring load-bearing capacity of 2nd rear axle, 16,000 kg	0P5C8
<input type="checkbox"/> Shock absorbers on front axle	0P1M4
<input type="checkbox"/> Shock absorbers on rear axle	0P1LQ
<input type="checkbox"/> Shock absorbers on 2nd rear axle	0P1M9
<input type="checkbox"/> Stabiliser, front axle	0P1LD
<input type="checkbox"/> Stabiliser, rear axle	0P1LA
<input type="checkbox"/> Stabiliser, 2nd rear axle	0P1LH
<input type="checkbox"/> Wishbone	0P6ZR
<input type="checkbox"/> Without air suspension control, trailer/semitrailer	0PHN2

CabCab and cab exterior

<input type="checkbox"/> Local transport cab NN	0P2DL
<input type="checkbox"/> Cab mount, Basic	0P1V8
<input type="checkbox"/> Cab tilt mechanism, manual	0P1V6
<input type="checkbox"/> No tilting roof/sliding roof	0P1VY
<input type="checkbox"/> Bumper, steel, 3 pieces	0P1SG
<input type="checkbox"/> Front step, integrated, with grab option	0P1VE
<input type="checkbox"/> Windscreen, composite safety glass, tinted	0P1X0
<input type="checkbox"/> Sunblind, in front of windscreen	0P1WK
<input type="checkbox"/> Wiper system for windscreen	0P1WG
<input type="checkbox"/> Wiper activation, manual	0P1UL
<input type="checkbox"/> Step unit, hinged	0P1V0
<input type="checkbox"/> Central locking, no remote control	0P1WS
<input type="checkbox"/> Vehicle key, 2 units	0P3JT
<input type="checkbox"/> No door extension	0P1WV

<input type="checkbox"/>	Door labelling, according to maximum technically permitted overall vehicle weight	0P2DO
<input type="checkbox"/>	Door windows, tinted	0P1WO
<input type="checkbox"/>	Door window, safety glass	0P1WM
<input type="checkbox"/>	Cab rear wall, no window	0P1VD

Lights and acoustic signals on cab exterior (headlights, horn, ...)

<input type="checkbox"/>	H7 package Basic, front headlights	0PKWT
<input type="checkbox"/>	Front headlights, H7	0P1ZN
<input type="checkbox"/>	Stone protection guard for front headlights, wide and fine mesh	0PICD
<input type="checkbox"/>	Daytime driving lights, H7	0P2BN
<input type="checkbox"/>	Turn signal lights, sides, bulb	0P1Z6
<input type="checkbox"/>	Headlight beam regulator, manual	0P2AC
<input type="checkbox"/>	Driving-light control, manual	0P1ZF
<input type="checkbox"/>	Contour lights, LED, 2 units	0P2BS
<input type="checkbox"/>	Horn, two-tone, electrical	0P1W1
<input type="checkbox"/>	Revolving beacons, LED, yellow (individual LEDs light up in cascades, revolving)	0P2BD
<input type="checkbox"/>	2 revolving beacons on cab roof, 1 right and 1 left	0P2B3
<input type="checkbox"/>	Spotlights, 2 units, cab roof, 1 right and 1 left	0P1YM
<input type="checkbox"/>	Spotlight, LED, white	0PJQA
<input type="checkbox"/>	Switch for spotlight/manoeuvring light	0P5U5
<input type="checkbox"/>	Without revolving beacons at the rear of the vehicle	0PJRO

Mirrors and mirror replacements

<input type="checkbox"/>	Mirror package, exterior rear-view mirror, manually adjustable, front mirror, kerb mirror, right	0PKWY
<input type="checkbox"/>	Exterior rear-view mirror, mechanically adjustable	0P2CC
<input type="checkbox"/>	Kerb mirror, right, mechanically adjustable	0P2CH
<input type="checkbox"/>	Front mirror, mechanical adjustment	0P2CJ
<input type="checkbox"/>	Mirror housing, not painted	0P2CP
<input type="checkbox"/>	Vehicle components, suitable for body width larger than 2,400 mm to 2,600 mm	0P2CT

Seats

<input type="checkbox"/>	Seat covers, fabric, standard	0P2PQ
<input type="checkbox"/>	Premium driver's seat package, air-sprung	0PKXJ
<input type="checkbox"/>	Comfort driver's seat, air-sprung, with lumbar support and shoulder adjustment	0P2P5
<input type="checkbox"/>	Adjustment of seat belt height, driver's seat	0P4XQ
<input type="checkbox"/>	Basic co-driver's seat package, unsprung, with storage box	0PKTZ
<input type="checkbox"/>	Co-driver's seat, not sprung, with storage box	0P2OO
<input type="checkbox"/>	Storage space, in seat bracket of co-driver's seat	0P2Q6

Driver's workplace

<input type="checkbox"/>	Multi-function steering wheel, adjustable height and angle	0P2GD
<input type="checkbox"/>	Steering wheel, with parking position	0P2GE
<input type="checkbox"/>	Steering lock	0P3JZ
<input type="checkbox"/>	Professional instrumentation, 12.3"	0P3L2
<input type="checkbox"/>	Tachograph Simulation Unit (TSU), instead of tachograph	0P2KY
<input type="checkbox"/>	Tachograph, calibrated	0P2KG
<input type="checkbox"/>	Stowage compartment, open with two USB sockets, 5 V, charging only, to the right of climate control panel	0PGT7
<input type="checkbox"/>	2 pull-out cup holders in instrument panel	0P2FA

<input type="checkbox"/> Plug-in ashtray, instrument panel in middle section, 1 unit	0P2FO
<input type="checkbox"/> Cigarette lighter	0P2IH
<input type="checkbox"/> Single DIN slots, 4 units, roof space, front	0P2FJ
<input type="checkbox"/> Without storage tray next to seat	0PJRS

Cab air-conditioning system

<input type="checkbox"/> Air-conditioning system, manual	0P2NU
--	-------

Bunk area

<input type="checkbox"/> Without bunk area	0PKFY
--	-------

Cab interior

<input type="checkbox"/> Dark Moon Grey with silver colour scheme for cab interior	0PKFZ
<input type="checkbox"/> Interior styling analogous to colour scheme	0PGBT
<input type="checkbox"/> Driver's workplace package with roller blind, driver's side	0PKUB
<input type="checkbox"/> Windscreen roller blind, internal	0P2FE
<input type="checkbox"/> Roller blind for door windows, internal, mechanical, driver's side	0P2FH
<input type="checkbox"/> Interior light, reading light (both sides)	0PKMZ
<input type="checkbox"/> Interior light, central	0PHA6
<input type="checkbox"/> Reading light, 2 units, 1 on driver's side and 1 on co-driver's side	0P2IR
<input type="checkbox"/> Entry lighting	0P2IO
<input type="checkbox"/> Entry handles, standard	0PHPK
<input type="checkbox"/> Door interior cladding, washable	0P2IA
<input type="checkbox"/> Storage and stowage compartment package Basic, with storage box, rear area	0PKWH
<input type="checkbox"/> 2 storage compartments, cab rear wall, behind driver's and co-driver's side and net on cab rear wall	0PGB8
<input type="checkbox"/> Storage, instrument panel in middle section, open	0P2HK
<input type="checkbox"/> Storage box, centre area, to rear	0P2H9
<input type="checkbox"/> Grab handle, above door, internal, 2 units, 1 right and 1 left	0P2G2

Accessories and tools

<input type="checkbox"/> Vehicle tool kit without accessories	0PKXB
<input type="checkbox"/> Vehicle toolkit	0P2TX
<input type="checkbox"/> No warning triangle	0P3FH
<input type="checkbox"/> Jack, 12,000 kg	0P3F8

Intelligent TruckAssistance systems

<input type="checkbox"/> Without rear area monitoring	0PMA9
<input type="checkbox"/> Anti-slip control (ASR)	0P1T2
<input type="checkbox"/> Tempomat (cruise control, CC)	0P1TR
<input type="checkbox"/> Road speed limiter, adjustable, limiter (engine speed regulation)	0P0C3
<input type="checkbox"/> Without advanced emergency braking system	0P1U5
<input type="checkbox"/> Without driving fitness detection system	0PHN5
<input type="checkbox"/> Without Front Detection	0PHNA
<input type="checkbox"/> Without traffic sign recognition	0PHNE
<input type="checkbox"/> Without Reversing Motion System	0PHNV
<input type="checkbox"/> Without distance warning system	0PKA0

Without MAN SafeStop Assist 0PLB5

Infotainment (radio,...)

<input type="checkbox"/> MMT infotainment system, Starter Basic	0P2M1
<input type="checkbox"/> MAN loudspeaker system	0P2MF
<input type="checkbox"/> No navigation map	0P2N2
<input type="checkbox"/> French additionally for display	0P2JT

Bodies/interfaces

Interfaces to semitrailer (e.g. fifth-wheel coupling, brake connection,...)

<input type="checkbox"/> Without trailer brake connection behind cab	0P1O3
<input type="checkbox"/> No fifth-wheel coupling	0P1RJ
<input type="checkbox"/> Without sensing of the fifth-wheel coupling	0PHN7

Interfaces to trailer (e.g. trailer coupling, brake connections,..)

<input type="checkbox"/> Towing coupling at final cross member, ROCKINGER SK5	0P1MZ
<input type="checkbox"/> Towing coupling on final cross member	0P1SH
<input type="checkbox"/> 2-line trailer brake connection, end of frame, centre, standard coupling	0P1NZ
<input type="checkbox"/> Trailer socket, frame end, 24 V, 15-pin	0P1OM
<input type="checkbox"/> Trailer socket for anti-lock brake system (ABS), end of frame	0P1O4

Ex works bodies and interfaces to bodies (e.g. tipper indicator...)

<input type="checkbox"/> Interface for digital data exchange (Application Fit)	0PIXU
<input type="checkbox"/> Interface for extended signal output (EIO)	0PJBE

PTOs

<input type="checkbox"/> Without flange coupling for PTO, gearbox-dependent, elastic	0PMCB
<input type="checkbox"/> Without flange coupling for auxiliary output, dependent on PTO, elastic	0PMCD
<input type="checkbox"/> Without fan wheel for PTO, gearbox-dependent	0P4VR
<input type="checkbox"/> Preparation, electr., for subsequent installation of a shiftable PTO, gearbox-dependent	0P4OI
<input type="checkbox"/> Sector-specific parameterisation, general	0P4X0

Towing, recovery and lashing

<input type="checkbox"/> Central coupling jaw, integrated in bumper/front cross member, with lock pin	0P1MK
<input type="checkbox"/> Shackles, 2 units, front of vehicle	0P1S3

Paintworks

Paintwork, cab, top

<input type="checkbox"/> Top coating, cab	0P6YB
---	-------

Paintwork, cab, bottom

<input type="checkbox"/> Textured coating, step units	0P6X9
<input type="checkbox"/> Textured coating, mudguard, behind cab	0P6YG
<input type="checkbox"/> Textured coating, bumper, steel	0P6YQ

Paintwork, chassis



- Without additional top coating on chassis
- Top coating, rims, steel, white-aluminium

0PJTK

0P6YL

Colour

- Top coating, cab

PURE WHITE RAL 9010

N

Technical data: TGS 33.440 6x6 BB CH / L56EAA04

Vehicle type: Vehicle type, platform truck and chassis (LK)

Cab: Local transport cab NN

Drive Type: 6x6

Lengths		mm
TD071	Total length	10370.0
TD063	Front vehicle overhang	1605.0
TD057	Wheelbase between front axles	0
TD058	Wheelbase between leading axle and rear axle	0
TD059	Wheelbase between rear axles	1400
TD060	Wheelbase between rear axle and trailing axle	0
TD064	Rear frame overhang	2500.0
TD072	Distance from first front axle to body	465.0
TD067	Distance to kingpin from front axle, nominal position	-
TD074	Slew radius, front	-
TD075	Slew radius, rear	-
TD068	Coupling length	9799.0
Lengths		mm
TD071	Total length	10370.0
TD063	Front vehicle overhang	1605.0
TD057	Wheelbase between front axles	0
TD058	Wheelbase between leading axle and rear axle	0
TD059	Wheelbase between rear axles	1400
TD060	Wheelbase between rear axle and trailing axle	0
TD064	Rear frame overhang	2500.0
TD072	Distance from first front axle to body	465.0
TD067	Distance to kingpin from front axle, nominal position	-
TD074	Slew radius, front	-
TD075	Slew radius, rear	-
TD068	Coupling length	9799.0
Widths		mm
TD008	Width included rearview mirror	2981.0
TD001	Width over cab	2240.0
Widths		mm
TD008	Width included rearview mirror	2981.0
TD001	Width over cab	2240.0
Frame		mm
TD009	Frame width at front	945.0
TD010	Frame width at the rear	765.0
TD078	Frame profile	270 x 85 x 9,5
Frame		mm
TD009	Frame width at front	945.0
TD010	Frame width at the rear	765.0
TD078	Frame profile	270 x 85 x 9,5

Heights

	mm
TD033	Maximum external height, unladen
TD082	Total transport height, unladen
TD034	Maximum external height, laden
TD035	Frame height at theoretical rear wheelbase, unladen
TD036	Frame height at theoretical rear wheelbase, laden
TD045	Raising from driving position, front
TD046	Lowering from driving position, front
TD047	Raising from driving position, rear
TD048	Lowering from driving position, rear
TD051	Height of fifth-wheel coupling above ground, unladen
TD052	Height of fifth-wheel coupling above ground, laden

Heights

	mm
TD033	Maximum external height, unladen
TD082	Total transport height, unladen
TD034	Maximum external height, laden
TD035	Frame height at theoretical rear wheelbase, unladen
TD036	Frame height at theoretical rear wheelbase, laden
TD045	Raising from driving position, front
TD046	Lowering from driving position, front
TD047	Raising from driving position, rear
TD048	Lowering from driving position, rear
TD051	Height of fifth-wheel coupling above ground, unladen
TD052	Height of fifth-wheel coupling above ground, laden

Circle dimensions

	m
TD055	Track circle diameter
TD056	Wall-to-wall turning circle diameter

Circle dimensions

	m
TD055	Track circle diameter
TD056	Wall-to-wall turning circle diameter

Weights/loads

	kg
TD026	Chassis weight with cab
TD027	Chassis weight, front
TD028	Chassis weight, rear
TD029	Payload
TD018	Statutorily permissible gross vehicle weight
TD025	Technically permissible gross vehicle weight
TD031	Statutorily permissible gross train weight
TD032	Statutorily permissible trailer load

Weights/loads

	kg
TD026	Chassis weight with cab
TD027	Chassis weight, front
TD028	Chassis weight, rear

The technical data must be considered as an approximation. Some of the values are given in a simplified form. More detailed notes and descriptions can be found in the respective information in the overview. Contents and specifications have been compiled with the greatest possible care. Nevertheless, we do not assume responsibility for the data and values supplied being correct and up to date. Subject to errors and changes. MAN Truck & Bus AG is liable only in cases of intent, gross negligence or culpable breach of significant contractual obligations.

TD029	Payload	22173
TD018	Statutorily permissible gross vehicle weight	33000
TD025	Technically permissible gross vehicle weight	33000
TD031	Statutorily permissible gross train weight	44000
TD032	Statutorily permissible trailer load	0

The technical data must be considered as an approximation. Some of the values are given in a simplified form. More detailed notes and descriptions can be found in the respective information in the overview. Contents and specifications have been compiled with the greatest possible care. Nevertheless, we do not assume responsibility for the data and values supplied being correct and up to date. Subject to errors and changes. MAN Truck & Bus AG is liable only in cases of intent, gross negligence or culpable breach of significant contractual obligations.