



Vehicle description for: TGS 33.400 6x6 BB CH



Illustration can deviate

Vehicle standards

Product family	The new MAN Truck Generation
Model & Variant	TGS 33.400 6x6 BB CH
Emission class	EURO2
Engine family	D20
Engine output	294 kW
Vehicle type	Vehicle type, platform truck and chassis (LK)
Body type	999 Miscellaneous vehicle
Cab	Local transport cab NN
Main wheel distance	4500 mm
Overhang	2500 mm
Steering configuration	Left

Vertical Load

	National Registration	Technical Load	Technical Load Plus
Gross weight	33,000 kg	33,000 kg	33,000 kg
Front axle	8,000 kg	8,000 kg	8,000 kg
Rear axle	13,000 kg	13,000 kg	13,000 kg
Rear axle 2	13,000 kg	13,000 kg	13,000 kg

Horizontal Load

	National Registration	Technical Load	Technical Load Plus
Gross train weight	0 kg	0 kg	0 kg



The printed images in this offer are for explanatory purposes and may differ from the actual configuration.
For further product information on the tire selection "selectively", please contact our sales staff.

Vehicle characteristics

Basic characteristics

☐	Vehicle version for public service deployment	0P0H7
☐	Chassis	0P2U9
☐	Chassis class, heavy	0P2UC
☐	Destination: Ivory Coast (CI)	0P3GD
☐	Merchant tonnage 33 t	0P8LK
☐	Basic layout of vehicle, all-round	0PGCU
☐	Frame type, high	0P2TP
☐	Vehicle type, platform truck and chassis (LK)	0P2UQ
☐	Left-hand-drive	0P3AS
☐	Right-hand traffic	0P3F5
☐	Vehicle documents in English	0P2L7
☐	Labelling in English	0P8NM
☐	Cab position 720 mm (distance from frame lower edge to cab floor)	0PHBF

Registration

☐	Vehicle approval, N3G class	0P3JS
☐	Maximum speed limiter, 85 km/h, electronic, engine speed regulation	0P2UI
☐	Maximum vehicle noise level not defined	0P2YN
☐	Height over cab, unloaded up to 4,000 mm	0PHA1
☐	Vehicle classification in accordance with regulation (EU) 2018/858	0PKAW

Documents

☐	European standard exhaust emission confirmation	0P2Q7
☐	Without registration documentation, national	0P3B0
☐	Dangerous goods equipment, in accordance with ADR Type AT	0P0YR

Application scope / transport tasks

☐	Construction	0P6WH
☐	999 Miscellaneous vehicle	0P2S2
☐	Temperature range, vehicle deployment, warm country	0PHIB
☐	Case hardness of final drive Distribution	0P4F0

Lines, editions and packages

☐	Special request paintwork	0PJTD
☐	Without Individual Lion package	0PJT1

Horizontal and vertical loads

☐	33,000 kg permitted gross load, vertical, nat. appr.	0P5QP
☐	33,000 kg permitted gross load, vertical, tech.	0P5UA
☐	33,000 kg permitted gross load, vertical, tech. Plus	0P8HZ
☐	8,000 kg permitted load on front axle, nat. appr.	0P5KT
☐	8,000 kg permitted load on front axle, tech.	0P5LN
☐	8,000 kg permitted load on front axle, tech. Plus	0P8D4
☐	13,000 kg permitted load on rear axle NatZu	0P5HC
☐	13,000 kg permitted load on rear axle, tech.	0P5IO



☐	13,000 kg permitted load on rear axle, tech. Plus	0P8BY
☐	13,000 kg permitted load on 2nd rear axle NatZu	0P5FM
☐	13,000 kg permitted load on 2nd rear axle, tech.	0P5M9
☐	13,000 kg permitted load on 2nd rear axle, tech. Plus	0P7TJ
☐	0kN D value	0P8XD

Notification texts

☐	Note: Restricted steerability with engaged differential lock on front axle	0PFZN
☐	Note: Max. 42,000 kg tech. permitted gross weight with engaged off-road reduction ratio in transfer case	0PFZS
☐	Without note (propshaft wear)	0PJRV

Chassis

Vehicle frame (wheelbase, overhang, ...)

☐	Main wheelbase, 4,500 mm	0P2ZW
☐	Wheelbase between rear axles, 1,400 mm	0P3BX
☐	Frame overhang, rear, 2,500 mm	0P3E1
☐	Main frame side member thickness, 9.5 mm	0P0Y7
☐	Vehicle rear, straight end of frame	0P0XT

Exhaust system, air intake

☐	Exhaust silencer, side, left	0P1BG
☐	Exhaust tailpipe, towards rear	0P1BQ
☐	Air intake, behind cab, raised	0P0AY
☐	Pre-separator for engine air intake	0P0BA

Battery cases, batteries, alternator

☐	2 batteries, 12 V, 180 Ah, long-life (EFB), maintenance free	0PGB1
☐	Three-phase alternator 28 V, 120 A, 3,360 W, Longlife Eco	0P1BW
☐	Medium battery box, 2 batteries	0P0WU
☐	Battery box, left	0P0WO
☐	Main battery switch, mechanical	0P0WF
☐	Fuses	0P1V1

Tanks and fuel line

☐	Fuel tank capacity 400 l, right	0P4ED
☐	Fuel tank, right, steel	0P4GN
☐	Tank cross-section, right, medium	0P4HE
☐	Fuel tank cap, lockable for master key system	0P4H5
☐	Filter screen for fuel tank filler neck	0P1EM
☐	Fuel pre-filter position on the battery box	0PIW9

Frame attachments

☐	Without underride protection, front	0P1FM
☐	Without working platform	0P0VH
☐	Without underride protection, side	0P1FG
☐	Spare wheel hoist on left side, in front of rear axle	0P0XO
☐	Hoist for spare wheel	0P0VN



☐	Final cross member, with hole pattern 160 x 100 mm	0P1SB
☐	Underride protection, rear, round	0P1FD
☐	Wheel chock, 1 unit, with retaining device	0P1FO
☐	Without body attachment brackets/thrust plates	0P0X6

Pneumatic brakes, compressed-air generation, brake system

☐	Air compressor, 1-cylinder, 360 ccm	0P0AF
☐	Compressed-air treatment, pneumatically controlled	0P0AB
☐	Steel compressed-air tank	0P0XH
☐	Electronic brake system (EBS)	0P0BL
☐	Anti-lock braking system (ABS), Offroad, with additional off-road logic	0P0BF
☐	Full brake assistant	0P0CM
☐	Without preparation for EBS Full control unit	0PHPM
☐	MAN EVBec high-performance engine brake, stages possible	0P0BW
☐	Drum brakes on front axle	0P1IA
☐	Drum brakes on rear axle	0P1I5
☐	Drum brakes on 2nd rear axle	0P1IF
☐	Parking brake control, next to driver's seat	0P3KH
☐	Parking brake with spring-type actuator on rear axles (incl. leading axle/ trailing axle)	0PGBL
☐	MAN EasyStart immobiliser	0P1TF

Lights and acoustic signals on the chassis (rear lights, ...)

☐	Rear lights	0P2AQ
☐	Stone protection, for rear lights, guard, wide mesh	0P2AT
☐	Acoust. Reversing warning system deactivatable when reverse gear selected	0P3CE
☐	Light function test	0P2AD
☐	Side marker lights, LED	0P2BJ

Driveline/running gear

Engine, radiator

☐	Diesel engine MAN D2066 LF06, 294 kW (400 hp) output, 1,900 Nm torque, Euro 2	0P6BR
☐	Fuel filter, for fuels up to Cleanliness Class 25	0PHII
☐	Fuel pre-filter, with oil separator/water trap, with water sensor	0P4XO
☐	Without torque reduction	0P0G5
☐	Engine dry-air filter, with safety insert	0P0B8
☐	Ventilation, crankcase, closed	0P8PM
☐	Reduction of dust swirl through radiator fan	0P1YE
☐	Engine cooler, normal length	0P4XX
☐	Radiator protection, lower	0P1XE
☐	Front radiator protection, grille	0P1VP
☐	Engine oil dipstick and digital oil level gauge	0P0B6
☐	Warning message for engine coolant level, with advance warning	0P0KA
☐	Antifreeze, down to -32 °C	0P0AK
☐	Service product level indicator and intake system vacuum	0P3KT

Gearbox, clutch

☐	MAN TipMatic 12.28 OD	0P5VW
--------------------------	-----------------------	-------



☐	Gearbox for increased percentage of overrun during driving operation	0PGCL
☐	MAN TipMatic actuation, with drop arm, manual (DNR option, switching strategy option)	0P3KI
☐	MAN Idle Speed Driving gearbox function	0P0ER
☐	Rock-free gearbox function	0P0EV
☐	MAN TipMatic Efficiency driving program, up to 70,000 kg	0P0FA
☐	MAN TipMatic Offroad gearbox shift strategy, up to 70,000 kg	0P0F4
☐	MAN TipMatic Manoeuvre driving program, manoeuvring feature	0P0FI
☐	Transfer case MAN G173 with on-road and off-road gear, neutral position	0P4XK
☐	Transfer case lock management, electronic (VSM)	0P0FU
☐	Single-disc clutch, 430 mm, dry, reinforced (LongLife)	0P0DW
☐	Main propshaft, 30,000 Nm functional limit torque	0PKZJ
☐	Propshafts with standard grease, cannot be lubricated	0PKZL
☐	Driveline propshaft, reinforced	0P0E2
☐	Propshaft, 2nd rear axle, reinforced	0PGCF

Wheels, tyres



- Required tyre speed index J
- Front axle tyres Bridgestone 385/65R22.5 M-STEER 001 Steering-S+G TL

0PFW2
0PGXV



Product Information Sheet

Delegated Regulation (EU) 2020/740

Supplier name or trademark	BRIDGESTONE
Commercial name or trade designation	M-STEER 001
Tyre type identifier	23732
Tyre size designation	385/65 R22.5
Load-capacity index	160
Load-capacity index (Load index for Dual mounting)	
Speed category symbol	K
Fuel efficiency class	C
Wet grip class	B
External rolling noise class	A
External rolling noise value	71 dB
Severe snow tyre	Yes
Date of start of production	23/20
Date of end of production	-
Additional information	
Load-capacity index (Single load index for Additional Service Description)	
Load-capacity index (Dual load index for Additional Service Description)	
Speed category symbol (for Additional Service Description)	


- Rim type, front axle, steel, single-part

0P0P0



- Rim size, front axle, 10-hole, 11.75x22.5
- Rear axle tyres Bridgestone 315/80R22.5 M-DRIVE 001 Drive-S+G TL

0P0NB
0PDT9



Product Information Sheet

Delegated Regulation (EU) 2020/740

Supplier name or trademark	BRIDGESTONE
Commercial name or trade designation	M-DRIVE 001
Tyre type identifier	8691
Tyre size designation	315/80 R22.5
Load-capacity index	156
Load-capacity index (Load index for Dual mounting)	150
Speed category symbol	K
Fuel efficiency class	D
Wet grip class	B
External rolling noise class	A
External rolling noise value	72 dB
Severe snow tyre	Yes
Date of start of production	14/16
Date of end of production	-
Additional information	
Load-capacity index (Single load index for Additional Service Description)	
Load-capacity index (Dual load index for Additional Service Description)	
Speed category symbol (for Additional Service Description)	


- Rim type, rear axle, steel, single-part

0P000



- Rim size, rear axle, 10-hole, 9.00x22.5
- Tyres for 2nd rear axle Bridgestone 315/80R22.5 M-DRIVE 001 Drive-Road+Offroad TL

0P0MU
0PEB9



Product Information Sheet

Delegated Regulation (EU) 2020/740

Supplier name or trademark	BRIDGESTONE
Commercial name or trade designation	M-DRIVE 001
Tyre type identifier	8691
Tyre size designation	315/80 R22.5
Load-capacity index	156
Load-capacity index (Load index for Dual mounting)	150
Speed category symbol	K
Fuel efficiency class	D
Wet grip class	B
External rolling noise class	A
External rolling noise value	72 dB
Severe snow tyre	Yes
Date of start of production	14/16
Date of end of production	-
Additional information	
Load-capacity index (Single load index for Additional Service Description)	
Load-capacity index (Dual load index for Additional Service Description)	
Speed category symbol (for Additional Service Description)	

- Rim type, 2nd rear axle, steel, single-part
- Rim size, 2nd rear axle, 10-hole, 9.00x22.5
- Spare wheel, in accordance with configuration for front axle tyres

0P0PA
0P0O7
0P0MH

Axes

- 6x6
- Steering ratio, indirect
- Steering oil tank with electrical measuring sensor
- Front axle, 9,000 kg, planetary axle without drive shaft, straight, steered, not liftable
- Front axle as planetary axle, driven, engageable
- Mudguard, front axle
- Rear axle HPD-1382, 13,000 kg, planetary axle with drive-through, straight, not steered, not liftable
- Twin tyre on rear axle

0P3BD
0P1JY
0P1JV
0P5ES
0P1GY
0P1AT
0PIY1
0P1HN



☐	Mudguard, rear axle, upper shell removable	0P1AM
☐	Splash guard mat on mudguard, rear axle, longer at bottom	0P1XK
☐	2nd rear axle HP-1352, 13,000 kg, planetary axle without drive-through, straight, not steered, not liftable	0P1VD
☐	Twin tyre on 2nd rear axle	0P1HW
☐	Mudguard, 2nd rear axle, removable upper shell	0P1B3
☐	Splash guard mat on mudguard, 2nd rear axle, longer at bottom	0P1Y0
☐	Axle ratio, $i = 4.33$	0P0D6
☐	Differential locks on driven rear axles	0P0DI
☐	Differential locks on driven front axles	0P0DK
☐	Warning buzzer when front axle locks are engaged	0P0DQ
☐	Mudguard enlargement	0P1W5

Axle control system and suspension

☐	Suspension type for front axles and driven rear axles, leaf/leaf (BB)	0P2YB
☐	Leaf-spring suspension on front axle, parabolic, 3-leaf, steel	0P1JE
☐	Leaf-spring suspension on rear axle, parabolic, 5-leaf, steel	0P1J2
☐	Leaf-spring suspension on 2nd rear axle, parabolic, 5-leaf, steel	0P1JL
☐	Spring load-bearing capacity front axle 9,500 kg	0P5C4
☐	Spring load-bearing capacity of rear axle, 16,000 kg	0P5BW
☐	Spring load-bearing capacity of 2nd rear axle, 16,000 kg	0P5C8
☐	Shock absorbers on front axle	0P1M4
☐	Shock absorbers on rear axle	0P1LQ
☐	Shock absorbers on 2nd rear axle	0P1M9
☐	Stabiliser, front axle	0P1LD
☐	Stabiliser, rear axle	0P1LA
☐	Stabiliser, 2nd rear axle	0P1LH
☐	Wishbone, reinforced	0P6ZS
☐	Without air suspension control, trailer/semitrailer	0PHN2

Cab

Cab and cab exterior

☐	Local transport cab NN	0P2DL
☐	Cab mount, Basic	0P1V8
☐	Cab tilt mechanism, manual	0P1V6
☐	No tilting roof/sliding roof	0P1VY
☐	Bumper, steel, 3 pieces	0P1SG
☐	Front step, integrated, with grab option	0P1VE
☐	Windscreen, composite safety glass, tinted	0P1X0
☐	Sunblind, in front of windscreen	0P1WK
☐	Wiper system for windscreen	0P1WG
☐	Wiper activation, manual	0P1UL
☐	Step unit, hinged	0P1V0
☐	Central locking, no remote control	0P1WS
☐	Vehicle key, 2 units	0P3JT
☐	No door extension	0P1WV
☐	Door labelling, according to trade tonnage of vehicle	0P2DQ



☐	Door windows, tinted	0P1WO
☐	Door window, safety glass	0P1WM
☐	Cab rear wall, no window	0P1VD
☐	A-pillar cladding, aerodynamically optimised	0PIY8

Lights and acoustic signals on cab exterior (headlights, horn, ...)

☐	Without light and headlight package	0PKWU
☐	Front headlights, H7	0P1ZN
☐	Stone protection guard for front headlights, wide and fine mesh	0PICD
☐	Daytime driving lights with rear lights, H7	0P2BO
☐	Fog lights, H7	0P2AH
☐	Turn signal lights, sides, bulb	0P1Z6
☐	Headlight beam regulator, manual	0P2AC
☐	Driving-light control, manual	0P1ZF
☐	Contour lights, LED, 2 units	0P2BS
☐	Horn, two-tone, electrical	0P1W1
☐	Revolving beacons, LED, yellow (individual LEDs light up in cascades, revolving)	0P2BD
☐	2 revolving beacons on cab roof, 1 right and 1 left	0P2B3
☐	Spotlight, 1 unit, cab roof, left	0P1YK
☐	Spotlight, LED, white	0PJQA
☐	Switch for spotlight/manoeuvring light	0P5U5
☐	Preparation for loading area lighting	0P2A5
☐	Without revolving beacons at the rear of the vehicle	0PJRO

Mirrors and mirror replacements

☐	Without mirror package	0PKWV
☐	Exterior rear-view mirror, mechanically adjustable	0P2CC
☐	Kerb mirror, right, mechanically adjustable	0P2CH
☐	Front mirror, mechanical adjustment	0P2CJ
☐	Mirror housing, not painted	0P2CP
☐	Vehicle components, suitable for body width larger than 2,400 mm to 2,600 mm	0P2CT

Seats

☐	Seat covers, fabric, standard	0P2PQ
☐	Without driver's seat package	0PKXV
☐	Comfort driver's seat, air-sprung	0P2P2
☐	Driver's seat arm rests	0P2OE
☐	Adjustment of seat belt height, driver's seat	0P4XQ
☐	Without co-driver's seat package	0PKXU
☐	Co-driver's seat, not sprung, with storage box	0P2OO
☐	Storage space, in seat bracket of co-driver's seat	0P2Q6
☐	Seat belt indicator, driver's side, acoustic and visual	0P2NB

Driver's workplace

☐	Multi-function steering wheel, adjustable height and angle	0P2GD
☐	Steering wheel, with parking position	0P2GE
☐	Steering lock	0P3JZ
☐	Instrumentation, Basic km/h	0P3L3
☐	Tachograph Simulation Unit (TSU), instead of tachograph	0P2KY



☐	Tachograph, calibrated	0P2KG
☐	Stowage compartment, open with two USB sockets, 5 V, charging only, to the right of climate control panel	0PGT7
☐	Cigarette lighter	0P2IH
☐	Single DIN slots, 4 units, roof space, front	0P2FJ
☐	Without storage tray next to seat	0PJRS

Cab air-conditioning system

☐	Air-conditioning system, manual	0P2NU
☐	Pre-separator (cyclone filter) for interior air intake	0P2O7

Bunk area

☐	Without bunk area	0PKFY
--------------------------	-------------------	-------

Cab interior

☐	Colour scheme for interior styling, dark	0P2I6
☐	Interior styling analogous to colour scheme	0PGBT
☐	Without driver's workplace package, Comfort	0PKXT
☐	Windscreen roller blind, internal	0P2FE
☐	Interior light, reading light (driver's side)	0PKMY
☐	Interior light, central	0PHA6
☐	Reading light, 1 unit, driver's side	0P2IQ
☐	Entry lighting	0P2IO
☐	Entry handles, standard	0PHPK
☐	Door interior cladding, washable	0P2IA
☐	Without stowage and storage space package	0PKXS
☐	2 storage compartments, cab rear wall, behind driver's and co-driver's side and net on cab rear wall	0PGB8
☐	Storage, instrument panel in middle section, open	0P2HK
☐	Grab handle, above door, internal, 2 units, 1 right and 1 left	0P2G2

Accessories and tools

☐	Without accessories and tools package	0PKXA
☐	Vehicle toolkit	0P2TX
☐	No warning triangle	0P3FH
☐	Jack, 12,000 kg	0P3F8

Intelligent Truck

Assistance systems

☐	Tempomat (cruise control, CC)	0P1TR
☐	Without advanced emergency braking system	0P1U5
☐	Without driving fitness detection system	0PHN5
☐	Without Front Detection	0PHNA
☐	Without traffic sign recognition	0PHNE
☐	Without Reversing Motion System	0PHNV
☐	Without distance warning system	0PKA0
☐	Without MAN SafeStop Assist	0PLB5



Infotainment (radio,...)

☐	MMT infotainment system, Starter Basic	0P2M1
☐	MAN Advanced sound system	0P2MH
☐	No navigation map	0P2N2

Bodies/interfaces

Interfaces to semitrailer (e.g. fifth-wheel coupling, brake connection,...)

☐	Without trailer brake connection behind cab	0P1O3
☐	No fifth-wheel coupling	0P1RJ
☐	Without sensing of the fifth-wheel coupling	0PHN7

Interfaces to trailer (e.g. trailer coupling, brake connections,...)

☐	Towing coupling at final cross member, ROCKINGER SK5	0P1MZ
☐	Towing coupling on final cross member	0P1SH
☐	Without trailer brake connection at end of frame, centre	0P1O0
☐	Without trailer socket at frame end	0P1OW
☐	Without trailer socket for anti-lock brake system (ABS)	0P1O9

Ex works bodies and interfaces to bodies (e.g. tipper indicator...)

☐	Interface for data exch. with body (customer-specific control module) and engine intermediate speed control (ZDR), front area of cab	0P2NA
☐	Interface for vehicle data (FMS)	0P2J3

PTOs

☐	PTO, gearbox-dependent, type NH/4c, without flange, $f=0.88/1.14$, position approx. 2:30 o'clock	0P4QS
☐	PTO, gearbox-dependent, for short-time operation less than 60 min	0P4VK
☐	PTO, gearbox-dependent, shiftable	0P4X9
☐	Without fan wheel for PTO, gearbox-dependent	0P4VR
☐	Function parameters for PTO, gearbox-dependent, stationary operation	0P4WO
☐	Gearbox shift blocking for PTO operation, electric/electronic	0P4VU
☐	Sector-specific parameterisation, general	0P4X0

Towing, recovery and lashing

☐	Central coupling jaw, integrated in bumper/front cross member, with lock pin	0P1MK
--------------------------	--	-------

Paintworks

Paintwork, cab, top

☐	Top coating, cab	0P6YB
--------------------------	------------------	-------

Paintwork, cab, bottom

☐	Textured coating, step units	0P6X9
☐	Textured coating, mudguard, behind cab	0P6YG
☐	Textured coating, bumper, steel	0P6YQ

Paintwork, chassis

☐	Without additional top coating on chassis	0PJTK
--------------------------	---	-------



□ Top coating, rims, steel, white-aluminium

0P6YL

Colour

□ Top coating, cab

PURE WHITE RAL 9010

N



Technical data: TGS 33.400 6x6 BB CH / L56EAA04

Vehicle type: Vehicle type, platform truck and chassis (LK)

Cab: Local transport cab NN

Drive Type: 6x6

Lengths		mm
TD071	Total length	10375.0
TD063	Front vehicle overhang	1605.0
TD057	Wheelbase between front axles	0
TD058	Wheelbase between leading axle and rear axle	0
TD059	Wheelbase between rear axles	1400
TD060	Wheelbase between rear axle and trailing axle	0
TD064	Rear frame overhang	2500.0
TD072	Distance from first front axle to body	465.0
TD067	Distance to kingpin from front axle, nominal position	-
TD074	Slew radius, front	-
TD075	Slew radius, rear	-
TD068	Coupling length	9799.0

Lengths		mm
TD071	Total length	10375.0
TD063	Front vehicle overhang	1605.0
TD057	Wheelbase between front axles	0
TD058	Wheelbase between leading axle and rear axle	0
TD059	Wheelbase between rear axles	1400
TD060	Wheelbase between rear axle and trailing axle	0
TD064	Rear frame overhang	2500.0
TD072	Distance from first front axle to body	465.0
TD067	Distance to kingpin from front axle, nominal position	-
TD074	Slew radius, front	-
TD075	Slew radius, rear	-
TD068	Coupling length	9799.0

Widths		mm
TD008	Width included rearview mirror	2981.0
TD001	Width over cab	2240.0

Widths		mm
TD008	Width included rearview mirror	2981.0
TD001	Width over cab	2240.0

Frame		mm
TD009	Frame width at front	945.0
TD010	Frame width at the rear	765.0
TD078	Frame profile	270 x 85 x 9,5

Frame		mm
TD009	Frame width at front	945.0
TD010	Frame width at the rear	765.0
TD078	Frame profile	270 x 85 x 9,5

Heights		mm
TD033	Maximum external height, unladen	3431.0
TD082	Total transport height, unladen	3431.0
TD034	Maximum external height, laden	3333.0
TD035	Frame height at theoretical rear wheelbase, unladen	1193.0
TD036	Frame height at theoretical rear wheelbase, laden	1110.0
TD045	Raising from driving position, front	0.0
TD046	Lowering from driving position, front	0.0
TD047	Raising from driving position, rear	0.0
TD048	Lowering from driving position, rear	0.0
TD051	Height of fifth-wheel coupling above ground, unladen	-
TD052	Height of fifth-wheel coupling above ground, laden	-

Heights		mm
TD033	Maximum external height, unladen	3431.0
TD082	Total transport height, unladen	3431.0
TD034	Maximum external height, laden	3333.0
TD035	Frame height at theoretical rear wheelbase, unladen	1193.0
TD036	Frame height at theoretical rear wheelbase, laden	1110.0
TD045	Raising from driving position, front	0.0
TD046	Lowering from driving position, front	0.0
TD047	Raising from driving position, rear	0.0
TD048	Lowering from driving position, rear	0.0
TD051	Height of fifth-wheel coupling above ground, unladen	-
TD052	Height of fifth-wheel coupling above ground, laden	-

Circle dimensions		m
TD055	Track circle diameter	20.5
TD056	Wall-to-wall turning circle diameter	22.3

Circle dimensions		m
TD055	Track circle diameter	20.5
TD056	Wall-to-wall turning circle diameter	22.3

Weights/loads		kg
TD026	Chassis weight with cab	10570
TD027	Chassis weight, front	5433
TD028	Chassis weight, rear	5137
TD029	Payload	22430
TD018	Statutorily permissible gross vehicle weight	33000
TD025	Technically permissible gross vehicle weight	33000
TD031	Statutorily permissible gross train weight	0
TD032	Statutorily permissible trailer load	0

Weights/loads		kg
TD026	Chassis weight with cab	10570
TD027	Chassis weight, front	5433
TD028	Chassis weight, rear	5137

The technical data must be considered as an approximation. Some of the values are given in a simplified form. More detailed notes and descriptions can be found in the respective information in the overview. Contents and specifications have been compiled with the greatest possible care. Nevertheless, we do not assume responsibility for the data and values supplied being correct and up to date. Subject to errors and changes. MAN Truck & Bus AG is liable only in cases of intent, gross negligence or culpable breach of significant contractual obligations.



TD029	Payload	22430
TD018	Statutorily permissible gross vehicle weight	33000
TD025	Technically permissible gross vehicle weight	33000
TD031	Statutorily permissible gross train weight	0
TD032	Statutorily permissible trailer load	0

The technical data must be considered as an approximation. Some of the values are given in a simplified form. More detailed notes and descriptions can be found in the respective information in the overview. Contents and specifications have been compiled with the greatest possible care. Nevertheless, we do not assume responsibility for the data and values supplied being correct and up to date. Subject to errors and changes. MAN Truck & Bus AG is liable only in cases of intent, gross negligence or culpable breach of significant contractual obligations.
