

BUILDING SPECIFICATION:

- L - inside length approx. (mm) 5650
- B - external width approx. (mm) 2550
- H - side height approx. (mm) 1450
- V - volume approx. (m³) 17.5
- 8mm floor, wear-resistant HARDOX 450 steel
- side walls 5mm, hard-wearing HARDOX 450 steel, fixed without reinforcing ribs, rear wall 6mm opens automatically when lifted
- 5mm front side, with roof over the hydraulic cylinder

HYDRAULIC SYSTEM

- front, HYVA hydraulic cylinder
- HYVA hydraulic pump
- main hydraulic valve
- Tipping limit valve
- HYVA oil tank with filter and oil level indicator
- hydraulic oil HLP 32
- Raised box indicator light on panel with buzzer
- pneumatic tipping control lever in the cabin

OTHER EQUIPMENT

- scissor stabilizer between the box and the frame
- repair supports
- aluminum rear axle fenders
- foldable ladder mounted to the front boot
- tarpaulin rolled up manually on the front side, without pleats
- steel rear light cover with easily removable grille
- yellow and red reflective plates
- installation of yellow marker lights
- self-adhesive reflective tapes
- all steel parts shot-blasted, primed and painted
- Weight of the structure approx. 4400 kg
- Box built onto the chassis

