



Vehicle description for: TGM 18.250 4x2 BB CH



Vehicle standards

Product family	The new MAN Truck Generation
Model & Variant	TGM 18.250 4x2 BB CH
Emission class	EURO5
Engine family	D08R6
Engine output	184 kW
Vehicle type	Vehicle type, platform truck and chassis (LK)
Body type	060 Box body, universal
Cab	DN cab: the crew cab (narrow, extra long, normal height)
Main wheel distance	4425 mm
Overhang	2325 mm
Steering configuration	Right

Vertical Load

	National Registration	Technical Load	Technical Load Plus
Gross weight	18,000 kg	18,000 kg	18,000 kg
Front axle	7,100 kg	7,100 kg	7,100 kg
Rear axle	11,500 kg	11,500 kg	11,500 kg

Horizontal Load

	National Registration	Technical Load	Technical Load Plus
Gross train weight	0 kg	0 kg	0 kg



The printed images in this offer are for explanatory purposes and may differ from the actual configuration.
For further product information on the tire selection "selectively", please contact our sales staff.

Vehicle characteristics

Basic characteristics

<input type="checkbox"/>	Vehicle version for public service deployment	0P0H7
<input type="checkbox"/>	Chassis	0P2U9
<input type="checkbox"/>	Chassis class, light/medium	0P2UB
<input type="checkbox"/>	Destination: Columbia (CO)	0P3H1
<input type="checkbox"/>	Merchant tonnage 18 t	0P8LF
<input type="checkbox"/>	Basic layout, weight-optimised vehicle	0PLSK
<input type="checkbox"/>	Application area, beside road easy (T1)	0PLSE
<input type="checkbox"/>	Frame type, normal height	0P2TS
<input type="checkbox"/>	Vehicle type, platform truck and chassis (LK)	0P2UQ
<input type="checkbox"/>	Right-hand-drive	0P3AT
<input type="checkbox"/>	Right-hand traffic	0P3F5
<input type="checkbox"/>	Vehicle documents in English	0P2L7
<input type="checkbox"/>	Labelling in English	0P8NM
<input type="checkbox"/>	Cab position 530 mm (distance from frame lower edge to cab floor)	0PHBD

Registration

<input type="checkbox"/>	VO (EU) (towing equipment) not required	0PJW7
<input type="checkbox"/>	Vehicle approval, N3 class	0P3JR
<input type="checkbox"/>	Maximum speed limiter, 80 km/h, electronic, engine speed regulation	0P2UG
<input type="checkbox"/>	VO (E.U.) 1003/2010 (mounting and fixing of number plate) not required	0PFWT
<input type="checkbox"/>	Maximum vehicle noise level not defined	0P2YN
<input type="checkbox"/>	Height over cab, unloaded up to 4,000 mm	0PHA1
<input type="checkbox"/>	Vehicle classification in accordance with regulation (EU) 2018/858	0PKAW

Documents

<input type="checkbox"/>	Without registration documentation, national	0P3B0
--------------------------	--	-------

Application scope / transport tasks

<input type="checkbox"/>	Distribution transport, general cargo	0P6WA
<input type="checkbox"/>	060 Box body, universal	0P2QS
<input type="checkbox"/>	Temperature range, vehicle deployment, warm country	0PHIB
<input type="checkbox"/>	Case hardness of final drive Distribution	0P4F0

Lines, editions and packages

<input type="checkbox"/>	Without Efficient Drive	0PVBQ
<input type="checkbox"/>	Special request paintwork	0PJTD
<input type="checkbox"/>	Without Individual Lion package	0PJT1

Horizontal and vertical loads

<input type="checkbox"/>	18,000 kg permitted gross load, vertical, nat. appr.	0P5PB
<input type="checkbox"/>	18,000 kg permitted gross load, vertical, tech.	0P5S4
<input type="checkbox"/>	18,000 kg permitted gross load, vertical, tech. Plus	0P8GQ
<input type="checkbox"/>	7,100 kg permitted load on front axle, nat. appr.	0P5KQ
<input type="checkbox"/>	7,100 kg permitted load on front axle, tech.	0P5LK
<input type="checkbox"/>	7,100 kg permitted load on front axle, tech. Plus	0P8DY



<input type="checkbox"/>	11,500 kg permitted load on rear axle NatZu	0P5G7
<input type="checkbox"/>	11,500 kg permitted load on rear axle, tech.	0P5IJ
<input type="checkbox"/>	11,500 kg permitted load on rear axle, tech. Plus	0P8BN
<input type="checkbox"/>	0kN D value	0P8XD

Notification texts

<input type="checkbox"/>	Note: With increased permissible gross weight, increase in wear of driveline and reduced service life	0PFZP
<input type="checkbox"/>	Note: Difference of more than 2% in FA/RA rolling circumference may lead to perceptible tension in the driveline.	0PHCX
<input type="checkbox"/>	Without note (propshaft wear)	0PJRV

Chassis

Vehicle frame (wheelbase, overhang, ...)

<input type="checkbox"/>	Main wheelbase, 4,425 mm	0P2ZV
<input type="checkbox"/>	Frame overhang, rear, 2,325 mm	0P3DT
<input type="checkbox"/>	Main frame side member thickness, 7 mm	0P0Y5
<input type="checkbox"/>	Vehicle rear, straight end of frame	0P0XT

Exhaust system, air intake

<input type="checkbox"/>	Exhaust silencer, side, right	0P1BH
<input type="checkbox"/>	Exhaust tailpipe, towards middle of frame	0P1BT
<input type="checkbox"/>	Air intake, behind cab, raised	0P0AY
<input type="checkbox"/>	Pre-separator for engine air intake	0P0BA

Battery cases, batteries, alternator

<input type="checkbox"/>	Without AC charging	0PNW4
<input type="checkbox"/>	2 batteries, 12 V, 180 Ah, long-life (EFB), maintenance free	0PGB1
<input type="checkbox"/>	Three-phase alternator 28 V, 120 A, 3,360 W, Longlife Eco	0P1BW
<input type="checkbox"/>	Medium battery box, 2 batteries	0P0WU
<input type="checkbox"/>	Battery box, left	0P0WO
<input type="checkbox"/>	Main battery switch, mechanical	0P0WF
<input type="checkbox"/>	Fuses	0P1V1

Tanks and fuel line

<input type="checkbox"/>	Fuel tank capacity 300 l, right	0P4E8
<input type="checkbox"/>	Fuel tank, right, steel	0P4GN
<input type="checkbox"/>	Tank cross-section, right, low	0P4HF
<input type="checkbox"/>	AdBlue tank capacity 27 l, right	0P4CY
<input type="checkbox"/>	AdBlue tank, right, plastic	0P4HU
<input type="checkbox"/>	Fuel tank cap, lockable for master key system	0P4H5
<input type="checkbox"/>	Cap for AdBlue tank, lockable	0P4GE
<input type="checkbox"/>	Fuel pre-filter on the frame	0PKN2

Frame attachments

<input type="checkbox"/>	Underride protection, front	0P1FN
<input type="checkbox"/>	Without working platform	0P0VH
<input type="checkbox"/>	Without underride protection, side	0P1FG



<input type="checkbox"/>	Spare wheel, provisionally mounted	0P1GR
<input type="checkbox"/>	Final cross member, with hole pattern 160 x 100 mm	0P1SB
<input type="checkbox"/>	Without underride protection, rear	0P1FB
<input type="checkbox"/>	Wheel chock, 1 unit, with retaining device	0P1FO
<input type="checkbox"/>	Without body attachment brackets/thrust plates	0P0X6
<input type="checkbox"/>	Without sensors on the side	0PMCP

Pneumatic brakes, compressed-air generation, brake system

<input type="checkbox"/>	Air compressor, 1-cylinder, 238 ccm	0P0AD
<input type="checkbox"/>	Air dryer, heated	0P0B2
<input type="checkbox"/>	Compressed-air treatment, electronically controlled	0P0AA
<input type="checkbox"/>	Steel compressed-air tank	0P0XH
<input type="checkbox"/>	Electronic brake system (EBS)	0P0BL
<input type="checkbox"/>	Anti-lock braking system (ABS)	0P0BE
<input type="checkbox"/>	Full brake assistant	0P0CM
<input type="checkbox"/>	Without preparation for EBS Full control unit	0PHPM
<input type="checkbox"/>	MAN EVB high-performance engine brake	0P0BV
<input type="checkbox"/>	Disc brakes on front axle with brake lining return	0PKA7
<input type="checkbox"/>	Disc brakes on rear axle with brake lining return	0PKA5
<input type="checkbox"/>	Parking brake control, next to driver's seat	0P3KH
<input type="checkbox"/>	Parking brake with spring-type actuator on rear axles (incl. leading axle/ trailing axle)	0PGBL
<input type="checkbox"/>	MAN EasyStart immobiliser	0P1TF
<input type="checkbox"/>	Brake lining thickness display, with brake lining wear warning	0P0BG

Lights and acoustic signals on the chassis (rear lights, ...)

<input type="checkbox"/>	Rear lights	0P2AQ
<input type="checkbox"/>	Acoust. Reversing warning system when reverse gear selected	0P3CD
<input type="checkbox"/>	Light function test	0P2AD
<input type="checkbox"/>	No side marker lights	0P2BK

Driveline/running gear

Engine, radiator

<input type="checkbox"/>	MAN D0836 LFL89 diesel engine (ODm), 184 kW (250 HP) power, 1,050 Nm torque, Euro 5	0P5ZX
<input type="checkbox"/>	Fuel filter, heated, for fuels up to Cleanliness Class 25	0PHIG
<input type="checkbox"/>	Fuel pre-filter, with water trap, with water sensor, heated (mixing valve)	0P4XP
<input type="checkbox"/>	Without torque reduction	0P0G5
<input type="checkbox"/>	Ventilation, crankcase, closed	0P8PM
<input type="checkbox"/>	Engine cooler, normal length	0P4XX
<input type="checkbox"/>	Engine oil dipstick	0P0B5
<input type="checkbox"/>	Antifreeze, down to -32 °C	0P0AK

Gearbox, clutch

<input type="checkbox"/>	MAN PowerMatic 08.13 OD	0PHMK
<input type="checkbox"/>	Gearbox for normal percentage of overrun during driving operation	0PGDA
<input type="checkbox"/>	Gearbox, 8-speed	0PHML
<input type="checkbox"/>	MAN TipMatic actuation, with drop arm, manual (DNR option, switching strategy option)	0P3KI
<input type="checkbox"/>	MAN Idle Speed Driving gearbox function	0P0ER



- ❑ MAN TipMatic Efficiency driving program, up to 70,000 kg
0P0FA
- ❑ Without drive clutch
0PIXX
- ❑ Main propshaft, 14,000 Nm functional limit torque
0PKZG
- ❑ Propshafts with standard grease, cannot be lubricated
0PKZL
- ❑ Gearbox heat exchanger
0P0FW

Wheels, tyres


- ❑ Required tyre speed index F
0PFW9
- ❑ Tyres for front axle, Goodyear 295/80R22.5 OMNITRAC S Steering-Road+Offroad TL
0PGJZ






Goodyear 569544

295/80R22,5 152/148 K C3



D



B



A



YES

2020/740

Product Information Sheet

Delegated Regulation (EU) 2020/740

Supplier name or trademark	GOODYEAR
Commercial name or trade designation	OMNITRAC S
Tyre type identifier	569544
Tyre size designation	295/80R22.5
Load-capacity index	152
Load-capacity index (Load index for Dual mounting)	148
Speed category symbol	K
Fuel efficiency class	D
Wet grip class	B
External rolling noise class	A
External rolling noise value	71 dB
Severe snow tyre	YES
Date of start of production	40/18
Date of end of production	-
Additional information	
Load-capacity index (Single load index for Additional Service Description)	
Load-capacity index (Dual load index for Additional Service Description)	
Speed category symbol (for Additional Service Description)	

- ❑ Rim type, front axle, steel, single-part
0P0P0
- ❑ Rim size, front axle, 10-hole, 9.00x22.5
0P0NI



- Wheel nut cover ring, front axle
- Tyres for rear axle, Goodyear 295/80R22.5 OMNITRAC D Drive-Road+Offroad TL

0P0PR
0PGEB



Product Information Sheet

Delegated Regulation (EU) 2020/740

Supplier name or trademark	GOODYEAR
Commercial name or trade designation	OMNITRAC D
Tyre type identifier	569562
Tyre size designation	295/80R22.5
Load-capacity index	152
Load-capacity index (Load index for Dual mounting)	148
Speed category symbol	K
Fuel efficiency class	D
Wet grip class	B
External rolling noise class	B
External rolling noise value	75 dB
Severe snow tyre	YES
Date of start of production	40/18
Date of end of production	-
Additional information	
Load-capacity index (Single load index for Additional Service Description)	
Load-capacity index (Dual load index for Additional Service Description)	
Speed category symbol (for Additional Service Description)	

- Rim type, rear axle, steel, single-part
- Rim size, rear axle, 10-hole, 8.25x22.5
- Spare wheel, in accordance with configuration for front axle tyres
- Centring sleeves for rim mounting

0P000
0P0MQ
0P0MH
0PHZW

Axles

- 4x2
- Steering ratio, standard
- Steering oil tank with dipstick
- Front axle, 7,500 kg, not driven, cranked, steered, not liftable
- Mudguard, front axle
- Splash guard mat on mudguard, front axle, longer at bottom
- Rear axle, 11,500 kg, HY axle without drive shaft, straight, not steered, not liftable
- Twin tyre on rear axle

0P3B1
0P1JX
0P1JW
0P5EQ
0P1AT
0P1XS
0P4ZL
0P1HN



<input type="checkbox"/>	Transfer mudguard, rear axle	0P1AQ
<input type="checkbox"/>	Axle ratio, $i = 5.29$	0P0DC
<input type="checkbox"/>	Differential locks on driven rear axles	0P0DI
<input type="checkbox"/>	Without differential locks, front axles	0P0DL

Axle control system and suspension

<input type="checkbox"/>	Suspension type for front axles and driven rear axles, leaf/leaf (BB)	0P2YB
<input type="checkbox"/>	Leaf-spring suspension on front axle, parabolic, 1-leaf, steel	0P1JC
<input type="checkbox"/>	Leaf-spring suspension on rear axle, parabolic, 4-leaf, steel	0PGBF
<input type="checkbox"/>	Spring load-bearing capacity front axle 7,500 kg	0P5CZ
<input type="checkbox"/>	Spring load-bearing capacity of rear axle, 11,500 kg	0P5BT
<input type="checkbox"/>	Shock absorbers on front axle	0P1M4
<input type="checkbox"/>	Shock absorbers on rear axle	0P1LQ
<input type="checkbox"/>	Stabiliser, front axle	0P1LD
<input type="checkbox"/>	Stabiliser, rear axle	0P1LA
<input type="checkbox"/>	Axle location system not as wishbone	0P6ZY
<input type="checkbox"/>	Without air suspension control, trailer/semitrailer	0PHN2

Cab

Cab and cab exterior

<input type="checkbox"/>	DN cab: the crew cab (narrow, extra long, normal height)	0P2DE
<input type="checkbox"/>	Cab mount, Comfort	0P1V9
<input type="checkbox"/>	Cab tilt mechanism, manual	0P1V6
<input type="checkbox"/>	Tilting roof, mechanical	0P1VW
<input type="checkbox"/>	Bumper, steel, 3 pieces	0P1SG
<input type="checkbox"/>	Front step, integrated, with grab option	0P1VE
<input type="checkbox"/>	Windscreen, composite safety glass, tinted	0P1X0
<input type="checkbox"/>	Sunblind, in front of windscreen	0P1WK
<input type="checkbox"/>	Wiper system for windscreen	0P1WG
<input type="checkbox"/>	Wiper activation, manual	0P1UL
<input type="checkbox"/>	Step unit, rigid	0P1UZ
<input type="checkbox"/>	Central locking, no remote control	0P1WS
<input type="checkbox"/>	Vehicle key, 4 units	0P3JU
<input type="checkbox"/>	No door extension	0P1WW
<input type="checkbox"/>	Door labelling, according to trade tonnage of vehicle	0P2DQ
<input type="checkbox"/>	Door windows, tinted	0P1WO
<input type="checkbox"/>	Door window, safety glass	0P1WM
<input type="checkbox"/>	Cab rear wall, no window	0P1VD

Lights and acoustic signals on cab exterior (headlights, horn, ...)

<input type="checkbox"/>	H7 package, front headlights, fog lights	0PKWS
<input type="checkbox"/>	Front headlights, H7	0P1ZN
<input type="checkbox"/>	Stone protection guard for front headlights, wide and fine mesh	0PICD
<input type="checkbox"/>	Daytime driving lights, H7	0P2BN
<input type="checkbox"/>	Fog lights, H7	0P2AH
<input type="checkbox"/>	Turn signal lights, sides, bulb	0P1Z6
<input type="checkbox"/>	Headlight beam regulator, manual	0P2AC



<input type="checkbox"/>	Driving-light control, manual	0P1ZF
<input type="checkbox"/>	Contour lights, bulb, 2 units	0P2BT
<input type="checkbox"/>	Horn, single-tone, electrical	0P1W0
<input type="checkbox"/>	Revolving beacons, LED, blue, with function monitoring (individual LEDs light up in cascades, revolving)	0P2BB
<input type="checkbox"/>	2 revolving beacons on cab roof, 1 right and 1 left	0P2B3
<input type="checkbox"/>	Without revolving beacons at the rear of the vehicle	0PJRO

Mirrors and mirror replacements

<input type="checkbox"/>	Mirror package, exterior rear-view mirror, manually adjustable, front mirror, kerb mirror, left	0PKWZ
<input type="checkbox"/>	Exterior rear-view mirror, mechanically adjustable	0P2CC
<input type="checkbox"/>	Kerb mirror, left, mechanically adjustable	0P2CE
<input type="checkbox"/>	Front mirror, mechanical adjustment	0P2CJ
<input type="checkbox"/>	Mirror housing, not painted	0P2CP
<input type="checkbox"/>	Vehicle components, suitable for body width larger than 2,400 mm to 2,600 mm	0P2CT

Seats

<input type="checkbox"/>	Seat covers, fabric, standard	0P2PQ
<input type="checkbox"/>	Plus driver's seat package, air-sprung	0PKXF
<input type="checkbox"/>	Comfort driver's seat, air-sprung	0P2P2
<input type="checkbox"/>	Basic co-driver's seat package, unsprung, with storage box	0PKTZ
<input type="checkbox"/>	Co-driver's seat, not sprung, with storage box	0P2OO
<input type="checkbox"/>	Storage space, in seat bracket of co-driver's seat	0P2Q6
<input type="checkbox"/>	Rear bench seat for 4 persons	0P2Q2

Driver's workplace

<input type="checkbox"/>	Multi-function steering wheel, adjustable height and angle	0P2GD
<input type="checkbox"/>	Steering wheel, with parking position	0P2GE
<input type="checkbox"/>	Steering lock	0P3JZ
<input type="checkbox"/>	Professional instrumentation, 12.3"	0P3L2
<input type="checkbox"/>	Tachograph Simulation Unit (TSU), instead of tachograph	0P2KY
<input type="checkbox"/>	Tachograph, calibrated	0P2KG
<input type="checkbox"/>	Plug-in ashtray, instrument panel in middle section, 1 unit	0P2FO
<input type="checkbox"/>	Cigarette lighter	0P2IH
<input type="checkbox"/>	Single DIN slots, 4 units, roof space, front	0P2FJ
<input type="checkbox"/>	Without storage tray next to seat	0PJRS

Cab air-conditioning system

<input type="checkbox"/>	Air-conditioning system, manual	0P2NU
<input type="checkbox"/>	Pre-separator (cyclone filter) for interior air intake	0P2O7

Bunk area

<input type="checkbox"/>	Without bunk area	0PKFY
--------------------------	-------------------	-------

Cab interior

<input type="checkbox"/>	Dark Moon Grey with silver colour scheme for cab interior	0PKFZ
<input type="checkbox"/>	Interior styling analogous to colour scheme	0PGBT
<input type="checkbox"/>	Basic driver's workplace package	0PKPN
<input type="checkbox"/>	Windscreen roller blind, internal	0P2FE
<input type="checkbox"/>	Interior light, reading light (driver's side)	0PKMY



<input type="checkbox"/>	Interior light, central	0PHA6
<input type="checkbox"/>	Reading light, 1 unit, driver's side	0P2IQ
<input type="checkbox"/>	Entry lighting	0P2IO
<input type="checkbox"/>	Entry handles, standard	0PHPK
<input type="checkbox"/>	Door interior cladding, washable	0P2IA
<input type="checkbox"/>	Without additional storage and stowage space	0PKWA
<input type="checkbox"/>	Storage, instrument panel in middle section, open	0P2HK
<input type="checkbox"/>	Multi-purpose storage box, centre of crew cab, in front of 2nd row of seats	0P2ES
<input type="checkbox"/>	Grab handle, above door, internal, 2 units, 1 right and 1 left	0P2G2
<input type="checkbox"/>	Grab handles on cab roof interior, rear	0P8QG

Accessories and tools

<input type="checkbox"/>	Vehicle tool kit without accessories	0PKXB
<input type="checkbox"/>	Vehicle toolkit	0P2TX
<input type="checkbox"/>	No warning triangle	0P3FH
<input type="checkbox"/>	Jack, 10,000 kg	0P3F7
<input type="checkbox"/>	Operator's manual in English, printed, additional	0P2JB

Intelligent Truck

Assistance systems

<input type="checkbox"/>	Electronic Stability Program (ESP)	0P1TN
<input type="checkbox"/>	Anti-slip control (ASR)	0P1T2
<input type="checkbox"/>	Tempomat (cruise control, CC)	0P1TR
<input type="checkbox"/>	Road speed limiter, adjustable, limiter (engine speed regulation)	0P0C3
<input type="checkbox"/>	Emergency Brake Assist EBA, cannot be deactivated	0PHDA
<input type="checkbox"/>	Without driving fitness detection system	0PHN5
<input type="checkbox"/>	Without Front Detection	0PHNA
<input type="checkbox"/>	Without traffic sign recognition	0PHNE
<input type="checkbox"/>	Without Reversing Motion System	0PHNV
<input type="checkbox"/>	Without distance warning system	0PKA0
<input type="checkbox"/>	Without MAN SafeStop Assist	0PLB5
<input type="checkbox"/>	Without rear area monitoring	0PMA9

Infotainment (radio,...)

<input type="checkbox"/>	MMT infotainment system, Advanced Basic	0P2LY
<input type="checkbox"/>	MAN sound system	0P2MG
<input type="checkbox"/>	No navigation map	0P2N2
<input type="checkbox"/>	Smartphone integration	0P2NE
<input type="checkbox"/>	French additionally for display	0P2JT

Bodies/interfaces

Interfaces to semitrailer (e.g. fifth-wheel coupling, brake connection,...)

<input type="checkbox"/>	Without trailer brake connection behind cab	0P1O3
<input type="checkbox"/>	No fifth-wheel coupling	0P1RJ
<input type="checkbox"/>	Without sensing of the fifth-wheel coupling	0PHN7



Interfaces to trailer (e.g. trailer coupling, brake connections...)

<input type="checkbox"/>	Towing coupling at final cross member, RINGFEDER type 6451	0P1MY
<input type="checkbox"/>	Towing coupling on final cross member	0P1SH
<input type="checkbox"/>	Without trailer brake connection at end of frame, centre	0P1OO
<input type="checkbox"/>	Without trailer socket at frame end	0P1OW
<input type="checkbox"/>	Without trailer socket for anti-lock brake system (ABS)	0P1O9

Ex works bodies and interfaces to bodies (e.g. tipper indicator...)

<input type="checkbox"/>	Interface for data exchange with tipper and engine speed. (ZDR), front area FHS and behind FHS	0PKNU
<input type="checkbox"/>	Interface for vehicle data (FMS)	0P2J3

PTOs

<input type="checkbox"/>	Without PTO, engine-dependent (direction of rotation)	0P4P8
<input type="checkbox"/>	PTO, gearbox-dependent, Heavy Duty type, with flange, f=1.3, position approx. 3 o'clock	0PHOC
<input type="checkbox"/>	PTO, gearbox-dependent, continuous operation	0P4VJ
<input type="checkbox"/>	PTO, gearbox-dependent, powershift	0PHMM
<input type="checkbox"/>	Without fan wheel for PTO, gearbox-dependent	0P4VR
<input type="checkbox"/>	Without flange coupling for PTO, gearbox-dependent, elastic	0PMCB
<input type="checkbox"/>	Function parameters for PTO; gearbox-dependent, driving operation	0P4WP
<input type="checkbox"/>	Without flange coupling for auxiliary output, dependent on PTO, elastic	0PMCD
<input type="checkbox"/>	Sector-specific parameterisation, general	0P4X0
<input type="checkbox"/>	Without electromechanical NA installation position	0PNXB

Towing, recovery and lashing

<input type="checkbox"/>	Central coupling jaw, integrated in bumper/front cross member, with lock pin	0P1MK
<input type="checkbox"/>	2 shackles on the front of the vehicle, shape C size 3	0P1S3

Paintworks

Paintwork, cab, top

<input type="checkbox"/>	Top coating, cab	0P6YB
--------------------------	------------------	-------

Paintwork, cab, bottom

<input type="checkbox"/>	Textured coating, step units	0P6X9
<input type="checkbox"/>	Textured coating, mudguard, behind cab	0P6YG
<input type="checkbox"/>	Textured coating, bumper, steel	0P6YQ

Paintwork, chassis

<input type="checkbox"/>	Without additional top coating on chassis	0PJTK
<input type="checkbox"/>	Top coating, rims, steel, white-aluminium	0P6YL

Other

<input type="checkbox"/>	Without MY 26 Budget TGS NN	YW543
--------------------------	-----------------------------	-------

Colour



□ Top coating, cab

FLAME RED RAL 3000

N



Technical data: TGM 18.250 4x2 BB CH / L08DAA04

Vehicle type: Vehicle type, platform truck and chassis (LK)

Cab: DN cab: the crew cab (narrow, extra long, normal height)

Drive Type: 4x2

Weights/loads		kg
TD026	Chassis weight with cab	6027
TD027	Chassis weight, front	3944
TD028	Chassis weight, rear	2083
TD029	Payload	11973
TD018	Statorily permissible gross vehicle weight	18000
TD025	Technically permissible gross vehicle weight	18000
TD031	Statorily permissible gross train weight	0
TD032	Statorily permissible trailer load	0

Frame		mm
TD009	Frame width at front	964.0
TD010	Frame width at the rear	864.0
TD078	Frame profile	270 x 70 x 7

Circle dimensions		m
TD055	Track circle diameter	15.5
TD056	Wall-to-wall turning circle diameter	17.0

Lengths		mm
TD071	Total length	8296.0
TD063	Front vehicle overhang	1530.0
TD057	Wheelbase between front axles	0
TD058	Wheelbase between leading axle and rear axle	0
TD059	Wheelbase between rear axles	0
TD060	Wheelbase between rear axle and trailing axle	0
TD064	Rear frame overhang	2325.0
TD072	Distance from first front axle to body	1604.0
TD067	Distance to kingpin from front axle, nominal position	-
TD074	Slew radius, front	-
TD075	Slew radius, rear	-
TD068	Coupling length	8127.0

Heights		mm
TD033	Maximum external height, unladen	3046.0
TD082	Total transport height, unladen	3046.0
TD034	Maximum external height, laden	2968.0
TD035	Frame height at theoretical rear wheelbase, unladen	1077.0
TD036	Frame height at theoretical rear wheelbase, laden	944.0
TD045	Raising from driving position, front	-
TD046	Lowering from driving position, front	-
TD047	Raising from driving position, rear	-
TD048	Lowering from driving position, rear	-

TD051 Height of fifth-wheel coupling above ground, unladen -

TD052 Height of fifth-wheel coupling above ground, laden -

Widths		mm
TD008	Width included rearview mirror	2981.0
TD001	Width over cab	2240.0

The technical data must be considered as an approximation. Some of the values are given in a simplified form. More detailed notes and descriptions can be found in the respective information in the overview. Contents and specifications have been compiled with the greatest possible care. Nevertheless, we do not assume responsibility for the data and values supplied being correct and up to date. Subject to errors and changes. MAN Truck & Bus AG is liable only in cases of intent, gross negligence or culpable breach of significant contractual obligations.