Refrigerated body + tail-lift



CHASSIS SPECIFICATIONS

Trade mark :	**MAN**
Model :	TGS 33.400 BB CH 6x4 Euro 2
G.V.W :	33 tons
Wheelbasis :	5100 mm

Day cab
Voltage 24 v
With underrun

BODY CFR IR 65 (51,4 m³ dual-temp – 20 Euro-pallets)

outer length : **8600** mm inner length : **8400** mm

outer width : **2600** mm inner width : **2454** mm


outer height : 2756 mm inner height : **2500** mm

Thickness of Panels
Floor : **141** mm Roof : **102** mm
Front : **117** mm Rear : **85** mm
Sides : **65** mm

Side wall laminate
Exterior : G.R.P. Interior : G.R.P. **(on 4 mm plywood)**

Apertures

Stainless steel rear frame 2 doors - Total opening
Opening priority to the right rear door
4 stainless steel locking gears >>> 2 per door
Back frame reinforced for off road use



1 single side door 1000*1950 (right hinged)
Location: right side at **155** mm from inner front bulkhead
With safety interior release

Floor

Grey antiskid GRP reinforced for trolleys
No wheel recess
2 Drain holes with siphon Ø 40 front L&R

Inside equipments



250 mm Aluminium kick strip

1 row universal steel Combi-rail 3009 (surface mounted) on side walls
Location: 1100 mm

1 movable & liftable bulkhead, with spring struts
With floor locking & trap door

Chassis equipments

Galvanized steel subframe, welded model - Height: 150 mm
Subframe reinforced for off road use
Subframe reinforced for tail-lft DH-LM30 according to MAN guidelines

1 side 3-step pull out ladder, with buzzer in cab



No rear ladder

Double aluminium sideguards
Plastic mudguards & mudflaps

General aspect

Bodywork : standard white RAL 9016
Outside capping in anodized aluminium
With reflective stickers
Tail-lift platform painted in white RAL 9016

Fridge equipments

Front bulkhead reinforced for THERMO KING TX-1300 R50 Spectrum
Roof reinforced for 2 evaporators S3
Multi-temp provision1
1 rear evaporator protection
Service catwalk + access ladder

Other equipments

2 Rubber buffers 490*110*47 on the rear frame
2 Rubber buffers 310*80 on the chassis

3 stainless steel spring door retainers

3 Internal led roof lights (1100 lumens) **with motion sensor**

2 multifunction LED lights on top rear frame

FRIDGE UNIT

THERMO KING TX-1300 R50 Spectrum S3-S3 Diesel / Electric 400 v

2 evaporators S3
Three-phase power 380 v
Refrigerant R452a
Standard control box in cab
Automatic defrosting
Extra battery + battery box included
Powered by vehicle's tank

1 temperature recorder TouchLog Premium in cab with printer

2 door switches >>> et the side door & at the rear right door

Fitting & commissioning included
15 meter electrical extension lead

TAIL-LIFT DHOLLANDIA

DH-LM 30
Capacity : **2000 kg**
Steel platform 2000 mm deep

With Manual **rollstops**
With supporting rollers

Tilting at all levels - Automatic tilting at the ground
Remote control + circuit breaker + rotary switch OAE030.BT.0
Internal remote control with spiral cable OAE001
Socket recessed into the roof at the rear right

24 months warranty (S340.24) - 58R03 compliant
Fitting & commissioning included