

INNOVATION BY TRADITION SINCE 1850



* picture similar, can include additional equipment

MEILLER rear tipper H436 22 m³

Pos. 10: rear tipper H436 22 m³

Model	<ul style="list-style-type: none"> MEILLER Classic rear tipper H436: <p>Tipper body: box-type tipper body inclined front wall and tailgate side walls with robust, circumferential top border inclined towards the inside chamfered edges in the front to ensure a better flow of material 150 mm higher front wall with side walls lower than 1,700 mm flush front and side walls with side wall height 1,700 mm and higher scissors-type stabiliser supports made of abrasion-resistant, shock-proof rubber adjustable front supports</p> <p>Subframe: welded box-type subframe made of high-strength fine-grained steel with longitudinal members, reinforced by a cross-type section at the rear</p> <p>MEILLER hydraulic system: oil tank, usable capacity of 60 litres operating pressure 275 bar tipping valve</p>	H3TYPH436
Veh. Basic	<ul style="list-style-type: none"> language on plates, lists and manuals: English (if available) suitable for a MAN chassis: sales name TGS wheelbase 2,980/1,400 cab OP2DL (cab NN) exhaust OP1BH+OP1BT (at side right) air intake OP0AY (vertical) emission standard Euro II/III type OP2UN (tipper) type of suspension leaf suspension drive 8x4 size of spare wheel 315/80 R 22.5 ride height cab OPBHE (640 mm) prepar. pneum.control in cab OP3KN (tipper) chassis overhang OP3EU (800 mm) PTO OP4QY (NH/4c - 2:30) size of tyres rear axle 315/80 R 22.5 mudguards 2nd steering axle OP1B8 (mudgu. 2.FA 1/2-shell) mudguards rear axle OP1AO+OP1AY (RA 1/4-shell ÜP) OEM-suppl. rear underr. protect. OP1FD+OP1FU (RUP w/o extens.) OEM-suppl. fix.elem. superstr. OP0X3 (fix.angles MEILLER) side marker lamps OP2BJ (with SML) OEM-supplied trailer coupling OP1MZ (ROCKINGER SK5) capacity 22 m³ tipper body length 6,000 mm 	H3SPR02 H3FFZG03 H3FVKB25 H3FRSD_2980_1400 H3FFHS42 H3FAPU64 H3FANS24 H3FEUN03 H3FART05 H3FFED01 H3FANT05 H3FFER01 H3FFAH05 H3FPNE23 H3FUBS54 H3FNAB57 H3FREI01 H3FKOL12 H3FKOT15 H3FUFS18 H3FBFA16 H3FSML10 H3FAKU65 H3VOL11 H3KBL22
Veh. Expert		
Tipp. body		

Offer number 67960-1

	<ul style="list-style-type: none"> tipper body width 2,300 mm side wall height 1,600 mm outside-positioned inclined top-hinged tailgate with grip lock (S1) flush tailgate hinges reinforcement of tipping bracket floor 10 mm STEELECT® 450* (HBW450) front wall 8 mm STEELECT® 450* (HBW450) side walls 8 mm STEELECT® 450* (HBW450) tailgate 6 mm STEELECT® 450* (HBW450) cab protection in accordance with FOPS regulations (not in combination with tarpaulin systems) preparation for tipper body heating preparation for spare wheel holder at the front wall on the left and right spare wheel holder at the front wall for tyre sizes 315/80 R 22.5 or 13 R 22.5 steps inside steps outside (not compliant with German accident prevention regulations) preparation for access ladder at the left and right side of the front wall access ladder with folding lower part at the left side of the front wall (compliant with German accident prevention regulations) 	H3KBB01 H3BWH06 H3RWF02 H3RWL01 H3KLV01 H3BOD04 H3WAN19 H3DAC04 H3HZV01 H3VBR01 H3ERH01 H3TRI00 H3TRA00 H3ALV00 H3LEI02
Accessori.	<ul style="list-style-type: none"> mudflaps under the tipper body (at the front and rear) rear light protection grid wheel chock holder(s) omission of pneumatic feed valve in cab pump pump 296 pump 296/1(115 cm³/rpm) yellow MEILLER labels (800 x 400 mm) at the front area of both side walls 	H3KSB03 H3RLS01 H3UKH01 H3GEB02 H3PUT96 H3PUM01 H3RAU01
Mounting	<ul style="list-style-type: none"> This MEILLER product is mounted by MEILLER Munich (Munich, Germany) in accordance with the general truck body directives, accident prevention regulations (German UVV) and road traffic legislation without major modifications at the chassis. The result is a functional, ready-for-use vehicle. In case of a high capacity utilization we reserve the right to change the mounting plant. colour of tipper body Eisengrau RAL 7011 one-colour painting of tipper body in standard colour painting of subframe in standard colour parameterisation hydraulic oil filling with mineral oil HLPD-22 (not for kit delivery) 1-year warranty excl. the incurring inspections (UVV inspections) 	H3MON01 Eisengrau RAL 7011 H3LKB02 H3HRL02 H3PAR02 H3OEL02 H3GAR01
Documents		

Customer special request:

- S14 chain tailgate outside width 2622mm
- rock breaker (floor and front wall) in 8mm HBW 450