

**Technical extent of delivery**

Code	Customer Special Request	Designation
001AA		steering arrangement, left
005UH		Wheelbase 1795+2505+1400 mm
006CI		rear frame overhang 800 mm
018KP		Engine D2676LF03 - 480 HP / 353 KW EURO2 - 2,300 Nm common rail
02AAG		Instrument panel km/h 'High-Line in colour'
021GG		Gearbox software MAN TipMatic Offroad (off-road deployment)
022QE		MAN TipMatic 12 28 OD gearbox
023EH		400l fuel tank on right side deleted – instead 960 liter fuel tank behind cabin
025ML		front axle VO-09/VO-09 straight
026EC		front springs parabolic 8.0 t
027AX		extended radiator and intercooler over 35 degrees ambient temperature
028EC		rear springs parabolic 13 t
028PA		Fit tandem axles
029GC		Propshafts for high load profile
03KAA		fuel tank fitted
030EE		steering wheel with height and inclination adjustment
032AB		MAN BrakeMatic (electronic brake system)
034EC		brake shoe width for rear axle 220 mm
034MH		hub-reduction rear axle HPD-1382/ HP-1352
035LF		Planetary axle ratio i = 4.33
037AC		with differential lock in rear axle
038GG		disc wheels 10 hole 9.00-22.5 on 1stFA TL
038JG		disc wheels 10-hole 9.00-22.5 on 2ndfront axle TL
038PG		disc wheels 10-hole 9.00-22.5 on 1stRA TL
038RG		disc wheels 10-hole 9.00-22.5 on 2ndRA TL
038XT		without spare wheel
042CY		EC tachograph electronic, automatic,2 drivers
045CA		MAN EasyStart for TipMatic
05NAE		front panel unlockable from inside
050NF		L cab 2240mm wide, 2280mm long
052AE		Storage box accessible from outside - flap unlocked from inside
058BA		seat coverings in standard quality
058NE		driver's seat static, longitudinal, seat back and height adjustment
059NA		co-driver's seat static, with longitudinal + seat back adjustment
068AS		door extension
080AE		door interior panelling washable
116AP		Visco fan with high cooling output
116AZ		Fan control for use in hot countries
118AC		air deflector to stop dust swirling
118EK		Short mounting base (engine only)

118MA	EDC engine regulation
119EH	General PTO parameterisation
123AC	guard plate for 1 tank
123CC	strainer for fuel tank
124AL	fuel filter
124AZ	Auxiliary fuel filter with water separator
150WR	Brushed aluminium insert on instrument panel
153KA	air conditioning system AC R134A without CFHC
159XS	without cab insulation NORDIC (against cold) for M, L and LX cab
194AB	operator's manual in English
201AR	air intake upswept with dry air filter / precleaner
201EM	Air filter cartridge with safety insert for heavy-duty deployment
201FA	fine dust and pollen filter
203EK	connection for external engine speedcontrol (ZDR)
205AN	air compressor 1-cylinder, 360 ccm
206EY	exhaust on rh side with tail pipe to rear
208AL	regulated rocker arm brake (EVBec)
210XX	Without flame-start/jump-start system
211FB	Single-disc clutch DBE 430, reinforced
227AC	rear axle breather upswept
230XW	Without front underride guard
230XX	Without rear underride guard
230YX	without lateral underride guard
233EM	3-part steel bumper
233FR	aeropackage for cab incl. loose spoiler and lateral deflectors and 2movable side flaps
236AF	cross member for trailer coupling
241AC	without platform mounting brackets
245XX	without spare wheel holder
256AA	steering wheel lock
256EA	emergency steering pump
258AC	antijackknife brake
258HA	anti-lock braking system (ABS)
259CA	disc brake for front axle
259CE	drum brake for rear axle
262AC	brake connection 2-line
272FA	Entry lighting for driver and co-driver
280AC	wiring for tank truck to ADR
280BA	Equipment for hazardous goods to ADR, type AT
280EU	stoneguard grille in front of radiator
281AB	medium-height design
283FS	Cab mounts on coil springs for 'L,LX,XL,XLX,XXL' cab
303AX	Lockable tank fastener - 1 u. ventilated for master key system
308CB	Electrical preparation for retrofitting a PTO

310EE	Halogen twin headlights H7 for right-hand traffic
310FA	2 spotlights on cab roof
311AA	protective grille for headlights headlights
318AI	LED clearance lamps
318AK	lateral marker lights
319AR	reading lamp for driver
321EC	central locking
324AC	Two-tone horn,electric
324CA	Two compressed air horns on the cab roof/roof spoiler
325AA	MAN Tronic (on-board computer)
325EC	Language 1 'English' for display in instrument panel
325FE	Language 2 'French' for display in instrument panel
326CK	trailer socket for anti-skid system on frame end
326CN	15-pin 24 V trailer socket on end offrame
327AF	battery main switch, mechanical
329CT	Two 12-V 175-Ah batteries
329ER	Battery box up to 180 Ah
329HC	Maintenance sign for batteries - 'maintenance-free'
331CY	28V three-phase alternator 120A 3360W Longlife Eco
339FP	Display on the dashboard for operating data
343AN	Acoustic warning system at end of frame for engaged reverse gear
345CV	Maximum electronic speed limitation 85 km/h
345EA	cruise control
346CA	charging pressure indicator
350NN	MAN Media Truck radio, 12 V with five-inch colour display
350XO	Without navigation SD
351US	AUX-IN/USB in the instrument panel
352CF	2 halogen revolving beacons on cab roof left and right
352WS	Revolving beacon, yellow
358AA	ETA electric cutout
362AH	Stabiliser on both rear axles
363AA	Stabiliser for front axle
370CM	air dryer
373AE	antifreeze effective down to -35 degrees
376FA	1 bunk with storage space (with aluminium frame).
376HA	Mattress for lower bunk
376KA	Bunk cover for bottom bunk
376XK	Without Mattress for upper bunk
380AC	windscreen of laminated glass tinted
380CA	door windows tinted
381AA	cab rear wall without windows
381CE	All-round curtain
381XC	Without curtain before bunks
385AT	Side windows tinted behind B-post

386AS	Mechanical lifting roof
387AF	Electric door window lifters for driver and co-driver
388AH	Roller blind for windscreen, mechanical
388AK	sun shade in front of windscreen
389AC	handles left and right (on B-post)
389AD	handles left and right (on A-post)
390CT	cup holder in dashboard
390XB	without pigeon hole on rear wall
390XX	without oddment box
392AH	kerb mirror, right
392CZ	Electrically heated and adjustable rear view mirror, heated wide-angle mirror
392HA	Mirror brackets for body width 2500-2600 mm width 2500 mm
392XJ	Without front mirror on co-driver's side/at centre
400AH	mudflap front
401EL	3-part synthetic mudguards for 2nd front axle
401EZ	Plastic mudguard three-part with flap (without spray reduction)
404AP	spray reducer
405AC	Bonding set, separate
405AK	hazard-warning sign
405AR	hazard-warning lamp
407AA	jack 25 t
411AA	1 chock
411AC	2nd chock
434CH	Smoking package
434DB	Interior design in Urban Concrete
44VCA	Crankcase ventilation closed
523AC	signs in English
538AE	plastic floor and engine tunnel covering
542FX	anti-noise measures are not in accordance with EU standard
542HS	aprons in wheel houses to prevent soiling of the engine
542NC	Registration as N3 vehicle, (GVW > 12t)
600AC	Fittings for right-hand traffic
798LF	Height over cab, unloaded up to 4000mm
798WF	vehicle cannot be registered to directive 2000/40/EC. Exceptions possible under cert. circumstances.
LQA08	steel bumper in 2-pack acrylic
LQA17	paint aeropackage acryl
LQA46	mudguards behind cab in 2-pack acrylic
LQA49	Door extension and step units, 2K acrylic
LQW01	chassis in water-based paint
LVS01	chassis graphite black RAL 9011 matt
LVS02	wheels White aluminium acrylic RAL 9006
LVS03	cab Pure white RAL 9010
LVS08	bumper Pure white RAL 9010

LVS17		aeropackage Pure white RAL 9010
LVS46		mudguards behind cab Pure white RAL 9010
LVS49		door extension and steps Pure white RAL 9010
80001		2 wahlweise 315/80R22,5 LENK-NAH TL
80002		2 wahlweise 315/80R22,5 LENK-NAH TL
90001		4 wahlweise 315/80R22,5 ANTR-S+G TL
90002		4 wahlweise 315/80R22,5 ANTR-S+G TL

00000		JOST fifth wheel 3,5"
00000		960 liter fuel tank behind cabin