

## Model : TGS 33.400 6X4 BB-WW

**Place of production:** MÜNCHEN

**Vehicle model:** TGS 33.400 6X4 BB-WW

**Basic vehicle** L 26W AE 12

**Delivery date:** 28.04.2021

### Technical extent of delivery

| Code  | Customer Special Request | Designation   |
|-------|--------------------------|---|
| 001AA |                          | steering arrangement, left  |
| 005OU |                          | Wheelbase 4500+1400 mm  |
| 006PK |                          | rear frame overhang 2500 mm                                       |
| 018SI |                          | engine D2066LF06 - 400 hp / 294 KW EURO2 - 1900 Nm Common-Rail    |
| 02AAG |                          | Instrument panel km/h 'High-Line in colour'                       |
| 022H3 |                          | Gearbox ZF 16 S 223 OD  |
| 023EH |                          | fuel tank 400l right  |
| 025MK |                          | front axle VO-09 straight   |
| 026EF |                          | front springs parabolic 9,5 t                                     |
| 027AP |                          | radiator and intercooler for over 35degrees ambient temperature   |
| 028FP |                          | rear springs parabolic 16 t                                       |
| 028PA |                          | Fit tandem axles  |
| 029GC |                          | Propshafts for high load profile                                  |
| 03KAA |                          | fuel tank fitted  |
| 030EE |                          | steering wheel with height and inclination adjustment             |
| 032AB |                          | MAN BrakeMatic (electronic brake system)                          |
| 034EC |                          | brake shoe width for rear axle 220 mm                             |
| 034MH |                          | hub-reduction rear axle HPD-1382/ HP-1352                         |
| 035KL |                          | Planetary axle ratio i = 4.00                                     |
| 037AC |                          | with differential lock in rear axle                               |
| 038GG |                          | disc wheels 10 hole 9.00-22.5 on 1stFA TL                         |
| 038PG |                          | disc wheels 10-hole 9.00-22.5 on 1stRA TL                         |
| 038RG |                          | disc wheels 10-hole 9.00-22.5 on 2ndRA TL                         |
| 038TG |                          | disc wheel 10-hole 9.00-22.5 as spare wheel TL                    |
| 042XY |                          | without electronic tachograph                                     |
| 05NAE |                          | front panel unlockable from inside                                |
| 050NN |                          | M cab 2240mm wide, 1880mm long                                    |
| 052XA |                          | without stowage boxes   |
| 058BA |                          | seat coverings in standard quality                                |
| 058NH |                          | driver's seat, high-comfort, with air suspension                  |
| 059NA |                          | co-driver's seat static, with longitudinal + seat back adjustment |
| 080AE |                          | door interior panelling washable                                  |
| 116AE |                          | visco fan   |

|       |   |
|-------|---|
| 118AC | air deflector to stop dust swirling                               |
| 118EK | Short mounting base (engine only)                                 |
| 118MA | EDC engine regulation   |
| 119EH | General PTO parameterisation                                      |
| 122QH | PTO NH/1C without flange f=0.91/1.09right side, horizontal        |
| 123AC | guard plate for 1 tank  |
| 123CC | strainer for fuel tank  |
| 124AL | fuel filter   |
| 124AZ | Auxiliary fuel filter with water separator                        |
| 150WR | Brushed aluminium insert on instrument panel                      |
| 153KA | air conditioning system AC R134A without CFHC                     |
| 159XS | without cab insulation NORDIC (against cold) for M, L and LX cab  |
| 194AB | operator's manual in English                                      |
| 194EC | additional operator's manual in FRENCH                            |
| 201AS | air intake raised with dry air filter                             |
| 201EM | Air filter cartridge with safety insert for heavy-duty deployment |
| 201FA | fine dust and pollen filter                                       |
| 203EK | connection for external engine speedcontrol (ZDR)                 |
| 205AN | air compressor 1-cylinder, 360 ccm                                |
| 206ET | exhaust on lh side with tail pipe towards rear                    |
| 208XD | without exhaust valve brake (EVB)                                 |
| 210XX | Without flame-start/jump-start system                             |
| 211FQ | Single-disc clutch DTE 430, reinforced                            |
| 227AC | rear axle breather upswept  |
| 230AH | rear underride guard, round                                       |
| 230XW | Without front underride guard                                     |
| 230YX | without lateral underride guard                                   |
| 233EM | 3-part steel bumper   |
| 234AX | towing coupling ROCKINGER SK5                                     |
| 236AF | cross member for trailer coupling                                 |
| 241AH | body attachment brackets bolted                                   |
| 245AE | spare-wheel holder on left side                                   |
| 256AA | steering wheel lock   |
| 258HA | anti-lock braking system (ABS)                                    |
| 259CC | drum brake for front axle   |
| 259CE | drum brake for rear axle  |
| 262AC | brake connection 2-line   |
| 272AT | Construction site step on front mudguard, driver's side           |
| 272FA | Entry lighting for driver and co-driver                           |
| 280AC | wiring for tank truck to ADR                                      |
| 280EU | stoneguard grille in front of radiator                            |
| 281AB | medium-height design  |
| 283FB | Cab mounts on coil springs for 'M' cab                            |
| 303AX | Lockable tank fastener - 1 u. ventilated for master key system    |

|       |   |
|-------|---|
| 310EE | Halogen twin headlights H7 for right-hand traffic         |
| 310FA | 2 spotlights on cab roof                                  |
| 318AA | marker lamps  |
| 318AK | lateral marker lights                                     |
| 319AR | reading lamp for driver                                   |
| 321EC | central locking   |
| 324AC | Two-tone horn,electric                                    |
| 325AA | MAN Tronic (on-board computer)                            |
| 325EC | Language 1 'English' for display in instrument panel      |
| 325FE | Language 2 'French' for display in instrument panel       |
| 326CK | trailer socket for anti-skid system on frame end          |
| 326CN | 15-pin 24 V trailer socket on end offrame                 |
| 327AF | battery main switch, mechanical                           |
| 329AS | Batteries 12 V 150 Ah, 2 units                            |
| 329ER | Battery box up to 175 Ah                                  |
| 329HC | Maintenance sign for batteries - 'maintenance-free'       |
| 331AB | Basic alternator  |
| 339FP | Display on the dashboard for operating data               |
| 345CV | Maximum electronic speed limitation 85 km/h               |
| 345EA | cruise control  |
| 346CA | charging pressure indicator                               |
| 350NN | MAN Media Truck radio, 12 V with five-inch colour display |
| 350XO | Without navigation SD                                     |
| 351US | AUX-IN/USB in the instrument panel                        |
| 352DX | 2 LED revolving beacons on cab roof, left and right       |
| 352WS | Revolving beacon, yellow                                  |
| 358AA | ETA electric cutout                                       |
| 362AF | Stabiliser on 2nd rear axle only                          |
| 363AA | Stabiliser for front axle                                 |
| 366CA | reinforced shock absorber for front axle                  |
| 370CM | air dryer   |
| 373AE | antifreeze effective down to -35 degrees                  |
| 376XH | Without Mattress for lower bunk                           |
| 376XK | Without Mattress for upper bunk                           |
| 376XL | No bunks for 'M', 'C', 'DK' cabs                          |
| 380AC | windscreen of laminated glass tinted                      |
| 380CA | door windows tinted                                       |
| 381AA | cab rear wall without windows                             |
| 381XC | Without curtain before bunks                              |
| 381YX | Without all-round curtain                                 |
| 384CD | Safety belt display, driver's side                        |
| 385AT | Side windows tinted behind B-post                         |
| 386XA | Without lifting roof                                      |
| 387AF | Electric door window lifters for driver and co-driver     |

|       |   |
|-------|---|
| 388AH | Roller blind for windscreen, mechanical   |
| 388AK | sun shade in front of windscreen  |
| 389AC | handles left and right (on B-post)  |
| 389AD | handles left and right (on A-post)  |
| 389CA | Grab handle on outside of cab roof, driver's side                                     |
| 390CT | cup holder in dashboard   |
| 390XX | without oddment box   |
| 392AH | kerb mirror, right  |
| 392CZ | Electrically heated and adjustable rear view mirror, heated wide-angle mirror         |
| 392HA | Mirror brackets for body width 2500-2600 mm width 2500 mm                             |
| 392XJ | Without front mirror on co-driver's side/at centre                                    |
| 400AH | mudflap front   |
| 401AS | mudguard cover for transfer   |
| 401CQ | Plastic mudguard rear (half-shell; without spray reduction)                           |
| 404AP | spray reducer   |
| 405AC | Bonding set, separate   |
| 405AK | hazard-warning sign   |
| 405AR | hazard-warning lamp   |
| 407AA | jack 25 t   |
| 411AA | 1 chock   |
| 434DB | Interior design in Urban Concrete   |
| 44VCA | Crankcase ventilation closed  |
| 523AC | signs in English  |
| 538AE | plastic floor and engine tunnel covering  |
| 542FX | anti-noise measures are not in accordance with EU standard                            |
| 542HS | aprons in wheel houses to prevent soiling of the engine                               |
| 542NC | Registration as N3 vehicle, (GVW > 12t)   |
| 600AC | Fittings for right-hand traffic   |
| 798LF | Height over cab, unloaded up to 4000mm  |
| 798WK | vehicle can be registered only as off-road vehicle to directive 70/156/EEC; note body |
| LQW01 | chassis in water-based paint  |
| LVS01 | chassis graphite black RAL 9011 matt  |
| LVS02 | wheels White aluminium acrylic RAL 9006   |
| LVS03 | cab Pure white RAL 9010   |
| 80001 | 2 wahlweise 315/80R22,5 LENK-S+G TL   |
| 90001 | 4 wahlweise 315/80R22,5 ANTR-S+G TL   |
| 90002 | 4 wahlweise 315/80R22,5 ANTR-S+G TL   |
| 90004 | 1 wahlweise 315/80R22,5 LENK-S+G TL   |

#### Weights:

Gross weight: 33000

1st front axle: 8000

2nd front axle: 0



3rd front axle: 0

Leading axle: 0

1st rear axle: 13000

2nd rear axle: 13000