

Vehicle description for: TGM 18.250 4x4 BB CH



Illustration can deviate

Vehicle standards

Product family	The new MAN Truck Generation
Model & Variant	TGM 18.250 4x4 BB CH
Engine family	D08R6
Vehicle type	Vehicle type, platform truck and chassis (LK)
Cab	DN cab: the crew cab (narrow, extra long, normal height)
Main wheel distance	4200 mm
Overhang	2125 mm
Steering configuration	Left

Vertical Load

	National Registration	Technical Load
Gross weight	17,500 kg	18,600 kg
Front axle	7,100 kg	7,100 kg
Rear axle	11,500 kg	11,500 kg

Horizontal Load

	National Registration	Technical Load
Gross train weight	0 kg	0 kg

The printed images in this offer are for explanatory purposes and may differ from the actual configuration.
For further product information on the tire selection "selectively", please contact our sales staff.

Vehicle characteristics

Basic characteristics

<input type="checkbox"/> Municipal vehicle version	0PBX1
<input type="checkbox"/> Chassis	0P2U9
<input type="checkbox"/> Chassis class, light/medium	0P2UB
<input type="checkbox"/> Destination: Jordan (JO)	0P3GV
<input type="checkbox"/> Merchant tonnage 18 t	0P8LF
<input type="checkbox"/> Basic layout of vehicle, all-round	0PGCU
<input type="checkbox"/> Frame type, high	0P2TP
<input type="checkbox"/> Vehicle type, platform truck and chassis (LK)	0P2UQ
<input type="checkbox"/> Left-hand-drive	0P3AS
<input type="checkbox"/> Right-hand traffic	0P3F5
<input type="checkbox"/> Vehicle documents in Arabic	0P2L0
<input type="checkbox"/> Labelling in English	0P8NM
<input type="checkbox"/> Cab position 480 mm (distance from frame lower edge to cab floor)	0PHBC

Registration

<input type="checkbox"/> Vehicle approval, N3G class	0P3JS
<input type="checkbox"/> Maximum speed limiter, 89 km/h, tolerance +1 km/h, electronic, engine speed regulation	0P2UJ
<input type="checkbox"/> Maximum vehicle noise level, 82 dB in acc. with UN/ECE-R 51.02	0PIND
<input type="checkbox"/> Height over cab, unloaded up to 4,000 mm	0PHA1
<input type="checkbox"/> Vehicle classification in accordance with regulation (EU) 2018/858	0PKAW

Documents

<input type="checkbox"/> European standard exhaust emission confirmation	0P2Q7
<input type="checkbox"/> Body manufacturer information sheet	0P2TN
<input type="checkbox"/> Without registration documentation, national	0P3B0

Application scope / transport tasks

<input type="checkbox"/> Special applications	0P6WS
<input type="checkbox"/> 311 Loading platform with crane	0P2RY
<input type="checkbox"/> Temperature range, vehicle deployment, warm country	0PHIB
<input type="checkbox"/> Case hardness of final drive Distribution	0P4F0
<input type="checkbox"/> Oil sump for gradeability, up to 60%	0P4F2

Lines, editions and packages

<input type="checkbox"/> Special request paintwork	0PJTD
<input type="checkbox"/> Without Individual Lion package	0PJT1

Horizontal and vertical loads

<input type="checkbox"/> 17,500 kg permitted gross load, vertical, nat. appr.	0P5O8
<input type="checkbox"/> 18,600 kg permitted gross load, vertical, tech.	0P5S7
<input type="checkbox"/> 18,600 kg permitted gross load, vertical, tech. Plus	0P8GT
<input type="checkbox"/> 7,100 kg permitted load on front axle, nat. appr.	0P5KQ
<input type="checkbox"/> 7,100 kg permitted load on front axle, tech.	0P5LK
<input type="checkbox"/> 7,100 kg permitted load on front axle, tech. Plus	0P8DY
<input type="checkbox"/> 11,500 kg permitted load on rear axle NatZu	0P5G7

- | | |
|--|-------|
| <input type="checkbox"/> 11,500 kg permitted load on rear axle, tech. | 0P5IJ |
| <input type="checkbox"/> 11,500 kg permitted load on rear axle, tech. Plus | 0P8BN |
| <input type="checkbox"/> 0kN D value | 0P8XD |

Notification texts

- | | |
|--|-------|
| <input type="checkbox"/> Note: Restricted steerability with engaged differential lock on front axle | 0PFZN |
| <input type="checkbox"/> Note: Max. 24,000 kg tech. permitted gross weight with engaged off-road reduction ratio in transfer case | 0PFZR |
| <input type="checkbox"/> Note: Difference of more than 2% in FA/RA rolling circumference may lead to perceptible tension in the driveline. | 0PHCX |
| <input type="checkbox"/> Without note (propshaft wear) | 0PJRV |

Chassis

Vehicle frame (wheelbase, overhang, ...)

- | | |
|---|-------|
| <input type="checkbox"/> Main wheelbase, 4,200 mm | 0P2ZQ |
| <input type="checkbox"/> Frame overhang, rear, 2,125 mm | 0P3DL |
| <input type="checkbox"/> Main frame side member thickness, 8 mm | 0P0Y6 |
| <input type="checkbox"/> Vehicle rear, straight end of frame | 0P0XT |

Exhaust system, air intake

- | | |
|--|-------|
| <input type="checkbox"/> Exhaust silencer, side, right | 0P1BH |
| <input type="checkbox"/> Exhaust tailpipe, towards middle of frame | 0P1BT |
| <input type="checkbox"/> Air intake, behind cab, raised | 0P0AY |
| <input type="checkbox"/> Exhaust silencer cover (styling) | 0PHCV |

Battery cases, batteries, alternator

- | | |
|--|-------|
| <input type="checkbox"/> Battery, 12 V, 175 Ah, 2 units, maintenance free | 0P0WA |
| <input type="checkbox"/> Three-phase alternator 28 V, 120 A, 3,360 W, Longlife Eco | 0P1BW |
| <input type="checkbox"/> Medium battery box, 2 batteries | 0P0WU |
| <input type="checkbox"/> Battery box, left | 0P0WO |
| <input type="checkbox"/> Main battery switch, mechanical | 0P0WF |
| <input type="checkbox"/> Safety cut-out | 0P1V2 |

Tanks and fuel line

- | | |
|--|-------|
| <input type="checkbox"/> Fuel tank capacity 300 l, right | 0P4E8 |
| <input type="checkbox"/> Fuel tank, right, steel | 0P4GN |
| <input type="checkbox"/> Tank cross-section, right, low | 0P4HF |
| <input type="checkbox"/> AdBlue tank capacity 27 l, right | 0P4CY |
| <input type="checkbox"/> AdBlue tank, right, plastic | 0P4HU |
| <input type="checkbox"/> Fuel tank cap, lockable for master key system | 0P4H5 |
| <input type="checkbox"/> Cap for AdBlue tank, lockable | 0P4GE |
| <input type="checkbox"/> Fuel pre-filter on the frame | 0PKN2 |

Frame attachments

- | | |
|--|-------|
| <input type="checkbox"/> Without underride protection, front | 0P1FM |
| <input type="checkbox"/> Without working platform | 0P0VH |
| <input type="checkbox"/> Without underride protection, side | 0P1FG |
| <input type="checkbox"/> Spare wheel, provisionally mounted | 0P1GR |

- | | | |
|--------------------------|--|-------|
| <input type="checkbox"/> | Final cross member, with hole pattern 160 x 100 mm | 0P1SB |
| <input type="checkbox"/> | Underride protection, rear, round | 0P1FD |
| <input type="checkbox"/> | Wheel chock, 1 unit, with retaining device | 0P1FO |
| <input type="checkbox"/> | Without body attachment brackets/thrust plates | 0P0X6 |

Pneumatic brakes, compressed-air generation, brake system

- | | | |
|--------------------------|---|-------|
| <input type="checkbox"/> | Air compressor, 1-cylinder, 238 ccm | 0P0AD |
| <input type="checkbox"/> | Air dryer, heated | 0P0B2 |
| <input type="checkbox"/> | Compressed-air treatment, pneumatically controlled | 0P0AB |
| <input type="checkbox"/> | Steel compressed-air tank | 0P0XH |
| <input type="checkbox"/> | Electronic brake system (EBS) | 0P0BL |
| <input type="checkbox"/> | Anti-lock braking system (ABS) | 0P0BE |
| <input type="checkbox"/> | Full brake assistant | 0P0CM |
| <input type="checkbox"/> | Without preparation for EBS Full control unit | 0PHPM |
| <input type="checkbox"/> | Engine brake, exhaust flap | 0P0BU |
| <input type="checkbox"/> | Drum brakes on front axle | 0P1IA |
| <input type="checkbox"/> | Drum brakes on rear axle | 0P1I5 |
| <input type="checkbox"/> | Parking brake control, next to driver's seat | 0P3KH |
| <input type="checkbox"/> | Parking brake with spring-type actuator on rear axles (incl. leading axle/ trailing axle) | 0PGBL |
| <input type="checkbox"/> | Parking brake, on front axle(s), pneumatic, additional, exhaustible | 0P0C1 |
| <input type="checkbox"/> | Hill-climbing brake braking function | 0P1TD |

Lights and acoustic signals on the chassis (rear lights, ...)

- | | | |
|--------------------------|---|-------|
| <input type="checkbox"/> | Rear lights | 0P2AQ |
| <input type="checkbox"/> | Acoust. Reversing warning system when reverse gear selected | 0P3CD |
| <input type="checkbox"/> | Light function test | 0P2AD |
| <input type="checkbox"/> | Side marker lights, LED | 0P2BJ |

Driveline/running gear

Engine, radiator

- | | | |
|--------------------------|--|-------|
| <input type="checkbox"/> | Diesel engine MAN D0836 LFL95, 184 kW (250 hp) output, 1,050 Nm torque, Euro 4 | 0P5ZG |
| <input type="checkbox"/> | Fuel filter, heated, for fuels up to Cleanliness Class 21 | 0PHIF |
| <input type="checkbox"/> | Fuel pre-filter, with oil separator/water trap, heated | 0P0AU |
| <input type="checkbox"/> | Without torque reduction | 0P0G5 |
| <input type="checkbox"/> | Engine dry-air filter, with safety insert | 0P0B8 |
| <input type="checkbox"/> | Ventilation, crankcase, closed | 0P8PM |
| <input type="checkbox"/> | Anti-noise skirt, engine | 0P2E7 |
| <input type="checkbox"/> | Engine cooler, normal length | 0P4XX |
| <input type="checkbox"/> | Radiator protection, lower | 0P1XE |
| <input type="checkbox"/> | Engine oil dipstick and digital oil level gauge | 0P0B6 |
| <input type="checkbox"/> | Antifreeze, down to -32 °C | 0P0AK |
| <input type="checkbox"/> | Service product level indicator and intake system vacuum | 0P3KT |

Gearbox, clutch

- | | | |
|--------------------------|---|-------|
| <input type="checkbox"/> | Manually operated gearbox, MAN 09.13 OD | 0P5VE |
| <input type="checkbox"/> | Gearbox for normal percentage of overrun during driving operation | 0PGDA |
| <input type="checkbox"/> | Manual gearbox operation, Single-H, group switch | 0P3KM |

<input type="checkbox"/> Transfer case MAN G102 with on-road and off-road gear	0P4XH
<input type="checkbox"/> Transfer case lock management, electronic (VSM)	0P0FU
<input type="checkbox"/> Single-disc clutch, 395 mm, dry	0P0DS

Wheels, tyres

<input type="checkbox"/> Required tyre speed index G	0PFWA
<input type="checkbox"/> Tyres for front axle, Goodyear 295/80R22.5 OMNITRAC S Steering-Road+Offroad TL	0PGJZ
<input type="checkbox"/> Rim type, front axle, steel, single-part	0P0P0
<input type="checkbox"/> Rim size, front axle, 10-hole, 9.00x22.5	0P0NI
<input type="checkbox"/> Wheel nut cover ring, front axle	0P0PR
<input type="checkbox"/> Tyres for rear axle, Goodyear 295/80R22.5 OMNITRAC D Drive-Road+Offroad TL	0PGEB
<input type="checkbox"/> Rim type, rear axle, steel, single-part	0P0OO
<input type="checkbox"/> Rim size, rear axle, 10-hole, 8.25x22.5	0P0MQ
<input type="checkbox"/> Spare wheel, in accordance with configuration for front axle tyres	0P0MH
<input type="checkbox"/> Tyre inflation hose, 20 m, with pressure gauge	0P1UA

Axles

<input type="checkbox"/> 4x4	0P3B2
<input type="checkbox"/> Steering ratio, standard	0P1JX
<input type="checkbox"/> Steering oil tank with electrical measuring sensor	0P1JV
<input type="checkbox"/> Front axle, 9,000 kg, planetary axle without drive shaft, straight, steered, not liftable	0P5ES
<input type="checkbox"/> Front axle as planetary axle, driven, engageable	0P1GY
<input type="checkbox"/> Mudguard, front axle	0P1AT
<input type="checkbox"/> Rear axle, 13,000 kg, planetary axle without drive shaft, straight, not steered, not liftable	0P4ZN
<input type="checkbox"/> Twin tyre on rear axle	0P1HN
<input type="checkbox"/> Transfer mudguard, rear axle	0P1AQ
<input type="checkbox"/> Axle ratio, $i = 5.33$	0P0DD
<input type="checkbox"/> Differential locks on driven rear axles	0P0DI
<input type="checkbox"/> Differential locks on driven front axles	0P0DK
<input type="checkbox"/> Warning buzzer when front axle locks are engaged	0P0DQ
<input type="checkbox"/> Mudguard enlargement	0P1W5

Axle control system and suspension

<input type="checkbox"/> Suspension type for front axles and driven rear axles, leaf/leaf (BB)	0P2YB
<input type="checkbox"/> Leaf-spring suspension on front axle, parabolic, 2-leaf, steel	0P1JD
<input type="checkbox"/> Leaf-spring suspension on rear axle, parabolic, 4-leaf, steel	0PGBF
<input type="checkbox"/> Spring load-bearing capacity front axle 7,500 kg	0P5CZ
<input type="checkbox"/> Spring load-bearing capacity of rear axle, 11,500 kg	0P5BT
<input type="checkbox"/> Shock absorbers on front axle	0P1M4
<input type="checkbox"/> Shock absorbers on rear axle	0P1LQ
<input type="checkbox"/> Stabiliser, front axle	0P1LD
<input type="checkbox"/> Stabiliser, rear axle	0P1LA
<input type="checkbox"/> Axle location system not as wishbone	0P6ZY
<input type="checkbox"/> Without trailer air suspension control	0PHN2

Cab

Cab and cab exterior

<input type="checkbox"/> DN cab: the crew cab (narrow, extra long, normal height)	0P2DE
<input type="checkbox"/> Cab mount, Comfort	0P1V9
<input type="checkbox"/> Cab tilt mechanism, manual	0P1V6
<input type="checkbox"/> Tilting roof, mechanical	0P1VW
<input type="checkbox"/> Bumper, steel, 3 pieces	0P1SG
<input type="checkbox"/> Front step, integrated, with grab option	0P1VE
<input type="checkbox"/> Windscreen, composite safety glass, tinted	0P1X0
<input type="checkbox"/> Sunblind, in front of windscreen	0P1WK
<input type="checkbox"/> Wiper system for windscreen	0P1WG
<input type="checkbox"/> Wiper activation, manual	0P1UL
<input type="checkbox"/> Step unit, hinged	0P1V0
<input type="checkbox"/> Central locking, no remote control	0P1WS
<input type="checkbox"/> Vehicle key, 2 units	0P3JT
<input type="checkbox"/> No door extension	0P1WV
<input type="checkbox"/> Door labelling, according to trade tonnage of vehicle	0P2DQ
<input type="checkbox"/> Door windows, tinted	0P1WO
<input type="checkbox"/> Door window, safety glass	0P1WM
<input type="checkbox"/> Cab rear wall, no window	0P1VD

Lights and acoustic signals on cab exterior (headlights, horn, ...)

<input type="checkbox"/> Without light and headlight package	0PKWU
<input type="checkbox"/> Front headlights, H7	0P1ZN
<input type="checkbox"/> Daytime driving lights with rear lights, LED	0P2BQ
<input type="checkbox"/> Fog lights, H7	0P2AH
<input type="checkbox"/> Turn signal lights, sides, bulb	0P1Z6
<input type="checkbox"/> Headlight beam regulator, manual	0P2AC
<input type="checkbox"/> Driving-light control, manual	0P1ZF
<input type="checkbox"/> Contour lights, bulb, 2 units	0P2BT
<input type="checkbox"/> Comfort indicator function, can be activated	0P1ZW
<input type="checkbox"/> Horn, single-tone, electrical	0P1W0
<input type="checkbox"/> Switch and electrical interface at cab isolation point for revolving beacon at rear of vehicle	0PJRN

Mirrors and mirror replacements

<input type="checkbox"/> Without mirror package	0PKWV
<input type="checkbox"/> Exterior rear-view mirror, electrically adjustable	0P2CA
<input type="checkbox"/> Kerb mirror, right, electrically adjustable	0P2CG
<input type="checkbox"/> Front mirror, mechanical adjustment	0P2CJ
<input type="checkbox"/> Mirror housing, not painted	0P2CP
<input type="checkbox"/> Vehicle components, suitable for body width larger than 2,400 mm to 2,600 mm	0P2CT

Seats

<input type="checkbox"/> Seat covers, fabric, standard	0P2PQ
<input type="checkbox"/> Without driver's seat package	0PKXV
<input type="checkbox"/> Comfort driver's seat, air-sprung	0P2P2
<input type="checkbox"/> Driver's seat heating	0P2PX
<input type="checkbox"/> Adjustment of seat belt height, driver's seat	0P4XQ
<input type="checkbox"/> Without co-driver's seat package	0PKXU
<input type="checkbox"/> Comfort co-driver's seat, air-sprung	0P2OK
<input type="checkbox"/> Crew area without seats, slotted floor, for subsequent installation of seating options	0P2Q0

- | | |
|--|-------|
| <input type="checkbox"/> Indicator, seat belt, 1st row of seats, acoustic and visual | 0P8L1 |
|--|-------|

Driver's workplace

- | | |
|--|-------|
| <input type="checkbox"/> Multi-function steering wheel, adjustable height and angle | 0P2GD |
| <input type="checkbox"/> Steering wheel, with parking position | 0P2GE |
| <input type="checkbox"/> Steering lock | 0P3JZ |
| <input type="checkbox"/> Instrumentation, Basic km/h | 0P3L3 |
| <input type="checkbox"/> Analogue tachograph, CONTINENTAL | 0P2KW |
| <input type="checkbox"/> Tachograph, calibrated | 0P2KG |
| <input type="checkbox"/> Socket, cab centre, 2 units, 12 V and 24 V | 0P2HX |
| <input type="checkbox"/> Cigarette lighter | 0P2IH |
| <input type="checkbox"/> Control panel MAN EasyControl Engine, 2 functions, operable from outside with door open | 0PGB5 |
| <input type="checkbox"/> Single DIN slots, 4 units, roof space, front | 0P2FJ |
| <input type="checkbox"/> Without storage tray next to seat | 0PJRS |

Cab air-conditioning system

- | | |
|---|-------|
| <input type="checkbox"/> Air-conditioning system, manual | 0P2NU |
| <input type="checkbox"/> Pre-separator (cyclone filter) for interior air intake | 0P2O7 |

Cab interior

- | | |
|--|-------|
| <input type="checkbox"/> Colour scheme for interior styling, dark | 0P2I6 |
| <input type="checkbox"/> Interior styling analogous to colour scheme | 0PGBT |
| <input type="checkbox"/> Without driver's workplace package, Comfort | 0PKXT |
| <input type="checkbox"/> Windscreen roller blind, internal | 0P2FE |
| <input type="checkbox"/> Without interior lighting package | 0PKNF |
| <input type="checkbox"/> Interior light, central | 0PHA6 |
| <input type="checkbox"/> Reading light, 1 unit, driver's side | 0P2IQ |
| <input type="checkbox"/> Entry lighting | 0P2IO |
| <input type="checkbox"/> Entry handles, standard | 0PHPK |
| <input type="checkbox"/> Door interior cladding, washable | 0P2IA |
| <input type="checkbox"/> Without stowage and storage space package | 0PKXS |
| <input type="checkbox"/> Storage, instrument panel in middle section, open | 0P2HK |
| <input type="checkbox"/> Multi-purpose storage box, centre of crew cab, in front of 2nd row of seats | 0P2ES |
| <input type="checkbox"/> Grab handle, above door, internal, 2 units, 1 right and 1 left | 0P2G2 |

Accessories and tools

- | | |
|--|-------|
| <input type="checkbox"/> Without accessories and tools package | 0PKXA |
| <input type="checkbox"/> Vehicle toolkit | 0P2TX |
| <input type="checkbox"/> First aid kit | 0P3F3 |
| <input type="checkbox"/> Warning triangle, 1 units | 0P3FI |
| <input type="checkbox"/> Hazard warning light, 1 units, with continuous light function | 0P3FF |
| <input type="checkbox"/> Jack, 10,000 kg | 0P3F7 |

Intelligent Truck

Assistance systems

- | | |
|---|-------|
| <input type="checkbox"/> Electronic Stability Program (ESP) | 0P1TN |
| <input type="checkbox"/> Anti-slip control (ASR) | 0P1T2 |

<input type="checkbox"/> Tempomat (cruise control, CC)	0P1TR
<input type="checkbox"/> Road speed limiter, adjustable, limiter (engine speed regulation)	0P0C3
<input type="checkbox"/> Without advanced emergency braking system	0P1U5
<input type="checkbox"/> Without driving fitness detection system	0PHN5
<input type="checkbox"/> Without Front Detection	0PHNA
<input type="checkbox"/> Without traffic sign recognition	0PHNE
<input type="checkbox"/> Without Reversing Motion System	0PHNV
<input type="checkbox"/> Without distance warning system	0PKA0

Infotainment (radio,...)

<input type="checkbox"/> Radio preparation, 12 V	0P2M4
<input type="checkbox"/> Loudspeaker, door, 2 units, 1 left and 1 right	0P2ME
<input type="checkbox"/> No navigation map	0P2N2
<input type="checkbox"/> English additionally for display	0P2JQ

Bodies/interfaces

Interfaces to semitrailer (e.g. fifth-wheel coupling, brake connection,...)

<input type="checkbox"/> Without trailer brake connection behind cab	0P1O3
<input type="checkbox"/> No fifth-wheel coupling	0P1RJ
<input type="checkbox"/> Without sensing of the fifth-wheel coupling	0PHN7

Interfaces to trailer (e.g. trailer coupling, brake connections,...)

<input type="checkbox"/> Without trailer/towing coupling on final cross member	0P1NQ
<input type="checkbox"/> Without trailer brake connection at end of frame, centre	0P1O0
<input type="checkbox"/> Without trailer socket at frame end	0P1OW
<input type="checkbox"/> Without trailer socket for anti-lock brake system (ABS)	0P1O9

Ex works bodies and interfaces to bodies (e.g. tipper indicator...)

<input type="checkbox"/> Preparation for engine start/stop facility, under front panel	0P0K8
<input type="checkbox"/> Interface for data exchange with body (customer-specific control module) and intermediate engine speed (ZDR), front area of cab and behind cab	0PHPE
<input type="checkbox"/> Interface for vehicle data (FMS)	0P2J3
<input type="checkbox"/> Y-adapter for rear lights	0P2C1
<input type="checkbox"/> Electrical preparation for keypad, body control	0PINX

PTOs

<input type="checkbox"/> Without fan wheel for PTO, gearbox-dependent	0P4VR
<input type="checkbox"/> Sector-specific parameterisation, general	0P4X0

Towing, recovery and lashing

<input type="checkbox"/> Central coupling jaw, integrated in bumper/front cross member, with lock pin	0P1MK
---	-------

Paintworks

Paintwork, cab, top

<input type="checkbox"/> Top coating, cab	0P6YB
---	-------

Paintwork, cab, bottom

<input type="checkbox"/>	Textured coating, step units	0P6X9
<input type="checkbox"/>	Textured coating, mudguard, behind cab	0P6YG
<input type="checkbox"/>	Textured coating, bumper, steel	0P6YQ

Paintwork, chassis

<input type="checkbox"/>	Top coating, chassis	0P6YC
<input type="checkbox"/>	Top coating, rims, steel, white-aluminium	0P6YL

Colour

<input type="checkbox"/>	Top coating, chassis	GRAPHITE BLACK RAL 9011	W
<input type="checkbox"/>	Top coating, cab	TRAFFIC WHITE RAL 9016	N

Technical data: TGM 18.250 4x4 BB CH / L38DAA03

Vehicle type: Vehicle type, platform truck and chassis (LK)

Cab: DN cab: the crew cab (narrow, extra long, normal height)

Drive Type: 4x4

Lengths		mm
TD071	Total length	7007.0
TD063	Front vehicle overhang	1607.0
TD057	Wheelbase between front axles	0
TD058	Wheelbase between leading axle and rear axle	0
TD059	Wheelbase between rear axles	0
TD060	Wheelbase between rear axle and trailing axle	0
TD064	Rear frame overhang	725.0
TD072	Distance from first front axle to body	1173.0
TD067	Distance to kingpin from front axle, nominal position	3525.0
TD074	Slew radius, front	2560.0
TD075	Slew radius, rear	2212.0
TD068	Coupling length	-

Widths		mm
TD008	Width included rearview mirror	2981.0
TD001	Width over cab	2440.0

Frame		mm
TD009	Frame width at front	942.0
TD010	Frame width at the rear	762.0
TD078	Frame profile	270 x 85 x 8

Heights		mm
TD033	Maximum external height, unladen	3958.0
TD082	Total transport height, unladen	3958.0
TD034	Maximum external height, laden	3891.0
TD035	Frame height at theoretical rear wheelbase, unladen	1011.0
TD036	Frame height at theoretical rear wheelbase, laden	981.0
TD045	Raising from driving position, front	0.0
TD046	Lowering from driving position, front	0.0
TD047	Raising from driving position, rear	145.0
TD048	Lowering from driving position, rear	90.0
TD051	Height of fifth-wheel coupling above ground, unladen	1320.0
TD052	Height of fifth-wheel coupling above ground, laden	1290.0

Circle dimensions		m
TD055	Track circle diameter	Error: 204
TD056	Wall-to-wall turning circle diameter	Error: 204

The technical data must be considered as an approximation. Some of the values are given in a simplified form. More detailed notes and descriptions can be found in the respective information in the overview. Contents and specifications have been compiled with the greatest possible care. Nevertheless, we do not assume responsibility for the data and values supplied being correct and up to date. Subject to errors and changes. MAN Truck & Bus AG is liable only in cases of intent, gross negligence or culpable breach of significant contractual obligations.