



* picture similar, can include additional equipment

MEILLER rear tipper H436 20 m³



Pos. 10: rear tipper H436 20 m³

Model	MEILLER Classic rear tipper H436:	H3TYPH436
	Tipper body: box-type tipper body inclined front wall and tailgate side walls with robust, circumferential top border inclined towards the inside chamfered edges in the front to ensure a better flow of material 150 mm higher front wall with side walls lower than 1,700 mm flush front and side walls with side wall height 1,700 mm and higher scissors-type stabiliser supports made of abrasion-resistant, shock-proof rubber adjustable front supports Subframe: welded box-type subframe made of high-strength fine-grained steel with longitudinal members, reinforced by a cross-type section at the rear MEILLER hydraulic system: oil tank, usable capacity of 60 litres operating pressure 275 bar tipping valve	
Veh. Basic	- language on plates, lists and manuals: English (if available) - suitable for a MAN chassis: - sales name TGS - wheelbase 2,505/1,400 - cab 0P2DL (cab NN) - exhaust 0P1BH+0P1BT (at side right) - air intake 0P0AY (vertical) - emission standard Euro II/III - type 0P2UN (tipper) - type of suspension leaf suspension - drive 8x4	H3SPR02 H3FFZG03 H3FVKB25 H3FRSD_2505_1400 H3FFHS42 H3FAPU64 H3FANS24 H3FEUN03 H3FART05 H3FFED01 H3FANT05 H3FFER01
Veh.Expert	- size of spare wheel 315/80 R 22.5 - ride height cab 0PHBE (640 mm) - Vorber. Steuerung im Fahrerh. 0P3KN (tipper) - chassis overhang 0P3EU (800 mm) - PTO 0P4QS (NH/4c - 2:30) - size of tyres rear axle 315/80 R 22.5 - mudguards 2nd steering axle 0P1B8 (mudgu. 2.FA 1/2-shell) - mudguards rear axle 0P1AQ+0P1B6 (RA transport) - OEM-suppl.side underr.protect. 0P1FG (w/o SUP) - OEM-suppl.rear underr.protect. 0P1FD+0P1FU (RUP w/o extens.)	H3FFAH05 H3FPNE23 H3FUBS54 H3FNAB58 H3FREI01 H3FKOL12 H3FKOT11 H3FSSV09 H3FUF518
Tipp. body	- OEM-suppl. fix.elem. superstr. 0P0X3 (fix.angles MEILLER) - side marker lamps 0P2BJ (with SML) - capacity 20 m³ - tipper body length 5,500 mm	H3FBFA16 H3FSML10 H3VOL09 H3KBL17

Accessories	• tipper body width 2,300 mm	H3KBB01
	• side wall height 1,600 mm	H3BWH06
	• outside-positioned inclined top-hinged tailgate with grip lock (S1)	H3RWF02
	• flush tailgate hinges	H3RWL01
	• floor 8 mm BS 50	H3BOD10
	• front wall 6 mm BS 50	H3WAN14
	• side walls 6 mm BS 50	
	• tailgate 6 mm BS 70	
	• cab protection up to upper cab edge (not in combination with sliding tarpaulin)	H3DAC01
	• preparation for tipper body heating	H3HZV01
	• preparation for spare wheel holder at the front wall on the left and right	H3VBR01
	• spare wheel holder at the front wall for tyre sizes 315/80 R 22.5 or 13 R 22.5	H3ERH01
	• steps inside	H3TRI00
	• steps outside (not compliant with German accident prevention regulations)	H3TRA00
	• preparation for access ladder at the left and right side of the front wall	H3ALV00
	• 1/4-shell steel mudguards without spray suppression mats (not compliant with EC regulations)	H3KOT04
	• mudflaps under the tipper body (at the front and rear)	H3KSB03
	• wheel chock holder(s)	H3UKH01
	• omission of pneumatic feed valve in cab	H3GEB02
Mounting	• pump 296	H3PUT96
	• pump 296/1 (115 cm ³ /rpm)	H3PUM01
	• without MEILLER labels	H3RAU00
	• Delivery as a pre-mounted kit as follows: pre-mounted kit (tipper body "and subframe already assembled) as well as mounting parts; in" accordance with the general truck body directives	H3MON05
	The responsibility for the CE marking in compliance with the machinery directive 2006/42/EG lies with the superstructure manufacturer.	
	• colour of tipper body Reinweiss RAL 9010	Reinweiss RAL 9010
	• one-colour painting of tipper body in standard colour	H3LKB01
	• colour of subframe Schwarzgrau RAL 7021	Schwarzgrau RAL 7021
	• painting of subframe in standard colour	H3HRL02
	• parameterisation	H3PAR02
Documents	• without hydraulic oil filling	H3OEL01
	• 1-year warranty excl. the incurring inspections (UVV inspections)	H3GAR01