* picture similar, can include additional equipment

MEILLER rear tipper H436 20 m^3

Pos. 10: rear tipper H436 20 m³

Model	• MEILLER Classic rear tipper H436: Tipper body: box-type tipper body inclined front wall and tailgate side walls with robust, circumferential top border inclined towards the inside chamfered edges in the front to ensure a better flow of material 150 mm higher front wall with side walls lower than 1,700 mm flush front and side walls with side wall height 1,700 mm and higher scissors-type stabiliser supports made of abrasion-resistant, shock-proof rubber adjustable front supports Subframe: welded box-type subframe made of high-strength fine-grained steel with longitudinal members, reinforced by a cross-type section at the rear MEILLER hydraulic system: oil tank, usable capacity of 60 litres operating pressure 275 bar tipping valve	H3TYPH436
	• language on plates, lists and manuals: English (if available)	H3SPR02
Veh. Basic	• suitable for a MAN chassis:	H3FFZG03
	• sales name TGS	H3FVKB25
	• wheelbase 2,505/1,400	H3FRSD_2505_1400
	• cab 0P2DL (cab NN)	H3FFHS42
	• exhaust 0P1BH+0P1BT (at side right)	H3FAPU64
	• air intake 0P0AY (vertical)	H3FANS24
	• emission standard Euro II/III	H3FEUN03
	• type 0P2UN (tipper)	H3FART05
	• type of suspension leaf suspension	H3FFED01
	• drive 8x4	H3FANT05
	• size of spare wheel 315/80 R 22.5	H3FFER01
Veh.Expert	• ride height cab 0PHBE (640 mm)	H3FFAH05
	• Vorber. Steuerung im Fahrerh. 0P3KN (tipper)	H3FPNE23
	• chassis overhang 0P3EU (800 mm)	H3FUBS54
	• PTO 0P4QS (NH/4c - 2:30)	H3FNAB58
	• size of tyres rear axle 315/80 R 22.5	H3FREI01
	• mudguards 2nd steering axle 0P1B8 (mudgu. 2.FA 1/2-shell)	H3FKOL12
	• mudguards rear axle 0P1AQ+0P1B6 (RA transport)	H3FKOT11
	• OEM-suppl.side underr.protect. 0P1FG (w/o SUP)	H3FSSV09
	• OEM-suppl.rear underr.protect. 0P1FD+0P1FU (RUP w/o extens.)	H3FUFS18
	• OEM-suppl. fix.elem. superstr. 0P0X3 (fix.angles MEILLER)	H3FBFA16
	• side marker lamps 0P2BJ (with SML)	H3FSML10
Tipp. body	• capacity 20 m³	H3VOL09
	• tipper body length 5,500 mm	H3KBL17

	• tipper body width 2,300 mm	H3KBB01
	• side wall height 1,600 mm	H3BWH06
	• outside-positioned inclined top-hinged tailgate with grip lock (S1)	H3RWF02
	• flush tailgate hinges	H3RWL01
	• floor 8 mm BS 50	H3BOD10
	• front wall 6 mm BS 50 side walls 6 mm BS 50 tailgate 6 mm BS 70	H3WAN14
	• cab protection up to upper cab edge (not in combination with sliding tarpaulin)	H3DAC01
	• preparation for tipper body heating	H3HZV01
	• preparation for spare wheel holder at the front wall on the left and right	H3VBR01
	• spare wheel holder at the front wall for tyre sizes 315/80 R 22.5 or 13 R 22.5	H3ERH01
	• steps inside	H3TRI00
	• steps outside (not compliant with German accident prevention regulations)	H3TRA00
	• preparation for access ladder at the left and right side of the front wall	H3ALV00
Accessor.	• 1/4-shell steel mudguards without spray suppression mats (not compliant with EC regulations)	H3KOT04
	• mudflaps under the tipper body (at the front and rear)	H3KSB03
	• wheel chock holder(s)	H3UKH01
	• omission of pneumatic feed valve in cab	H3GEB02
	• pump 296	H3PUT96
	• pump 296/1 (115 cm^3/rpm)	H3PUM01
	• without MEILLER labels	H3RAU00
Mounting	• Delivery as a pre-mounted kit as follows: pre-mounted kit (tipper body "and subframe already assembled) as well as mounting parts; in" accordance with the general truck body directives The responsibility for the CE marking in compliance with the machinery directive 2006/42/EG lies with the superstructure manufacturer.	H3MON05
	• colour of tipper body Reinweiss RAL 9010	Reinweiss RAL 9010
	• one-colour painting of tipper body in standard colour	H3LKB01
	• colour of subframe Schwarzgrau RAL 7021	Schwarzgrau RAL 7021
	• painting of subframe in standard colour	H3HRL02
	• parameterisation	H3PAR02
	• without hydraulic oil filling	H3OEL01
Documents	• 1-year warranty excl. the incurring inspections (UVV inspections)	H3GAR01